



Gnome::Gtk3::FileChooserDialog

Table of Contents

- 0.1 [FileChooserDialog — A file chooser dialog](#)
- 1 [Synopsis](#)
- 2 [Methods](#)
- 2.1 [\[gtk_file_chooser_\] dialog_new_two_buttons](#)
- 2.2 [new](#)

```
unit class Gnome::Gtk3::FileChooserDialog;  
also is Gnome::Gtk3::Dialog;
```

FileChooserDialog — A file chooser dialog

Synopsis

```
use Gnome::Gtk3::Dialog;  
use Gnome::Gtk3::FileChooserDialog;  
  
my Gnome::Gtk3::FileChooserDialog $fchoose .= new(:build-id<save-dialog>);  
  
# show the dialog  
my Int $response = $fchoose.gtk-dialog-run;  
if $response == GTK_RESPONSE_ACCEPT {  
    ...  
}  
  
# when dialog buttons are pressed hide it again  
$fchoose.hide;
```

Methods

[gtk_file_chooser_] dialog_new_two_buttons

```
method gtk_file_chooser_dialog_new_two_buttons (  
    Str $title, N-GObject $parent-window, int32 $file-chooser-action,  
    Str $first_button_text, int32 $first-button-response,  
    Str $secnd-button-text, int32 $secnd-button-response,  
    OpaquePointer $stopper  
    --> N-GObject  
)
```

Creates a new filechooser dialog widget. It returns a native object which must be stored in another object. Better, shorter and easier is to use `.new(. . .)`. See info below.

new

```
multi method new ( Str :$title! )
```

Create a filechooser dialog with given title. There will be only two buttons `:bt1text` and `:bt2text`. These are by default `Cancel` and `Accept`. Their response types are given by `:bt1response` and `:bt2response`. Defaults for these are `GTK_RESPONSE_CANCEL` and `GTK_RESPONSE_ACCEPT` respectively.

The filechooser action is set with `:action` which has `GTK_FILE_CHOOSER_ACTION_OPEN` as its default.

The parent window is set by `:window` and is by default `Any`.

The values are defined in `Gnome::Gtk3::Dialog` and `GtkFileChooser`.

```
multi method new ( :$widget! )
```

Create a filechooser dialog using a native object from elsewhere. See also `Gnome::GObject::Object`.

```
multi method new ( Str :$build-id! )
```

Create a filechooser dialog using a native object from a builder. See also `Gnome::GObject::Object`.

Generated using `Pod::Render`, `Pod::To::HTML`, `Camelia™` (butterfly) is © 2009 by Larry Wall