



Gnome::Gtk3::ComboBox

Table of Contents

- 0.1 [ComboBox](#) — A widget used to choose from a list of items
 - 1 [Synopsis](#)
 - 2 [Methods](#)
 - 2.1 [\[gtk_combo_box_\] get_active](#)
 - 2.2 [\[gtk_combo_box_\] set_active](#)
 - 2.3 [\[gtk_combo_box_\] get_active_id](#)
 - 2.4 [\[gtk_combo_box_\] set_active_id](#)
 - 2.5 [new](#)

```
unit class Gnome::Gtk3::ComboBox;  
also is Gnome::Gtk3::Bin;
```

ComboBox — A widget used to choose from a list of items

Synopsis

```
# Get a fully designed combobox  
my Gnome::Gtk3::ComboBox $server-cb .= new(:build-id<serverComboBox>);  
my Str $server = $server-cb.get-active-id;
```

Methods

[gtk_combo_box_] get_active

```
method gtk_combo_box_get_active ( --> int32 )
```

Returns the index of the currently active item, or -1 if there's no active item. See also [gnome developer docs](#).

[gtk_combo_box_] set_active

```
method gtk_combo_box_set_active ( int32 $index )
```

Sets the active item of `combo_box` to be the item at `index`. See also [gnome developer docs](#).

[gtk_combo_box_] get_active_id

```
method gtk_combo_box_get_active_id ( --> Str )
```

Returns the ID of the active row of `combo_box`. See also [gnome developer docs](#).

[gtk_combo_box_] set_active_id

```
method gtk_combo_box_set_active_id ( Str $active_id )
```

Changes the active row of `combo_box`. See also [gnome developer docs](#).

new

```
multi method new ( :$widget! )
```

Create a combobox using a native object from elsewhere. See also `Gnome::GObject::Object`.

```
multi method new ( Str :$build-id! )
```

Create a combobox using a native object from a builder. See also `Gnome::GObject::Object`.