

**NAME**

curl\_easy\_getinfo - Extract information from a curl session (added in 7.4)

**SYNOPSIS**

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_getinfo(CURL *curl, CURLINFO info, ... );
```

**DESCRIPTION**

Request internal information from the curl session with this function. The third argument **MUST** be a pointer to a long, a pointer to a char \* or a pointer to a double (as this documentation describes further down). The data pointed-to will be filled in accordingly and can be relied upon only if the function returns CURLE\_OK. This function is intended to get used *\*AFTER\** a performed transfer, all results from this function are undefined until the transfer is completed.

**AVAILABLE INFORMATION**

These are informations that can be extracted:

**CURLINFO\_EFFECTIVE\_URL**

Pass a pointer to a 'char \*' to receive the last used effective URL.

**CURLINFO\_HTTP\_CODE**

Pass a pointer to a long to receive the last received HTTP code.

**CURLINFO\_FILETIME**

Pass a pointer to a long to receive the remote time of the retrieved document. If you get -1, it can be because of many reasons (unknown, the server hides it or the server doesn't support the command that tells document time etc) and the time of the document is unknown. Note that you must tell the server to collect this information before the transfer is made, by using the CURLOPT\_FILETIME option to *curl\_easy\_setopt(3)*. (Added in 7.5)

**CURLINFO\_TOTAL\_TIME**

Pass a pointer to a double to receive the total transaction time in seconds for the previous transfer. This time does not include the connect time, so if you want the complete operation time, you should add the CURLINFO\_CONNECT\_TIME.

**CURLINFO\_NAMELOOKUP\_TIME**

Pass a pointer to a double to receive the time, in seconds, it took from the start until the name resolving was completed.

**CURLINFO\_CONNECT\_TIME**

Pass a pointer to a double to receive the time, in seconds, it took from the start until the connect to the remote host (or proxy) was completed.

**CURLINFO\_PRETRANSFER\_TIME**

Pass a pointer to a double to receive the time, in seconds, it took from the start until the file transfer is just about to begin. This includes all pre-transfer commands and negotiations that are specific to the particular protocol(s) involved.

**CURLINFO\_STARTTRANSFER\_TIME**

Pass a pointer to a double to receive the time, in seconds, it took from the start until the first byte is just about to be transferred. This includes CURLINFO\_PRETRANSFER\_TIME and also the time the server needs to calculate the result.

**CURLINFO\_REDIRECT\_TIME**

Pass a pointer to a double to receive the total time, in seconds, it took for all redirection steps include name lookup, connect, pretransfer and transfer before final transaction was started. CURLINFO\_REDIRECT\_TIME contains the complete execution time for multiple redirections. (Added in 7.9.7)

**CURLINFO\_REDIRECT\_COUNT**

Pass a pointer to a long to receive the total number of redirections that were actually followed. (Added in 7.9.7)

**CURLINFO\_SIZE\_UPLOAD**

Pass a pointer to a double to receive the total amount of bytes that were uploaded.

**CURLINFO\_SIZE\_DOWNLOAD**

Pass a pointer to a double to receive the total amount of bytes that were downloaded. The amount is only for the latest transfer and will be reset again for each new transfer.

**CURLINFO\_SPEED\_DOWNLOAD**

Pass a pointer to a double to receive the average download speed that curl measured for the complete download.

**CURLINFO\_SPEED\_UPLOAD**

Pass a pointer to a double to receive the average upload speed that curl measured for the complete upload.

**CURLINFO\_HEADER\_SIZE**

Pass a pointer to a long to receive the total size of all the headers received.

**CURLINFO\_REQUEST\_SIZE**

Pass a pointer to a long to receive the total size of the issued requests. This is so far only for HTTP requests. Note that this may be more than one request if FOLLOWLOCATION is true.

**CURLINFO\_SSL\_VERIFYRESULT**

Pass a pointer to a long to receive the result of the certification verification that was requested (using the CURLOPT\_SSL\_VERIFYPEER option to curl\_easy\_setopt). (Added in 7.4.2)

**CURLINFO\_CONTENT\_LENGTH\_DOWNLOAD**

Pass a pointer to a double to receive the content-length of the download. This is the value read from the Content-Length: field. (Added in 7.6.1)

**CURLINFO\_CONTENT\_LENGTH\_UPLOAD**

Pass a pointer to a double to receive the specified size of the upload. (Added in 7.6.1)

**CURLINFO\_CONTENT\_TYPE**

Pass a pointer to a 'char \*' to receive the content-type of the downloaded object. This is the value read from the Content-Type: field. If you get NULL, it means that the server didn't send a valid Content-Type header or that the protocol used doesn't support this. (Added in 7.9.4)

**CURLINFO\_PRIVATE**

Pass a pointer to a 'char \*' to receive the pointer to the private data associated with the curl handle (set with the CURLOPT\_PRIVATE option to curl\_easy\_setopt). (Added in 7.10.3)

**RETURN VALUE**

If the operation was successful, CURLE\_OK is returned. Otherwise an appropriate error code will be returned.

**SEE ALSO**

**curl\_easy\_setopt(3)**

**BUGS**

Surely there are some, you tell me!