

Package ‘BiocParallel’

April 21, 2020

Type Package

Title Bioconductor facilities for parallel evaluation

Version 1.21.3

Description This package provides modified versions and novel implementation of functions for parallel evaluation, tailored to use with Bioconductor objects.

URL <https://github.com/Bioconductor/BiocParallel>

BugReports <https://github.com/Bioconductor/BiocParallel/issues>

biocViews Infrastructure

License GPL-2 | GPL-3

SystemRequirements C++11

Depends methods

Imports stats, utils, futile.logger, parallel, snow

Suggests BiocGenerics, tools, foreach, BatchJobs, BBmisc, doParallel, Rmpi, GenomicRanges, RNAseqData.HNRNPC.bam.chr14, TxDb.Hsapiens.UCSC.hg19.knownGene, VariantAnnotation, Rsamtools, GenomicAlignments, ShortRead, codetools, RUnit, BiocStyle, knitr, batchtools, data.table

Collate AllGenerics.R DeveloperInterface.R prototype.R
bploop.R ErrorHandler.R log.R
bpbackend-methods.R bpisup-methods.R bplapply-methods.R
bpiterate-methods.R bpstart-methods.R bpstop-methods.R
BiocParallelParam-class.R
bpmapply-methods.R bpschedule-methods.R bpvec-methods.R
bpvectorize-methods.R bpworkers-methods.R bpaggregate-methods.R
bpvalidate.R SnowParam-class.R MulticoreParam-class.R
TransientMulticoreParam-class.R register.R
SerialParam-class.R DoparParam-class.R SnowParam-utils.R
BatchJobsParam-class.R BatchtoolsParam-class.R
progress.R ipcmutex.R utilities.R internal_rng_stream.R

LinkingTo BH

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/BiocParallel>

git_branch master

git_last_commit e5ba059

git_last_commit_date 2020-04-21

Date/Publication 2020-04-21

R topics documented:

BiocParallel-package	2
BatchJobsParam-class	3
BatchtoolsParam-class	5
BiocParallelParam-class	8
bpaggregate	11
bpiterate	12
bplapply	15
bploop	16
bpmapply	18
bpok	19
bpschedule	20
bptry	21
bpvalidate	22
bpvec	24
bpvectorize	26
DeveloperInterface	27
DoparParam-class	30
ipcmutex	31
MulticoreParam-class	33
register	39
SerialParam-class	41
SnowParam-class	42
Index	50

BiocParallel-package *Bioconductor facilities for parallel evaluation*

Description

This package provides modified versions and novel implementation of functions for parallel evaluation, tailored to use with Bioconductor objects.

Details

This package uses code from the [parallel](#) package,

Author(s)

Author: Bioconductor Package Maintainer [cre], Martin Morgan [aut], Valerie Obenchain [aut], Michel Lang [aut], Ryan Thompson [aut], Nitesh Turaga [aut]

Maintainer: Bioconductor Package Maintainer <maintainer@bioconductor.org>

BatchJobsParam-class *Enable parallelization on batch systems*

Description

This class is used to parameterize scheduler options on managed high-performance computing clusters.

Usage

```
BatchJobsParam(workers, cleanup = TRUE,
  work.dir = getwd(), stop.on.error = TRUE, seed = NULL,
  resources = NULL, conffile = NULL, cluster.functions = NULL,
  progressbar = TRUE, jobname = "BPJOB",
  reg.pars=list(seed=seed, work.dir=work.dir),
  conf.pars=list(conffile=conffile, cluster.functions=cluster.functions),
  submit.pars=list(resources=resources),
  ...)
```

Arguments

workers	integer(1) Number of workers to divide tasks (e.g., elements in the first argument of <code>bplapply</code>) between. On Multicore and SSH backends, this defaults to all available nodes. On managed (e.g., slurm, SGE) clusters workers defaults to NA, meaning that the number of workers equals the number of tasks. See argument <code>n.chunks</code> in chunk and submitJobs for more information.
cleanup	logical(1) BatchJobs creates temporary directories in the <code>work.dir</code> . If <code>cleanup</code> is set to TRUE (default), the directories are removed from the file systems automatically. Set this to FALSE whenever it might become necessary to utilize any special functionality provided by BatchJobs. To retrieve the registry, call loadRegistry on the temporary directory.
work.dir	character(1) Directory to store temporary files. Note that this must be shared across computational nodes if you use a distributed computing backend. Default is the current working directory of R, see getwd . Ignored when <code>reg.pars</code> is provided.
stop.on.error	logical(1) Stop all jobs as soon as one jobs fails (<code>stop.on.error == TRUE</code>) or wait for all jobs to terminate. Default is TRUE.
seed	integer(1L) Set an initial seed for the RNG. See makeRegistry for more information. Default is NULL where a random seed is chosen upon initialization. Ignored when <code>reg.pars</code> is provided.
resources	list() List of job specific resources passed to submitJobs . Default is NULL where the resources defined in the configuration are used. Ignored when <code>submit.pars</code> is provided.
conffile	character(1) URI to a custom BatchJobs configuration file used for execution. Default is NULL which relies on BatchJobs to handle configuration files. Ignored when <code>conf.pars</code> is provided.
cluster.functions	ClusterFunctions Specify a specific cluster backend using one of the constructors provided by BatchJobs, see ClusterFunctions . Default is NULL where the default

	cluster functions defined in the configuration are used. Ignored when <code>conf.pars</code> is provided.
<code>progressbar</code>	<code>logical(1)</code> Suppress the progress bar used in BatchJobs and be less verbose. Default is FALSE.
<code>jobname</code>	<code>character(1)</code> Job name that is prepended to the output log and result files. Default is "BPJOB".
<code>reg.pars</code>	<code>list()</code> List of parameters passed to <code>BatchJobs::makeRegistry()</code> . When present, user-supplied arguments <code>seed</code> and <code>work.dir</code> to <code>BatchJobsParam</code> are ignored.
<code>conf.pars</code>	<code>list()</code> List of parameters passed to <code>BatchJobs::setConfig()</code> . When present, user-supplied arguments <code>conf.file</code> , <code>cluster.functions</code> to <code>BatchJobsParam</code> are ignored.
<code>submit.pars</code>	<code>list()</code> List of parameters passed to <code>BatchJobs::submitJobs</code> . When present, user-supplied argument <code>resources</code> to <code>BatchJobsParam</code> is ignored. <code>submitJobs</code> parameters <code>reg</code> , <code>id</code> cannot be set.
<code>...</code>	Addition arguments, currently not handled.

BatchJobsParam constructor

Return an object with specified values. The object may be saved to disk or reused within a session.

Methods

The following generics are implemented and perform as documented on the corresponding help page: [bpworkers](#), [bpnworkers](#), [bpstart](#), [bpstop](#), [bpisup](#), [bpbackend](#), [bpbackend<-](#)

Author(s)

Michel Lang, <mailto:michellang@gmail.com>

See Also

`getClass("BiocParallelParam")` for additional parameter classes.
`register` for registering parameter classes for use in parallel evaluation.

Examples

```
p <- BatchJobsParam(progressbar=FALSE)
bplapply(1:10, sqrt, BPPARAM=p)

## Not run:
## see vignette for additional explanation
funs <- makeClusterFunctionsSLURM("~/slurm.tmpl")
param <- BatchJobsParam(4, cluster.functions=funs)
register(param)
bplapply(1:10, function(i) sqrt)

## End(Not run)
```

BatchtoolsParam-class *Enable parallelization on batch systems*

Description

This class is used to parameterize scheduler options on managed high-performance computing clusters using batchtools.

BatchtoolsParam(): Construct a BatchtoolsParam-class object.

batchtoolsWorkers(): Return the default number of workers for each backend.

batchtoolsTemplate(): Return the default template for each backend.

batchtoolsCluster(): Return the default cluster.

batchtoolsRegistryargs(): Create a list of arguments to be used in batchtools' makeRegistry; see registryargs argument.

Usage

```
BatchtoolsParam(
  workers = batchtoolsWorkers(cluster),
  cluster = batchtoolsCluster(),
  registryargs = batchtoolsRegistryargs(),
  saveregistry = FALSE,
  resources = list(),
  template = batchtoolsTemplate(cluster),
  stop.on.error = TRUE, progressbar = FALSE, RNGseed = NA_integer_,
  timeout = 30L * 24L * 60L * 60L, exportglobals=TRUE,
  log = FALSE, logdir = NA_character_, resultdir=NA_character_,
  jobname = "BPJOB"
)
batchtoolsWorkers(cluster = batchtoolsCluster())
batchtoolsCluster(cluster)
batchtoolsTemplate(cluster)
batchtoolsRegistryargs(...)
```

Arguments

workers	integer(1) Number of workers to divide tasks (e.g., elements in the first argument of bplapply) between. On 'multicore' and 'socket' backends, this defaults to multicoreWorkers() and snowWorkers(). On managed (e.g., slurm, SGE) clusters workers has no default, meaning that the number of workers needs to be provided by the user.
cluster	character(1) Cluster type being used as the backend by BatchtoolsParam. The available options are "socket", "multicore", "interactive", "sge", "slurm", "lsf", "torque" and "openlava". The cluster type if available on the machine registers as the backend. Cluster types which need a template are "sge", "slurm", "lsf", "openlava", and "torque". If the template is not given then a default is selected from the batchtools package.
registryargs	list() Arguments given to the registry created by BatchtoolsParam to configure the registry and where it's being stored. The registryargs can be specified by the function batchtoolsRegistryargs() which takes the arguments

	file.dir, work.dir, packages, namespaces, source, load, make.default. It's useful to configure these option, especially the file.dir to a location which is accessible to all the nodes on your job scheduler i.e master and workers. file.dir uses a default setting to make a registry in your working directory.
saveregistry	logical(1) Option given to store the entire registry for the job(s). This functionality should only be used when debugging. The storage of the entire registry can be time and space expensive on disk. The registry will be saved in the directory specified by file.dir in registryargs; the default locatoin is the current working directory. The saved registry directories will have suffix "-1", "-2" and so on, for each time the BatchtoolsParam is used.
resources	named list() Arguments passed to the resources argument of batchtools::submitJobs during evaluation of bplapply and similar functions. These name-value pairs are used for substitution into the template file.
template	character(1) Path to a template for the backend in BatchtoolsParam. It is possible to check which template is being used by the object using the getter bpbackend(BatchtoolsParam()). The template needs to be written specific to each backend. Please check the list of available templates in the batchtools package.
stop.on.error	logical(1) Stop all jobs as soon as one jobs fails (stop.on.error == TRUE) or wait for all jobs to terminate. Default is TRUE.
progressbar	logical(1) Suppress the progress bar used in BatchtoolsParam and be less verbose. Default is FALSE.
RNGseed	integer(1) Set an initial seed for the RNG. Default is NULL where a random seed is chosen upon initialization.
timeout	list() Time (in seconds) allowed for worker to complete a task. If the computation exceeds timeout an error is thrown with message 'reached elapsed time limit'.
exportglobals	logical(1) Export base::options() from manager to workers? Default TRUE.
log	logical(1) Option given to save the logs which are produced by the jobs. If log=TRUE then the logdir option must be specified.
logdir	character(1) Path to location where logs are stored. The argument log=TRUE is required before using the logdir option.
resultdir	logical(1) Path where results are stored.
jobname	character(1) Job name that is prepended to the output log and result files. Default is "BPJOB".
...	name-value pairs Names and values correspond to arguments from batchtools makeRegistry .

BatchtoolsParam constructor

Return an object with specified values. The object may be saved to disk or reused within a session.

Methods

The following generics are implemented and perform as documented on the corresponding help page: [bpworkers](#), [bpnworkers](#), [bpstart](#), [bpstop](#), [bpisup](#), [bpbackend](#).

[bplapply](#) handles arguments X of classes derived from S4Vectors::List specially, coercing to list.

Author(s)

Nitesh Turaga, <mailto:nitesh.turaga@roswellpark.org>

See Also

`getClass("BiocParallelParam")` for additional parameter classes.
`register` for registering parameter classes for use in parallel evaluation.
 The batchtools package.

Examples

```
## Pi approximation
piApprox = function(n) {
  nums = matrix(runif(2 * n), ncol = 2)
  d = sqrt(nums[, 1]^2 + nums[, 2]^2)
  4 * mean(d <= 1)
}

piApprox(1000)

## Calculate piApprox 10 times
param <- BatchtoolsParam()
result <- bplapply(rep(10e5, 10), piApprox, BPPARAM=param)

## Not run:
## see vignette for additional explanation
library(BiocParallel)
param = BatchtoolsParam(workers=5,
                        cluster="sge",
                        template="script/test-sge-template.tpl")

## Run parallel job
result = bplapply(rep(10e5, 100), piApprox, BPPARAM=param)

## bpmapply
param = BatchtoolsParam()
result = bpmapply(fun, x = 1:3, y = 1:3, MoreArgs = list(z = 1),
                  SIMPLIFY = TRUE, BPPARAM = param)

## bpvec
param = BatchtoolsParam(workers=2)
result = bpvec(1:10, seq_along, BPPARAM=param)

## bpvectorize
param = BatchtoolsParam(workers=2)
## this returns a function
bpseq_along = bpvectorize(seq_along, BPPARAM=param)
result = bpseq_along(1:10)

## biterate
ITER <- function(n=5) {
  i <- 0L
  function() {
    i <- i + 1L
    if (i > n)
      return(NULL)
  }
}
```

```

        rep(i, n)
      }
    }

param <- BatchtoolsParam()
res <- bpiterate(ITER=ITER(), FUN=function(x,y) sum(x) + y, y=10, BPPARAM=param)

## save logs
logdir <- tempfile()
dir.create(logdir)
param <- BatchtoolsParam(log=TRUE, logdir=logdir)
res <- bplapply(rep(10e5, 10), piApprox, BPPARAM=param)

## save registry (should be used only for debugging)
file.dir <- tempfile()
registryargs <- batchtoolsRegistryargs(file.dir = file.dir)
param <- BatchtoolsParam(saveregistry = TRUE, registryargs = registryargs)
res <- bplapply(rep(10e5, 10), piApprox, BPPARAM=param)
dir(dirname(file.dir), basename(file.dir))

## End(Not run)

```

BiocParallelParam-class

BiocParallelParam objects

Description

The `BiocParallelParam` virtual class stores configuration parameters for parallel execution. Concrete subclasses include `SnowParam`, `MulticoreParam`, `BatchtoolsParam`, and `DoparParam` and `SerialParam`.

Details

`BiocParallelParam` is the virtual base class on which other parameter objects build. There are 5 concrete subclasses:

- `SnowParam`: distributed memory computing
- `MulticoreParam`: shared memory computing
- `BatchtoolsParam`: scheduled cluster computing
- `DoparParam`: foreach computing
- `SerialParam`: non-parallel execution

The parameter objects hold configuration parameters related to the method of parallel execution such as shared memory, independent memory or computing with a cluster scheduler.

Construction

The `BiocParallelParam` class is virtual and has no constructor. Instances of the subclasses can be created with the following:

- `SnowParam()`

- MulticoreParam()
- BatchtoolsParam()
- DoparParam()
- SerialParam()

Accessors

Back-end control: In the code below BPPARAM is a BiocParallelParam object.

`bpworkers(x)`, `bpworkers(x, ...)`: `integer(1)` or `character()`. Gets the number or names of the back-end workers. The setter is supported for `SnowParam` and `MulticoreParam` only.

`bpnworkers(x)`: `integer(1)`. Gets the number of the back-end workers.

`bptasks(x)`, `bptasks(x) <-value`: `integer(1)`. Get or set the number of tasks for a job. value must be a scalar integer ≥ 0 L. This argument applies to `SnowParam` and `MulticoreParam` only; `DoparParam` and `BatchtoolsParam` have their own approach to dividing a job among workers.

We define a job as a single call to a function such as `bplapply`, `bpmapply` etc. A task is the division of the `X` argument into chunks. When `tasks == 0` (default), `X` is divided by the number of workers. This approach distributes `X` in (approximately) equal chunks.

A `tasks` value of > 0 dictates the total number of tasks. Values can range from 1 (all of `X` to a single worker) to the length of `X` (each element of `X` to a different worker).

When the length of `X` is less than the number of workers each element of `X` is sent to a worker and `tasks` is ignored. Another case where the `tasks` value is ignored is when using the `bpiterate` function; the number of tasks are defined by the number of data chunks returned by the `ITER` function.

`bpstart(x)`: `logical(1)`. Starts the back-end, if necessary.

`bpstop(x)`: `logical(1)`. Stops the back-end, if necessary and possible.

`bpisup(x)`: `logical(1)`. Tests whether the back-end is available for processing, returning a scalar logical value. `bp*` functions such as `bplapply` automatically start the back-end if necessary.

`bpbackend(x)`, `bpbackend(x) <-value`: Gets or sets the parallel `bpbackend`. Not all back-ends can be retrieved; see `methods("bpbackend")`.

`bplog(x)`, `bplog(x) <-value`: Get or enable logging, if available. value must be a `logical(1)`.

`bpthreshold(x)`, `bpthreshold(x) <-value`: Get or set the logging threshold. value must be a `character(1)` string of one of the levels defined in the `futile.logger` package: "TRACE", "DEBUG", "INFO", "WARN", "ERROR", or "FATAL".

`bplogdir(x)`, `bplogdir(x) <-value`: Get or set an optional directory for saving log files. The directory must already exist with read / write ability.

`bpresultdir(x)`, `bpresultdir(x) <-value`: Get or set an optional directory for saving results as 'rda' files. The directory must already exist with read / write ability.

`bptimeout(x)`, `bptimeout(x) <-value`: `numeric(1)` Time (in seconds) allowed for worker to complete a task. This value is passed to `base::setTimeLimit()` as both the `cpu` and `elapsed` arguments. If the computation exceeds `timeout` an error is thrown with message 'reached elapsed time limit'.

`bpexportglobals(x)`, `bpexportglobals(x) <-value`: `logical(1)` Export `base::options()` from manager to workers? Default TRUE.

`bpprogressbar(x)`, `bpprogressbar(x) <-value`: Get or set the value to enable text progress bar. value must be a `logical(1)`.

`bpRNGseed(x)`, `bpRNGseed(x) <-value`: Get or set the seed for random number generation. value must be a `numeric(1)` or `NULL`.

`bpjobname(x)`, `bpjobname(x) <-value`: Get or set the job name.

Error Handling: In the code below BPPARAM is a `BiocParallelParam` object.

`bpstopOnError(x)`, `bpstopOnError(x) <-value`: `logical()`. Controls if the job stops when an error is hit.

`stop.on.error` controls whether the job stops after an error is thrown. When `TRUE`, the output contains all successfully completed results up to and including the error. When `stop.on.error == TRUE` all computations stop once the error is hit. When `FALSE`, the job runs to completion and successful results are returned along with any error messages.

Methods

Evaluation: In the code below BPPARAM is a `BiocParallelParam` object. Full documentation for these functions are on separate man pages: see `?bpmapply`, `?bplapply`, `?bpvec`, `?bpiterate` and `?bpaggregate`.

```
bpmapply(FUN, ..., MoreArgs=NULL, SIMPLIFY=TRUE, USE.NAMES=TRUE, BPPARAM=bpparam())
bplapply(X, FUN, ..., BPPARAM=bpparam())
bpvec(X, FUN, ..., AGGREGATE=c, BPPARAM=bpparam())
bpiterate(ITER, FUN, ..., BPPARAM=bpparam())
bpaggregate(x, data, FUN, ..., BPPARAM=bpparam())
```

Other: In the code below BPPARAM is a `BiocParallelParam` object.

```
show(x)
```

Author(s)

Martin Morgan and Valerie Obenchain.

See Also

- [SnowParam](#) for computing in distributed memory
- [MulticoreParam](#) for computing in shared memory
- [BatchtoolsParam](#) for computing with cluster schedulers
- [DoparParam](#) for computing with foreach
- [SerialParam](#) for non-parallel execution

Examples

```
getClass("BiocParallelParam")

## For examples see ?SnowParam, ?MulticoreParam, ?BatchtoolsParam
## and ?SerialParam.
```

bpaggregate

*Apply a function on subsets of data frames***Description**

This is a parallel version of [aggregate](#).

Usage

```
## S4 method for signature 'formula,BiocParallelParam'
bpaggregate(x, data, FUN, ...,
            BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'data.frame,BiocParallelParam'
bpaggregate(x, by, FUN, ...,
            simplify=TRUE, BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'matrix,BiocParallelParam'
bpaggregate(x, by, FUN, ...,
            simplify=TRUE, BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'ANY,missing'
bpaggregate(x, ..., BPRED0=list(), BPPARAM=bpparam())
```

Arguments

x	A <code>data.frame</code> , <code>matrix</code> or a <code>formula</code> .
by	A list of factors by which x is split; applicable when x is <code>data.frame</code> or <code>matrix</code> .
data	A <code>data.frame</code> ; applicable when x is a <code>formula</code> .
FUN	Function to apply.
...	Additional arguments for FUN.
simplify	If set to <code>TRUE</code> , the return values of FUN will be simplified using simplify2array .
BPPARAM	An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation.
BPRED0	A list of output from <code>bpaggregate</code> with one or more failed elements. When a list is given in BPRED0, <code>bpok</code> is used to identify errors, tasks are rerun and inserted into the original results.

Details

`bpaggregate` is a generic with methods for `data.frame`, `matrix` and `formula` objects. x is divided into subsets according to factors in `by`. Data chunks are sent to the workers, FUN is applied and results are returned as a `data.frame`.

The function is similar in spirit to [aggregate](#) from the `stats` package but [aggregate](#) is not explicitly called. The `bpaggregate` `formula` method reformulates the call and dispatches to the `data.frame` method which in turn distributes data chunks to workers with `bpapply`.

Value

See [aggregate](#).

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>.

Examples

```
if (interactive() && require(Rsamtools) && require(GenomicAlignments)) {

  fl <- system.file("extdata", "ex1.bam", package="Rsamtools")
  param <- ScanBamParam(what = c("flag", "mapq"))
  gal <- readGAlignments(fl, param=param)

  ## Report the mean map quality by range cutoff:
  cutoff <- rep(0, length(gal))
  cutoff[start(gal) > 1000 & start(gal) < 1500] <- 1
  cutoff[start(gal) > 1500] <- 2
  baggregate(as.data.frame(mcols(gal)$mapq), list(cutoff = cutoff), mean)

}
```

bpiterate

Parallel iteration over an indeterminate number of data chunks

Description

bpiterate iterates over an indeterminate number of data chunks (e.g., records in a file). Each chunk is processed by parallel workers in an asynchronous fashion; as each worker finishes it receives a new chunk. Data are traversed a single time.

Usage

```
bpiterate(ITER, FUN, ..., BPPARAM=bpparam())

## S4 method for signature 'ANY,ANY,missing'
bpiterate(ITER, FUN, ..., BPPARAM=bpparam())

## S4 method for signature 'ANY,ANY,BatchtoolsParam'
bpiterate(
  ITER, FUN, ..., REDUCE, init, reduce.in.order=FALSE, BPPARAM=bpparam()
)
```

Arguments

ITER	A function with no arguments that returns an object to process, generally a chunk of data from a file. When no objects are left (i.e., end of file) it should return NULL and continue to return NULL regardless of the number of times it is invoked after reaching the end of file. This function is run on the master.
------	---

FUN	A function to process the object returned by ITER; run on parallel workers separate from the master. When BPPARAM is a MulticoreParam, FUN is ‘decorated’ with additional arguments and therefore must have ... in the signature.
BPPARAM	An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation, or a list of BiocParallelParam instances, to be applied in sequence for nested calls to bpiterate.
REDUCE	Optional function that combines (reduces) output from FUN. As each worker returns, the data are combined with the REDUCE function. REDUCE takes 2 arguments; one is the current result and the other is the output of FUN from a worker that just finished.
init	Optional initial value for REDUCE; must be of the same type as the object returned from FUN. When supplied, <code>reduce.in.order</code> is set to TRUE.
<code>reduce.in.order</code>	Logical. When TRUE, REDUCE is applied to the results from the workers in the same order the tasks were sent out.
...	Arguments to other methods, and named arguments for FUN.

Details

Supported for [SnowParam](#), [MulticoreParam](#) and [BatchtoolsParam](#).

bpiterate iterates through an unknown number of data chunks, dispatching chunks to parallel workers as they become available. In contrast, other bp*apply functions such as [bplapply](#) or [bpmapply](#) require the number of data chunks to be specified ahead of time. This quality makes bpiterate useful for iterating through files of unknown length.

ITER serves up chunks of data until the end of the file is reached at which point it returns NULL. Note that ITER should continue to return NULL regardless of the number of times it is invoked after reaching the end of the file. FUN is applied to each object (data chunk) returned by ITER.

Value

By default, a list the same length as the number of chunks in `ITER()`. When REDUCE is used, the return is consistent with application of the reduction.

Author(s)

Valerie Obenchain <mailto:vobencha@fhcrc.org>.

See Also

- [bpvec](#) for parallel, vectorized calculations.
- [bplapply](#) for parallel, lapply-like calculations.
- [BiocParallelParam](#) for details of BPPARAM.
- [BatchtoolsParam](#) for details of BatchtoolsParam.

Examples

```
## Not run:
if (require(Rsamtools) && require(RNaseqData.HNRNPC.bam.chr14) &&
    require(GenomicAlignments) && require(ShortRead)) {

## -----
```

```

## Iterate through a BAM file
## -----

## Select a single file and set 'yieldSize' in the BamFile object.
fl <- RNAseqData.HNRNPC.bam.chr14_BAMFILES[[1]]
bf <- BamFile(fl, yieldSize = 300000)

## bamIterator() is initialized with a BAM file and returns a function.
## The return function requires no arguments and iterates through the
## file returning data chunks the size of yieldSize.
bamIterator <- function(bf) {
  done <- FALSE
  if (!isOpen( bf))
    open(bf)

  function() {
    if (done)
      return(NULL)
    yld <- readGAlignments(bf)
    if (length(yld) == 0L) {
      close(bf)
      done <- TRUE
      NULL
    } else yld
  }
}

## FUN counts reads in a region of interest.
roi <- GRanges("chr14", IRanges(seq(19e6, 107e6, by = 10e6), width = 10e6))
counter <- function(reads, roi, ...) {
  countOverlaps(query = roi, subject = reads)
}

## Initialize the iterator.
ITER <- bamIterator(bf)

## The number of chunks returned by ITER() determines the result length.
bpparam <- MulticoreParam(workers = 3)
## bpparam <- BatchtoolsParam(workers = 3), see ?BatchtoolsParam
bpiterate(ITER, counter, roi = roi, BPPARAM = bpparam)

## Re-initialize the iterator and combine on the fly with REDUCE:
ITER <- bamIterator(bf)
bpparam <- MulticoreParam(workers = 3)
bpiterate(ITER, counter, REDUCE = sum, roi = roi, BPPARAM = bpparam)

## -----
## Iterate through a FASTA file
## -----

## Set data chunk size with 'n' in the FastqStreamer object.
sp <- SolexaPath(system.file('extdata', package = 'ShortRead'))
fl <- file.path(analysisPath(sp), "s_1_sequence.txt")

## Create an iterator that returns data chunks the size of 'n'.
fastqIterator <- function(fqs) {
  done <- FALSE

```

```

        if (!isOpen(fqs))
        open(fqs)

        function() {
        if (done)
            return(NULL)
        yld <- yield(fqs)
        if (length(yld) == 0L) {
            close(fqs)
            done <- TRUE
            NULL
        } else yld
        }
    }

    ## The process function summarizes the number of times each sequence occurs.
    summary <- function(reads, ...) {
        ShortRead::tables(reads, n = 0)$distribution
    }

    ## Create a param.
    bpparam <- SnowParam(workers = 2)

    ## Initialize the streamer and iterator.
    fqs <- FastqStreamer(fl, n = 100)
    ITER <- fastqIterator(fqs)
    bpiterate(ITER, summary, BPPARAM = bpparam)

    ## Results from the workers are combined on the fly when REDUCE is used.
    ## Collapsing the data in this way can substantially reduce memory
    ## requirements.
    fqs <- FastqStreamer(fl, n = 100)
    ITER <- fastqIterator(fqs)
    bpiterate(ITER, summary, REDUCE = merge, all = TRUE, BPPARAM = bpparam)

}

## End(Not run)

```

bplapply

*Parallel lapply-like functionality***Description**

bplapply applies FUN to each element of X. Any type of object X is allowed, provided length, [, and [[methods are available. The return value is a list of length equal to X, as with [lapply](#).

Usage

```
bplapply(X, FUN, ..., BPRED0 = list(), BPPARAM=bpparam())
```

Arguments

X Any object for which methods length, [, and [[are implemented.

FUN	The function to be applied to each element of X.
...	Additional arguments for FUN, as in lapply .
BPPARAM	An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation, or a list of BiocParallelParam instances, to be applied in sequence for nested calls to BiocParallel functions.
BPREDO	A list of output from <code>bplapply</code> with one or more failed elements. When a list is given in BPREDO, <code>bpok</code> is used to identify errors, tasks are rerun and inserted into the original results.

Details

See `methods{bploop}` for additional methods, e.g., `method?bploop("MulticoreParam")`.

Value

See [lapply](#).

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>. Original code as attributed in [mclapply](#).

See Also

- [bpvec](#) for parallel, vectorized calculations.
- [BiocParallelParam](#) for possible values of BPPARAM.

Examples

```
methods("bploop")

## ten tasks (1:10) so ten calls to FUN default registered parallel
## back-end. Compare with bpvec.
fun <- function(v) {
  message("working") ## 10 tasks
  sqrt(v)
}
bploop(1:10, fun)
```

bploop

Internal Functions for SNOW-style Parallel Evaluation

Description

The functions documented on this page are primarily for use within **BiocParallel** to enable SNOW-style parallel evaluation, using communication between manager and worker nodes through sockets.

Usage

```
## S3 method for class 'lapply'
bploop(manager, X, FUN, ARGFUN, BPPARAM, ...)

## S3 method for class 'iterate'
bploop(manager, ITER, FUN, ARGFUN, BPPARAM,
        REDUCE, init, reduce.in.order, ...)
```


Arguments

manager	An object representing the manager node. For workers, this is the node to which the worker will communicate. For managers, this is the form of iteration – <code>lapply</code> or <code>iterate</code> .
X	A vector of jobs to be performed.
FUN	A function to apply to each job.
ARGFUN	A function accepting an integer value indicating the job number, and returning the job-specific arguments to FUN.
BPPARAM	An instance of a <code>BiocParallelParam</code> class.
ITER	A function used to generate jobs. No more jobs are available when <code>ITER()</code> returns <code>NULL</code> .
REDUCE	(Optional) A function combining two values returned by FUN into a single value.
init	(Optional) Initial value for reduction.
reduce.in.order	(Optional) logical(1) indicating that reduction must occur in the order jobs are dispatched (<code>TRUE</code>) or that reduction can occur in the order jobs are completed (<code>FALSE</code>).
...	Additional arguments, ignored in all cases.

Details

Workers enter a loop. They wait to receive a message (`R` list) from the manager. The message contains a type element, with evaluation as follows:

“EXEC” Execute the `R` code in the message, returning the result to the manager.

“DONE” Signal termination to the manager, terminate the worker.

Managers under `lapply` dispatch pre-determined jobs, `X`, to workers, collecting the results from and dispatching new jobs to the first available worker. The manager returns a list of results, in a one-to-one correspondence with the order of jobs supplied, when all jobs have been evaluated.

Managers under `iterate` dispatch an undetermined number of jobs to workers, collecting previous jobs from and dispatching new jobs to the first available worker. Dispatch continues until available jobs are exhausted. The return value is by default a list of results in a one-to-one correspondence with the order of jobs supplied. The return value is influenced by `REDUCE`, `init`, and `reduce.in.order`.

Author(s)

Valerie Obenchain, Martin Morgan. Derived from similar functionality in the **snow** and **parallel** packages.

Examples

```
## These functions are not meant to be called by the end user.
```

bpmapply

*Parallel mapply-like functionality***Description**

bpmapply applies FUN to first elements of ..., the second elements and so on. Any type of object in ... is allowed, provided length, [, and [[methods are available. The return value is a list of length equal to the length of all objects provided, as with [mapply](#).

Usage

```
bpmapply(FUN, ..., MoreArgs=NULL, SIMPLIFY=TRUE, USE.NAMES=TRUE,
         BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'ANY,missing'
bpmapply(FUN, ..., MoreArgs=NULL, SIMPLIFY=TRUE,
         USE.NAMES=TRUE, BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'ANY,BiocParallelParam'
bpmapply(FUN, ..., MoreArgs=NULL,
         SIMPLIFY=TRUE, USE.NAMES=TRUE, BPRED0=list(), BPPARAM=bpparam())
```

Arguments

FUN	The function to be applied to each element passed via
...	Objects for which methods length, [, and [[are implemented. All objects must have the same length or shorter objects will be replicated to have length equal to the longest.
MoreArgs	List of additional arguments to FUN.
SIMPLIFY	If TRUE the result will be simplified using simplify2array .
USE.NAMES	If TRUE the result will be named.
BPPARAM	An optional BiocParallelParam instance defining the parallel back-end to be used during evaluation.
BPRED0	A list of output from bpmapply with one or more failed elements. When a list is given in BPRED0, bpok is used to identify errors, tasks are rerun and inserted into the original results.

Details

See `methods{bpmapply}` for additional methods, e.g., `method?bpmapply("MulticoreParam")`.

Value

See [mapply](#).

Author(s)

Michel Lang . Original code as attributed in [mclapply](#).

See Also

- [bpvec](#) for parallel, vectorized calculations.
- [BiocParallelParam](#) for possible values of BPPARAM.

Examples

```
methods("bpmapply")

fun <- function(greet, who) {
  paste(Sys.getpid(), greet, who)
}
greet <- c("morning", "night")
who <- c("sun", "moon")

param <- bpparam()
original <- bpworkers(param)
bpworkers(param) <- 2
result <- bpmapply(fun, greet, who, BPPARAM = param)
cat(paste(result, collapse="\n"), "\n")
bpworkers(param) <- original
```

bpok

*Resume computation with partial results***Description**

Identifies unsuccessful results returned from `bplapply`, `bpmapply`, `bpvec`, `bpaggregate` or `bpvectorize`.

Usage

```
bpok(x)
```

Arguments

`x` Results returned from a call to `bp*apply`.

Details

- `bpok` Returns a `logical()` vector: `FALSE` for any jobs that resulted in an error. `x` is the result list output by `bplapply`, `bpmapply`, `bpvec`, `bpaggregate` or `bpvectorize`.

Author(s)

Michel Lang, Martin Morgan and Valerie Obenchain

Examples

```
## -----
## Catch errors:
## -----

## By default 'stop.on.error' is TRUE in BiocParallelParam objects. If
## 'stop.on.error' is TRUE an ill-fated bplapply() simply stops,
## displaying the error message.
param <- SnowParam(workers = 2, stop.on.error = TRUE)
tryCatch({
  bplapply(list(1, "two", 3), sqrt, BPPARAM = param)
}, error=identity)

## If 'stop.on.error' is FALSE then the computation continues. Errors
## are signalled but the full evaluation can be retrieved
param <- SnowParam(workers = 2, stop.on.error = FALSE)
X <- list(1, "two", 3)
result <- bpttry(bplapply(X, sqrt, BPPARAM = param))
result

## Check for errors:
fail <- !bpok(result)
fail

## Access the traceback with attr():
tail(attr(result[[2]], "traceback"), 5)

## -----
## Resume calculations:
## -----

## The 'resume' mechanism is triggered by supplying a list of partial
## results as 'BPRED0'. Data elements that failed are rerun and merged
## with previous results.

## A call of sqrt() on the character "2" returns an error. Fix the input
## data by changing the character "2" to a numeric 2:
X_mod <- list(1, 2, 3)
bplapply(X_mod, sqrt, BPPARAM = param , BPRED0 = result)
```

bpschedule

Schedule back-end Params

Description

Use functions on this page to influence scheduling of parallel processing.

Usage

```
bpschedule(x)
```

Arguments

`x` An instance of a `BiocParallelParam` class, e.g., [MulticoreParam](#), [SnowParam](#), [DoparParam](#).
`x` can be missing, in which case the default back-end (see [register](#)) is used.

`...` Additional arguments, perhaps used by methods.

Details

`bpschedule` returns a `logical(1)` indicating whether the parallel evaluation should occur at this point.

Value

`bpschedule` returns a scalar logical.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>.

See Also

[BiocParallelParam](#) for possible values of `x`.

Examples

```
bpschedule(SnowParam())           # TRUE
bpschedule(MulticoreParam(2))     # FALSE on windows

p <- MulticoreParam()
bpschedule(p)                     # TRUE
bplapply(1:2, function(i, p) {
  bpschedule(p)                   # FALSE
}, p = p, BPPARAM=p)
```

bptry

Try expression evaluation, recovering from bpterror signals

Description

This function is meant to be used as a wrapper around `bplapply()` and friends, returning the evaluated expression rather than signalling an error.

Usage

```
bptry(expr, ..., bplist_error, bpterror)
```

Arguments

<code>expr</code>	An R expression; see tryCatch .
<code>bplist_error</code>	A ‘handler’ function of a single argument, used to catch <code>bplist_error</code> conditions signalled by <code>expr</code> . A <code>bplist_error</code> condition is signalled when an element of <code>bplapply</code> and other iterations contain a evaluation that failed. When missing, the default retrieves the “result” attribute from the error, containing the partially evaluated results. Setting <code>bplist_error=identity</code> returns the evaluated condition. Setting <code>bplist_error=stop</code> passes the condition to other handlers, notably the handler provided by <code>bperror</code> .
<code>bperror</code>	A ‘handler’ function of a single argument, use to catch <code>bperror</code> conditions signalled by <code>expr</code> . A <code>bperror</code> is a base class to all errors signaled by BiocParallel code. When missing, the default returns the condition without signalling an error.
<code>...</code>	Additional named handlers passed to <code>tryCatch()</code> . These user-provided handlers are evaluated before default handlers <code>bplist_error</code> , <code>bperror</code> .

Value

The partially evaluated list of results.

Author(s)

Martin Morgan <martin.morgan@roswellpark.org>

See Also

[tryCatch](#), [bplapply](#).

Examples

```
param = registered()[[1]]
param
X = list(1, "2", 3)
bptry(bplapply(X, sqrt))           # bplist_error handler
bptry(bplapply(X, sqrt), bplist_error=identity) # bperror handler
```

bpvalidate

Tools for developing functions for parallel execution in distributed memory

Description

`bpvalidate` interrogates the function environment and search path to locate undefined symbols.

Usage

```
bpvalidate(fun)
```

Arguments

fun The function to be checked.

Details

bpvalidate tests if a function can be run in a distributed memory environment (e.g., SOCK clusters, Windows machines). bpvalidate looks in the environment of fun, in the NAMESPACE exports of libraries loaded in fun, and along the search path to identify any symbols outside the scope of fun.

bpvalidate can be used to check functions passed to the bp* family of functions in BiocParallel or other packages that support parallel evaluation on clusters such as snow, BatchJobs, Rmpi, etc.

testing package functions The environment of a function defined inside a package is the NAMESPACE of the package. It is important to test these functions as they will be called from within the package, with the appropriate environment. Specifically, do not copy/paste the function into the workspace; once this is done the GlobalEnv becomes the function environment.

To test a package function, load the package then call the function by name (myfun) or explicitly (mypkg::myfun) if not exported.

testing workspace functions The environment of a function defined in the workspace is the GlobalEnv. Because these functions do not have an associated package NAMESPACE, the functions and variables used in the body must be explicitly passed or defined. See examples.

Defining functions in the workspace is often done during development or testing. If the function is later moved inside a package, it can be rewritten in a more lightweight form by taking advantage of imported symbols in the package NAMESPACE.

NOTE: bpvalidate does not currently work on Generics.

Value

A list of length 2 with named elements 'inPath' and 'unknown'.

- inPath A named list of symbols and where they were found. These symbols were found on the search path instead of the function environment and should probably be imported in the NAMESPACE or otherwise defined in the package.
- unknown A vector of symbols not found in the function environment or the search path.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org> and Valerie Obenchain <mailto:vobencha@fhcrc.org>.

Examples

```
## -----
## Testing package functions
## -----

## Not run:
library(myPkg)

## Test exported functions by name or the double colon:
bpvalidate(myExportedFun)
bpvalidate(myPkg::myExportedFun)
```

```

## Non-exported functions are called with the triple colon:
bpvalidate(myPkg::myInternalFun)

## End(Not run)

## -----
## Testing workspace functions
## -----

## Functions defined in the workspace have the .GlobalEnv as their
## environment. Often the symbols used inside the function body
## are not defined in .GlobalEnv and must be passed explicitly.

## Loading libraries:
## In 'fun1' countBam() is flagged as unknown:
fun1 <- function(f1, ...)
  countBam(f1)
bpvalidate(fun1)

## countBam() is not defined in .GlobalEnv and must be passed as
## an argument or made available by loading the library.
fun2 <- function(f1, ...) {
  library(Rsamtools)
  countBam(f1)
}
bpvalidate(fun2)

## Passing arguments:
## 'param' is defined in the workspace but not passed to 'fun3'.
## bpvalidate() flags 'param' as being found 'inPath' which means
## it is not defined in the function environment or inside the function.
library(Rsamtools)
param <- ScanBamParam(flag=scanBamFlag(isMinusStrand=FALSE))

fun3 <- function(f1, ...) {
  library(Rsamtools)
  countBam(f1, param=param)
}
bpvalidate(fun3)

## 'param' is explicitly passed by adding it as a formal argument.
fun4 <- function(f1, ..., param) {
  library(Rsamtools)
  countBam(f1, param=param)
}
bpvalidate(fun4)

## The corresponding call to a bp* function includes 'param':
## Not run: bplapply(files, fun4, param=param, BPPARAM=SnowParam(2))

```


Description

bpvec applies FUN to subsets of X. Any type of object X is allowed, provided length, and [are defined on X. FUN is a function such that `length(FUN(X)) == length(X)`. The objects returned by FUN are concatenated by AGGREGATE (`c()` by default). The return value is FUN(X).

Usage

```
bpvec(X, FUN, ..., AGGREGATE=c, BPRED0=list(), BPPARAM=bpparam())
```

Arguments

X	Any object for which methods <code>length</code> and <code>[</code> are implemented.
FUN	A function to be applied to subsets of X. The relationship between X and FUN(X) is 1:1, so that <code>length(FUN(X, ...)) == length(X)</code> . The return value of separate calls to FUN are concatenated with AGGREGATE.
...	Additional arguments for FUN.
AGGREGATE	A function taking any number of arguments ... called to reduce results (elements of the ... argument of AGGREGATE from parallel jobs. The default, <code>c</code> , concatenates objects and is appropriate for vectors; <code>rbind</code> might be appropriate for data frames.
BPPARAM	An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation, or a list of BiocParallelParam instances, to be applied in sequence for nested calls to BiocParallel functions.
BPRED0	A list of output from bpvec with one or more failed elements. When a list is given in BPRED0, bpok is used to identify errors, tasks are rerun and inserted into the original results.

Details

This method creates a vector of indices for X that divide the elements as evenly as possible given the number of `bpworkers()` and `bptasks()` of BPPARAM. Indices and data are passed to `bplapply` for parallel evaluation.

The distinction between `bpvec` and `bplapply` is that `bplapply` applies FUN to each element of X separately whereas `bpvec` assumes the function is vectorized, e.g., `c(FUN(x[1]), FUN(x[2]))` is equivalent to `FUN(x[1:2])`. This approach can be more efficient than `bplapply` but requires the assumption that FUN takes a vector input and creates a vector output of the same length as the input which does not depend on partitioning of the vector. This behavior is consistent with `parallel::pvec` and the `?pvec` man page should be consulted for further details.

Value

The result should be identical to `FUN(X, ...)` (assuming that AGGREGATE is set appropriately).

When evaluation of individual elements of X results in an error, the result is a list with the same geometry (i.e., `lengths()`) as the split applied to X to create chunks for parallel evaluation; one or more elements of the list contain a `bpererror` element, indicating that the vectorized calculation failed for at least one of the index values in that chunk.

An error is also signaled when `FUN(X)` does not return an object of the same length as X; this condition is only detected when the number of elements in X is greater than the number of workers.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>.

See Also

[bplapply](#) for parallel lapply.

[BiocParallelParam](#) for possible values of BPPARAM.

[pvec](#) for background.

Examples

```
methods("bpvec")

## ten tasks (1:10), called with as many back-end elements are specified
## by BPPARAM. Compare with bplapply
fun <- function(v) {
  message("working")
  sqrt(v)
}
system.time(result <- bpvec(1:10, fun))
result

## invalid FUN -- length(class(X)) is not equal to length(X)
bpttry(bpvec(1:2, class, BPPARAM=SerialParam()))
```

bpvectorize

Transform vectorized functions into parallelized, vectorized function

Description

This transforms a vectorized function into a parallel, vectorized function. Any function FUN can be used, provided its parallelized argument (by default, the first argument) has a length and [method defined, and the return value of FUN can be concatenated with c.

Usage

```
bpvectorize(FUN, ..., BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'ANY,ANY'
bpvectorize(FUN, ..., BPRED0=list(), BPPARAM=bpparam())

## S4 method for signature 'ANY,missing'
bpvectorize(FUN, ..., BPRED0=list(),
  BPPARAM=bpparam())
```

Arguments

FUN	A function whose first argument has a length and can be subset [, and whose evaluation would benefit by splitting the argument into subsets, each one of which is independently transformed by FUN. The return value of FUN must support concatenation with c.
-----	--

...	Additional arguments to parallization, unused.
BPPARAM	An optional BiocParallelParam instance determining the parallel back-end to be used during evaluation.
BPRED0	A list of output from bpvectorize with one or more failed elements. When a list is given in BPRED0, bpok is used to identify errors, tasks are rerun and inserted into the original results.

Details

The result of bpvectorize is a function with signature `...; arguments to the returned function are the original arguments FUN`. BPPARAM is used for parallel evaluation.

When BPPARAM is a class for which no method is defined (e.g., [SerialParam](#)), FUN(X) is used.

See `methods{bpvectorize}` for additional methods, if any.

Value

A function taking the same arguments as FUN, but evaluated using [bpvec](#) for parallel evaluation across available cores.

Author(s)

Ryan Thompson <mailto:rct@thompsonclan.org>

See Also

[bpvec](#)

Examples

```
psqrt <- bpvectorize(sqrt) ## default parallelization
psqrt(1:10)
```

DeveloperInterface *Developer interface*

Description

Functions documented on this page are meant for developers wishing to implement BPPARAM objects that extend the [BiocParallelParam](#) virtual class to support additional parallel back-ends.

Usage

```
## class extension

.prototype_update(prototype, ...)

## manager interface

.send_to(backend, node, value)
.recv_any(backend)
.send_all(backend, value)
```

```

.recv_all(backend)

## worker interface

.send(worker, value)
.recv(worker)
.close(worker)

## supporting implementations

.bpstart_impl(x)
.bpworker_impl(worker)
.bplapply_impl(X, FUN, ..., BPRED0 = list(), BPPARAM = bpparam())
.bpiterate_impl(ITER, FUN, ..., REDUCE, init, reduce.in.order = FALSE,
  BPPARAM = bpparam())
.bpstop_impl(x)

```

Arguments

prototype	A named list of default values for reference class fields.
x	A BPPARAM instance.
backend	An object containing information about the cluster, returned by <code>bppbackend(<BPPARAM>)</code> .
worker	The object to which the worker communicates via <code>.send</code> and <code>.recv</code> . <code>.close</code> terminates the worker.
node	An integer value indicating the node in the backend to which values are to be sent or received.
value	Any R object, to be sent to or from workers.
X, ITER, FUN, REDUCE, init, reduce.in.order, BPRED0, BPPARAM	See <code>bplapply</code> and <code>bpiterate</code> .
...	For <code>.prototype_update()</code> , name-value pairs to initialize derived and base class fields. For <code>.bplapply_impl()</code> , <code>.bpiterate_impl()</code> , additional arguments to <code>FUN()</code> ; see <code>bplapply</code> and <code>bpiterate</code> .

Details

Start a BPPARM implementation by creating a reference class, e.g., extending the virtual class `BiocParallelParam`. Because of idiosyncracies in reference class field initialization, an instance of the class should be created by calling the generator returned by `setRefClass()` with a list of key-value pairs providing default parameter arguments. The default values for the `BiocParallelParam` base class is provided in a list `.BiocParallelParam.prototype`, and the function `.prototype_update()` updates a prototype with new values, typically provided by the user. See the example below.

BPPARAM implementations need to implement `bpstart()` and `bpstop()` methods; they may also need to implement `bplapply()` and `bpiterate()` methods. Each method usually performs implementation-specific functionality before calling the next (`BiocParallelParam`) method. To avoid the intricacies of multiple dispatch, the bodies of `BiocParallelParam` methods are available for direct use as exported symbols.

- `bpstart,BiocParallelParam-method(.bpstart_impl())` initiates logging, random number generation, and registration of finalizers to ensure that started clusters are stopped.

- `bpstop`, `BiocParallelParam`-method `(.bpstop_impl())` ensures appropriate clean-up of stopped clusters, including sending the `DONE` semaphore. `bpstart()` will usually arrange for workers to enter `.bpworker_impl()` to listen for and evaluate tasks.
- `bplapply`, `ANY`, `BiocParallelParam`-method and `bpiterate`, `ANY`, `BiocParallelParam`-method `(.bplapply_impl(), .bpiterate_impl())` implement: serial evaluation when there is a single core or task available; `BPRED0` functionality, and parallel `lapply`-like or iterative calculation.

Invoke `.bpstart_impl()`, `.bpstop_impl()`, `.bplapply_impl()`, and `.bpiterate_impl()` after any `BPPARAM`-specific implementation details.

New implementations will also implement `bpiup()` and `bpbackend()` / `bpbackend<-(())`; there are no default methods.

The *backends* (object returned by `bpbackend()`) of new `BPPARAM` implementations must support `length()` (number of nodes). In addition, the backends must support `.send_to()` and `.recv_any()` manager and `.send()`, `.recv()`, and `.close()` worker methods. Default `.send_all()` and `.recv_all()` methods are implemented as simple iterations along the `length(cluster)`, invoking `.send_to()` or `.recv_any()` on each iteration.

Value

The return value of `.prototype_update()` is a list with elements in prototype substituted with key-value pairs provided in ...

All `send*` and `recv*` functions are endomorphic, returning a cluster object.

Examples

```
##
## Extend BiocParallelParam; `.A()` is not meant for the end user
##

.A <- setRefClass(
  "A",
  contains = "BiocParallelParam",
  fields = list(id = "character")
)

## Use a prototype for default values, including the prototype for
## inherited fields

.A_prototype <- c(
  list(id = "default_id"),
  .BiocParallelParam_prototype
)

## Provide a constructor for the user

A <- function(...) {
  prototype <- .prototype_update(.A_prototype, ...)
  do.call(.A, prototype)
}

## Provide an R function for field access

bpid <- function(x)
```

```

x$id

## Create and use an instance, overwriting default values

bpid(A())

a <- A(id = "my_id", threshold = "WARN")
bpid(a)
bpthreshold(a)

```

DoparParam-class

Enable parallel evaluation using registered dopar backend

Description

This class is used to dispatch parallel operations to the dopar backend registered with the foreach package.

Usage

```
DoparParam(stop.on.error=TRUE)
```

Arguments

`stop.on.error` `logical(1)` Stop all jobs as soon as one jobs fails (`stop.on.error == TRUE`) or wait for all jobs to terminate. Default is `TRUE`.

Details

DoparParam can be used for shared or non-shared memory computing depending on what backend is loaded. The doSNOW package supports non-shared memory, doParallel supports both shared and non-shared. When not specified, the default number of workers in DoparParam is determined by `getDoParWorkers()`. See the foreach package vignette for details using the different backends:

<http://cran.r-project.org/web/packages/foreach/vignettes/foreach.pdf>

DoparParam constructor

Return a proxy object that dispatches parallel evaluation to the registered foreach parallel backend.

There are no options to the constructor. All configuration should be done through the normal interface to the foreach parallel backends.

Methods

The following generics are implemented and perform as documented on the corresponding help page (e.g., `?bpisup`): `bpworkers`, `bpnworkers`, `bpstart`, `bpstop`, `bpisup`, `bpbackend`, `bpbackend<-`, `bpvec`.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>

See Also

getClass("BiocParallelParam") for additional parameter classes.
 register for registering parameter classes for use in parallel evaluation.
 foreach-package for the parallel backend infrastructure used by this param class.

Examples

```
## Not run:
# First register a parallel backend with foreach
library(doParallel)
registerDoParallel(2)

p <- DoparParam()
bplapply(1:10, sqrt, BPPARAM=p)
bpvec(1:10, sqrt, BPPARAM=p)

register(DoparParam(), default=TRUE)

## End(Not run)
```

ipcmutex

*Inter-process locks and counters***Description**

Functions documented on this page enable locks and counters between processes on the *same* computer.

Use ipcId() to generate a unique mutex or counter identifier. A mutex or counter with the same id, including those in different processes, share the same state.

ipcremove() removes external state associated with mutex or counters created with id.

ipclock() blocks until the lock is obtained. ipctrylock() tries to obtain the lock, returning immediately if it is not available. ipcunlock() releases the lock. ipclocked() queries the lock to determine whether it is currently held.

ipcyield() returns the current counter, and increments the value for subsequent calls. ipcvalue() returns the current counter without incrementing. ipcretset() sets the counter to n, such that the next call to ipcyield() or ipcvalue() returns n.

Usage

```
## Utilities
```

```
ipcId(id)
```

```
ipcremove(id)
```

```
## Locks
```

```
ipclock(id)
```

```

ipctrylock(id)

ipcunlock(id)

ipcllocked(id)

## Counters

ipcyield(id)

ipcvalue(id)

ipcreset(id, n = 1)

```

Arguments

<code>id</code>	character(1) identifier string for mutex or counter. <code>ipcid()</code> ensures that the identifier is universally unique.
<code>n</code>	integer(1) value from which <code>ipcyield()</code> will increment.

Value

Locks:

`ipclock()` creates a named lock, returning TRUE on success.

`trylock()` returns TRUE if the lock is obtained, FALSE otherwise.

`ipcunlock()` returns TRUE on success, FALSE (e.g., because there is nothing to unlock) otherwise.

`ipcllocked()` returns TRUE when `id` is locked, and FALSE otherwise.

Counters:

`ipcyield()` returns an integer(1) value representing the next number in sequence. The first value returned is 1.

`ipcvalue()` returns the value to be returned by the next call to `ipcyield()`, without incrementing the counter. If the counter is no longer available, `ipcyield()` returns NA.

`ipcreset()` returns `n`, invisibly.

Utilities:

`ipcid()` returns a character(1) unique identifier, with `id` (if not missing) prepended.

`ipcremove()` returns (invisibly) TRUE if external resources were released or FALSE if not (e.g., because the resources has already been released).

Examples

```

ipcid()

## Locks

id <- ipcid()

ipclock(id)
ipctrylock(id)
ipcunlock(id)

```



```

ipctrylock(id)
ipclocked(id)

ipcremove(id)

id <- ipcid()
system.time({
  ## about 1s, .2s for each process instead of .2s if no lock
  result <- bplapply(1:2, function(i, id) {
    BiocParallel::ipclock(id)
    Sys.sleep(.2)
    time <- Sys.time()
    BiocParallel::ipcunlock(id)
    time
  }, id)
})
ipcremove(id)
diff(sort(unlist(result, use.names=FALSE)))

## Counters

id <- ipcid()

ipcyield(id)
ipcyield(id)

ipcvalue(id)
ipcyield(id)

ipcreset(id, 10)
ipcvalue(id)
ipcyield(id)

ipcremove(id)

id <- ipcid()
result <- bplapply(1:2, function(i, id) {
  BiocParallel::ipcyield(id)
}, id)
ipcremove(id)
sort(unlist(result, use.names=FALSE))

```

MulticoreParam-class *Enable multi-core parallel evaluation*

Description

This class is used to parameterize single computer multicore parallel evaluation on non-Windows computers. `multicoreWorkers()` chooses the number of workers.

Usage

```
## constructor
```

```
## -----

MulticoreParam(workers = multicoreWorkers(), tasks = 0L,
               stop.on.error = TRUE,
               progressbar = FALSE, RNGseed = NULL,
               timeout = 30L * 24L * 60L * 60L, exportglobals=TRUE,
               log = FALSE, threshold = "INFO", logdir = NA_character_,
               resultdir = NA_character_, jobname = "BPJOB",
               manager.hostname = NA_character_, manager.port = NA_integer_,
               ...)

## detect workers
## -----

multicoreWorkers()
```

Arguments

workers	integer(1) Number of workers. Defaults to all cores available as determined by detectCores.
tasks	integer(1). The number of tasks per job. value must be a scalar integer >= 0L. In this documentation a job is defined as a single call to a function, such as bplapply, bpmapply etc. A task is the division of the X argument into chunks. When tasks == 0 (default), X is divided as evenly as possible over the number of workers. A tasks value of > 0 specifies the exact number of tasks. Values can range from 1 (all of X to a single worker) to the length of X (each element of X to a different worker). When the length of X is less than the number of workers each element of X is sent to a worker and tasks is ignored.
stop.on.error	logical(1) Enable stop on error.
progressbar	logical(1) Enable progress bar (based on plyr::progress_text).
RNGseed	integer(1) Seed for random number generation. When not NULL, this value is passed to parallel::clusterSetRNGStream to generate random number streams on each worker.
timeout	numeric(1) Time (in seconds) allowed for worker to complete a task. This value is passed to base::setTimeLimit() as both the cpu and elapsed arguments. If the computation exceeds timeout an error is thrown with message 'reached elapsed time limit'.
exportglobals	logical(1) Export base::options() from manager to workers? Default TRUE.
log	logical(1) Enable logging.
threshold	character(1) Logging threshold as defined in futile.logger.
logdir	character(1) Log files directory. When not provided, log messages are returned to stdout.
resultdir	character(1) Job results directory. When not provided, results are returned as an R object (list) to the workspace.

jobname	character(1) Job name that is prepended to log and result files. Default is "BPJOB".
manager.hostname	character(1) Host name of manager node. See 'Global Options', in SnowParam .
manager.port	integer(1) Port on manager with which workers communicate. See 'Global Options' in SnowParam .
...	Additional arguments passed to makeCluster

Details

MulticoreParam is used for shared memory computing. Under the hood the cluster is created with `makeCluster(..., type = "FORK")` from the `parallel` package.

The default number of workers is determined by `multicoreWorkers()`. On windows, the number of multicore workers is always 1. Otherwise, the default is normally the maximum of 1 and `parallel::detectCores() - 2`. Machines with 3 or fewer cores, or machines where number of cores cannot be determined, are assigned a single worker. Machines with more than 127 cores are limited to the number of *R* connections available when the workers start; this is 128 (a hard-coded limit in *R*) minus the number of open connections as returned by `nrow(showConnections(all=TRUE))`. The option `mc.cores` can be used to specify an arbitrary number of workers, e.g., `options(mc.cores=4L)`; the *Bioconductor* build system enforces a maximum of 4 workers.

A FORK transport starts workers with the `mcfork` function and communicates between master and workers using socket connections. `mcfork` builds on `fork()` and thus a Linux cluster is not supported. Because FORK clusters are Posix based they are not supported on Windows. When MulticoreParam is created/used in Windows it defaults to `SerialParam` which is the equivalent of using a single worker.

error handling: By default all computations are attempted and partial results are returned with any error messages.

- `stop.on.error` A logical. Stops all jobs as soon as one job fails or wait for all jobs to terminate. When FALSE, the return value is a list of successful results along with error messages as 'conditions'.
- The `bpok(x)` function returns a `logical()` vector that is FALSE for any jobs that threw an error. The input `x` is a list output from a `bp*apply` function such as `bplapply` or `bpmapply`.

logging: When `log = TRUE` the `futile.logger` package is loaded on the workers. All log messages written in the `futile.logger` format are captured by the logging mechanism and returned in real-time (i.e., as each task completes) instead of after all jobs have finished.

Messages sent to `stdout` and `stderr` are returned to the workspace by default. When `log = TRUE` these are diverted to the log output. Those familiar with the `outfile` argument to `makeCluster` can think of `log = FALSE` as equivalent to `outfile = NULL`; providing a `logdir` is the same as providing a name for `outfile` except that `BiocParallel` writes a log file for each task.

The log output includes additional statistics such as memory use and task runtime. Memory use is computed by calling `gc(reset=TRUE)` before code evaluation and `gc()` (no reset) after. The output of the second `gc()` call is sent to the log file. There are many ways to track memory use - this particular approach was taken because it is consistent with how the `BatchJobs` package reports memory on the workers.

log and result files: Results and logs can be written to a file instead of returned to the workspace. Writing to files is done from the master as each task completes. Options can be set with the `logdir` and `resultdir` fields in the constructor or with the accessors, `bplogdir` and `bpresultdir`.

random number generation: MulticoreParam and SnowParam use the random number generation support from the parallel package. These params are snow-derived clusters so the arguments for multicore-derived functions such as `mc.set.seed` and `mc.reset.stream` do not apply.

Random number generation is controlled through the `param` argument, `RNGseed` which is passed to `parallel::clusterSetRNGStream`. `clusterSetRNGStream` uses the L'Ecuyer-CMRG random number generator and distributes streams to the members of a cluster. If `RNGseed` is not `NULL` it serves as the seed to the streams, otherwise the streams are set from the current seed of the master process after selecting the L'Ecuyer generator. See `?clusterSetRNGStream` for more details.

Constructor

```
MulticoreParam(workers = multicoreWorkers(), tasks = 0L, stop.on.error = FALSE, tasks
= 0L, progressbar = FALSE, RNGseed = NULL, timeout = Inf, exportglobals = TRUE, log = FALSE, threshold
= "INFO", logdir = NA_character_, resultdir = NA_character_, manager.hostname = NA_character_, mana
= NA_integer_, ...):
```

Return an object representing a FORK cluster. The cluster is not created until `bpstart` is called. Named arguments in ... are passed to `makeCluster`.

Accessors: Logging and results

In the following code, `x` is a `MulticoreParam` object.

```
bpprogressbar(x), bpprogressbar(x) <-value: Get or set the value to enable text progress
bar. value must be a logical(1).
bpjobname(x), bpjobname(x) <-value: Get or set the job name.
bpRNGseed(x), bpRNGseed(x) <-value: Get or set the seed for random number generaton. value
must be a numeric(1) or NULL.
bplog(x), bplog(x) <-value: Get or set the value to enable logging. value must be a logical(1).
bpthreshold(x), bpthreshold(x) <-value: Get or set the logging threshold. value must be a
character(1) string of one of the levels defined in the futile.logger package: "TRACE",
"DEBUG", "INFO", "WARN", "ERROR", or "FATAL".
bplogdir(x), bplogdir(x) <-value: Get or set the directory for the log file. value must be a
character(1) path, not a file name. The file is written out as LOGFILE.out. If no logdir is
provided and bplog=TRUE log messages are sent to stdout.
bpresultdir(x), bpresultdir(x) <-value: Get or set the directory for the result files. value
must be a character(1) path, not a file name. Separate files are written for each job with the
prefix JOB (e.g., JOB1, JOB2, etc.). When no resultdir is provided the results are returned
to the session as list.
```

Accessors: Back-end control

In the code below `x` is a `MulticoreParam` object. See the `?BiocParallelParam` man page for details on these accessors.

```
bpworkers(x)
bpnworkers(x)
bptasks(x), bptasks(x) <-value
bpstart(x)
bpstop(x)
```

```
bpisup(x)
bpbackend(x), bpbackend(x) <-value
```

Accessors: Error Handling

In the code below `x` is a `MulticoreParam` object. See the `?BiocParallelParam` man page for details on these accessors.

```
bpstopOnError(x), bpstopOnError(x) <-value
```

Methods: Evaluation

In the code below `BPPARAM` is a `MulticoreParam` object. Full documentation for these functions are on separate man pages: see `?bpmapply`, `?bplapply`, `?bpvec`, `?bpiterate` and `?bpaggregate`.

```
bpmapply(FUN, ..., MoreArgs=NULL, SIMPLIFY=TRUE, USE.NAMES=TRUE, BPPARAM=bpparam())
bplapply(X, FUN, ..., BPPARAM=bpparam())
bpvec(X, FUN, ..., AGGREGATE=c, BPPARAM=bpparam())
bpiterate(ITER, FUN, ..., BPPARAM=bpparam())
bpaggregate(x, data, FUN, ..., BPPARAM=bpparam())
```

Methods: Other

In the code below `x` is a `MulticoreParam` object.

```
show(x): Displays the MulticoreParam object.
```

Global Options

See the 'Global Options' section of [SnowParam](#) for manager host name and port defaults.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org> and Valerie Obenchain

See Also

- [register](#) for registering parameter classes for use in parallel evaluation.
- [SnowParam](#) for computing in distributed memory
- [BatchJobsParam](#) for computing with cluster schedulers
- [DoparParam](#) for computing with foreach
- [SerialParam](#) for non-parallel evaluation

Examples

```
## -----
## Job configuration:
## -----

## MulticoreParam supports shared memory computing. The object fields
## control the division of tasks, error handling, logging and
## result format.
bpparam <- MulticoreParam()
```

```

bpparam

## By default the param is created with the maximum available workers
## determined by multicoreWorkers().
multicoreWorkers()

## Fields are modified with accessors of the same name:
bplog(bpparam) <- TRUE
dir.create(resultdir <- tempfile())
bpresultdir(bpparam) <- resultdir
bpparam

## -----
## Logging:
## -----

## When 'log == TRUE' the workers use a custom script (in BiocParallel)
## that enables logging and access to other job statistics. Log messages
## are returned as each job completes rather than waiting for all to finish.

## In 'fun', a value of 'x = 1' will throw a warning, 'x = 2' is ok
## and 'x = 3' throws an error. Because 'x = 1' sleeps, the warning
## should return after the error.

X <- 1:3
fun <- function(x) {
  if (x == 1) {
    Sys.sleep(2)
    if (TRUE & c(TRUE, TRUE)) ## warning
      x
  } else if (x == 2) {
    x ## ok
  } else if (x == 3) {
    sqrt("FOO") ## error
  }
}

## By default logging is off. Turn it on with the bplog()<- setter
## or by specifying 'log = TRUE' in the constructor.
bpparam <- MulticoreParam(3, log = TRUE, stop.on.error = FALSE)
res <- tryCatch({
  bplapply(X, fun, BPPARAM=bpparam)
}, error=identity)
res

## When a 'logdir' location is given the messages are redirected to a file:
## Not run:
bplogdir(bpparam) <- tempdir()
bplapply(X, fun, BPPARAM = bpparam)
list.files(bplogdir(bpparam))

## End(Not run)

## -----
## Managing results:
## -----

```

```

## By default results are returned as a list. When 'resultdir' is given
## files are saved in the directory specified by job, e.g., 'TASK1.Rda',
## 'TASK2.Rda', etc.
## Not run:
dir.create(resultdir <- tempfile())
bpparam <- MulticoreParam(2, resultdir = resultdir, stop.on.error = FALSE)
bplapply(X, fun, BPPARAM = bpparam)
list.files(bpresultdir(bpparam))

## End(Not run)

## -----
## Error handling:
## -----

## When 'stop.on.error' is TRUE the job is terminated as soon as an
## error is hit. When FALSE, all computations are attempted and partial
## results are returned along with errors. In this example the number of
## 'tasks' is set to equal the length of 'X' so each element is run
## separately. (Default behavior is to divide 'X' evenly over workers.)

## All results along with error:
bpparam <- MulticoreParam(2, tasks = 4, stop.on.error = FALSE)
res <- bpttry(bplapply(list(1, "two", 3, 4), sqrt, BPPARAM = bpparam))
res

## Calling bpok() on the result list returns TRUE for elements with no error.
bpok(res)

## -----
## Random number generation:
## -----

## Random number generation is controlled with the 'RNGseed' field.
## This seed is passed to parallel::clusterSetRNGStream
## which uses the L'Ecuyer-CMRG random number generator and distributes
## streams to members of the cluster.

bpparam <- MulticoreParam(3, RNGseed = 7739465)
bplapply(seq_len(bpnworkers(bpparam)), function(i) rnorm(1), BPPARAM = bpparam)

```

register

Maintain a global registry of available back-end Params

Description

Use functions on this page to add to or query a registry of back-ends, including the default for use when no BPPARAM object is provided to functions.

Usage

```

register(BPPARAM, default=TRUE)
registered(bpparamClass)
bpparam(bpparamClass)

```

Arguments

BPPARAM	An instance of a BiocParallelParam class, e.g., MulticoreParam , SnowParam , DoparParam .
default	Make this the default BiocParallelParam for subsequent evaluations? If FALSE, the argument is placed at the lowest priority position.
bpparamClass	When present, the text name of the BiocParallelParam class (e.g., “MulticoreParam”) to be retrieved from the registry. When absent, a list of all registered instances is returned.

Details

The registry is a list of back-ends with configuration parameters for parallel evaluation. The first list entry is the default and is used by BiocParallel functions when no BPPARAM argument is supplied.

At load time the registry is populated with default backends. On Windows these are SnowParam and SerialParam and on non-Windows MulticoreParam, SnowParam and SerialParam. When snowWorkers() or multicoreWorkers returns a single core, only SerialParam is registered.

The [BiocParallelParam](#) objects are constructed from global options of the corresponding name, or from the default constructor (e.g., SnowParam()) if no option is specified. The user can set customizations during start-up (e.g., in an .Rprofile file) with, for instance, options(MulticoreParam=quote(Multicore

The act of “registering” a back-end modifies the existing [BiocParallelParam](#) in the list; only one param of each type can be present in the registry. When default=TRUE, the newly registered param is moved to the top of the list thereby making it the default. When default=FALSE, the param is modified ‘in place’ vs being moved to the top.

bpparam(), invoked with no arguments, returns the default [BiocParallelParam](#) instance from the registry. When called with the text name of a bpparamClass, the global options are consulted first, e.g., options(MulticoreParam=MulticoreParam()) and then the value of registered(bpparamClass).

Value

register returns, invisibly, a list of registered back-ends.

registered returns the back-end of type bpparamClass or, if bpparamClass is missing, a list of all registered back-ends.

bpparam returns the back-end of type bpparamClass or,

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>.

See Also

[BiocParallelParam](#) for possible values of BPPARAM.

Examples

```
## -----
## The registry
## -----

## The default registry.
default <- registered()
```



```

default

## When default = TRUE the last param registered becomes the new default.
snowparam <- SnowParam(workers = 3, type = "SOCK")
register(snowparam, default = TRUE)
registered()

## Retrieve the default back-end,
bpparam()

## or a specific BiocParallelParam.
bpparam("SnowParam")

## restore original registry -- push the defaults in reverse order
for (param in rev(default))
  register(param)

## -----
## Specifying a back-end for evaluation
## -----

## The back-end of choice is given as the BPPARAM argument to
## the BiocParallel functions. None, one, or multiple back-ends can be
## used.

bplapply(1:6, sqrt, BPPARAM = MulticoreParam(3))

## When not specified, the default from the registry is used.
bplapply(1:6, sqrt)

```

SerialParam-class	<i>Enable serial evaluation</i>
-------------------	---------------------------------

Description

This class is used to parameterize serial evaluation, primarily to facilitate easy transition from parallel to serial code.

Usage

```
SerialParam(stop.on.error = TRUE, log = FALSE,
            threshold = "INFO", logdir = NA_character_, progressbar = FALSE)
```

Arguments

stop.on.error	A logical determining behavior on error; see SnowParam .
log	logical(1) Enable logging; see SnowParam .
threshold	character(1) Logging threshold; see SnowParam .
logdir	character(1) Log files directory. When not provided, log messages are returned to stdout.
progressbar	logical(1) Enable progress bar (based on <code>plyr:::progress_text</code>).

Constructor

```
SerialParam():
```

Return an object to be used for serial evaluation of otherwise parallel functions such as [bplapply](#), [bpvec](#).

Methods

The following generics are implemented and perform as documented on the corresponding help page (e.g., `?bpworkers`): [bpworkers](#), [bpisup](#), [bpstart](#), [bpstop](#), are implemented, but do not have any side-effects.

Author(s)

Martin Morgan <mailto:mtmorgan@fhcrc.org>

See Also

`getClass("BiocParallelParam")` for additional parameter classes.
`register` for registering parameter classes for use in parallel evaluation.

Examples

```
p <- SerialParam()
simplify2array(bplapply(1:10, sqrt, BPPARAM=p))
bpvec(1:10, sqrt, BPPARAM=p)

## Not run:
register(SerialParam(), default=TRUE)

## End(Not run)
```

SnowParam-class	<i>Enable simple network of workstations (SNOW)-style parallel evaluation</i>
-----------------	---

Description

This class is used to parameterize simple network of workstations (SNOW) parallel evaluation on one or several physical computers. `snowWorkers()` chooses the number of workers.

Usage

```
## constructor
## -----

SnowParam(workers = snowWorkers(type), type=c("SOCK", "MPI", "FORK"),
  tasks = 0L, stop.on.error = TRUE,
  progressbar = FALSE, RNGseed = NULL,
  timeout = 30L * 24L * 60L * 60L, exportglobals = TRUE,
  log = FALSE, threshold = "INFO", logdir = NA_character_,
  resultdir = NA_character_, jobname = "BPJOB",
```

```

        manager.hostname = NA_character_, manager.port = NA_integer_,
        ...)

## coercion
## -----

## as(SOCKcluster, SnowParam)
## as(spawnedMPIcluster, SnowParam)

## detect workers
## -----

snowWorkers(type = c("SOCK", "MPI", "FORK"))

```

Arguments

workers	integer(1) Number of workers. Defaults to all cores available as determined by detectCores. For a SOCK cluster workers can be a character() vector of host names.
type	character(1) Type of cluster to use. Possible values are SOCK (default) and MPI. Instead of type=FORK use MulticoreParam.
tasks	integer(1). The number of tasks per job. value must be a scalar integer >= 0L. In this documentation a job is defined as a single call to a function, such as bplapply, bpmapply etc. A task is the division of the X argument into chunks. When tasks == 0 (default), X is divided as evenly as possible over the number of workers. A tasks value of > 0 specifies the exact number of tasks. Values can range from 1 (all of X to a single worker) to the length of X (each element of X to a different worker). When the length of X is less than the number of workers each element of X is sent to a worker and tasks is ignored.
stop.on.error	logical(1) Enable stop on error.
progressbar	logical(1) Enable progress bar (based on plyr::progress_text).
RNGseed	integer(1) Seed for random number generation. When not NULL, this value is passed to parallel::clusterSetRNGStream to generate random number streams on each worker.
timeout	numeric(1) Time (in seconds) allowed for worker to complete a task. This value is passed to base::setTimeLimit() as both the cpu and elapsed arguments. If the computation exceeds timeout an error is thrown with message 'reached elapsed time limit'.
exportglobals	logical(1) Export base::options() from manager to workers? Default TRUE.
log	logical(1) Enable logging.
threshold	character(1) Logging threshold as defined in futile.logger.
logdir	character(1) Log files directory. When not provided, log messages are returned to stdout.
resultdir	character(1) Job results directory. When not provided, results are returned as an R object (list) to the workspace.

<code>jobname</code>	character(1) Job name that is prepended to log and result files. Default is "BPJOB".
<code>manager.hostname</code>	character(1) Host name of manager node. See 'Global Options', below.
<code>manager.port</code>	integer(1) Port on manager with which workers communicate. See 'Global Options', below.
<code>...</code>	Additional arguments passed to makeCluster

Details

SnowParam is used for distributed memory computing and supports 2 cluster types: 'SOCK' (default) and 'MPI'. The SnowParam builds on infrastructure in the `snow` and `parallel` packages and provides the additional features of error handling, logging and writing out results.

The default number of workers is determined by `snowWorkers()` which is usually the maximum of `1L` and `parallel::detectCores() - 2`. Machines with 3 or fewer cores, or machines where number of cores cannot be determined, are assigned a single worker. Machines with more than 127 cores are limited to the number of *R* connections available when the workers start; this is 128 (a hard-coded limit in *R*) minus the number of open connections as returned by `nrow(showConnections(all=TRUE))`. The option `mc.cores` can be used to specify an arbitrary number of workers, e.g., `options(mc.cores=4L)`; the *Bioconductor* build system enforces a maximum of 4 workers.

error handling: By default all computations are attempted and partial results are returned with any error messages.

- `stop.on.error` A logical. Stops all jobs as soon as one job fails or wait for all jobs to terminate. When `FALSE`, the return value is a list of successful results along with error messages as 'conditions'.
- The `bpok(x)` function returns a `logical()` vector that is `FALSE` for any jobs that threw an error. The input `x` is a list output from a `bp*apply` function such as `bplapply` or `bpmapply`.

logging: When `log = TRUE` the `futile.logger` package is loaded on the workers. All log messages written in the `futile.logger` format are captured by the logging mechanism and returned real-time (i.e., as each task completes) instead of after all jobs have finished.

Messages sent to `stdout` and `stderr` are returned to the workspace by default. When `log = TRUE` these are diverted to the log output. Those familiar with the `outfile` argument to `makeCluster` can think of `log = FALSE` as equivalent to `outfile = NULL`; providing a `logdir` is the same as providing a name for `outfile` except that `BiocParallel` writes a log file for each task.

The log output includes additional statistics such as memory use and task runtime. Memory use is computed by calling `gc(reset=TRUE)` before code evaluation and `gc()` (no reset) after. The output of the second `gc()` call is sent to the log file. There are many ways to track memory use - this particular approach was taken because it is consistent with how the `BatchJobs` package reports memory on the workers.

log and result files: Results and logs can be written to a file instead of returned to the workspace. Writing to files is done from the master as each task completes. Options can be set with the `logdir` and `resultdir` fields in the constructor or with the accessors, `bplogdir` and `bpresultdir`.

random number generation: `MulticoreParam` and `SnowParam` use the random number generation support from the `parallel` package. These params are snow-derived clusters so the arguments for multicore-derived functions such as `mc.set.seed` and `mc.reset.stream` do not apply.

Random number generation is controlled through the `param` argument, `RNGseed` which is passed to `parallel::clusterSetRNGStream`. `clusterSetRNGStream` uses the L'Ecuyer-CMRG random number generator and distributes streams to the members of a cluster. If `RNGseed` is not `NULL` it serves as the seed to the streams, otherwise the streams are set from the current seed of the master process after selecting the L'Ecuyer generator. See `?clusterSetRNGStream` for more details.

NOTE: The `PSOCK` cluster from the `parallel` package does not support cluster options `scriptdir` and `userScript`. `PSOCK` is not supported because these options are needed to re-direct to an alternate worker script located in `BiocParallel`.

Constructor

```
SnowParam(workers = snowWorkers(), type=c("SOCK", "MPI"), tasks = 0L, stop.on.error =
  FALSE, progressbar = FALSE, RNGseed = NULL, timeout = Inf, exportglobals = TRUE, log
  = FALSE, threshold = "INFO", logdir = NA_character_, resultdir = NA_character_, jobname
  = "BPJOB", manager.hostname = NA_character_, manager.port = NA_integer_, ...):
```

Return an object representing a SNOW cluster. The cluster is not created until `bpstart` is called. Named arguments in `...` are passed to `makeCluster`.

Accessors: Logging and results

In the following code, `x` is a `SnowParam` object.

```
bpprogressbar(x), bpprogressbar(x) <-value: Get or set the value to enable text progress
  bar. value must be a logical(1).
bpjobname(x), bpjobname(x) <-value: Get or set the job name.
bpRNGseed(x), bpRNGseed(x) <-value: Get or set the seed for random number generaton. value
  must be a numeric(1) or NULL.
bplog(x), bplog(x) <-value: Get or set the value to enable logging. value must be a logical(1).
bpthreshold(x), bpthreshold(x) <-value: Get or set the logging threshold. value must be a
  character(1) string of one of the levels defined in the futile.logger package: "TRACE",
  "DEBUG", "INFO", "WARN", "ERROR", or "FATAL".
bplogdir(x), bplogdir(x) <-value: Get or set the directory for the log file. value must be a
  character(1) path, not a file name. The file is written out as BPLOG.out. If no logdir is
  provided and bplog=TRUE log messages are sent to stdout.
bpresultdir(x), bpresultdir(x) <-value: Get or set the directory for the result files. value
  must be a character(1) path, not a file name. Separate files are written for each job with
  the prefix TASK (e.g., TASK1, TASK2, etc.). When no resultdir is provided the results are
  returned to the session as list.
```

Accessors: Back-end control

In the code below `x` is a `SnowParam` object. See the `?BiocParallelParam` man page for details on these accessors.

```
bpworkers(x), bpworkers(x) <-value, bpnworkers(x)
bptasks(x), bptasks(x) <-value
bpstart(x)
bpstop(x)
bpisup(x)
bpbackend(x), bpbackend(x) <-value
```

Accessors: Error Handling

In the code below `x` is a `SnowParam` object. See the `?BiocParallelParam` man page for details on these accessors.

```
bpstopOnError(x), bpstopOnError(x) <-value
```

Methods: Evaluation

In the code below `BPPARAM` is a `SnowParam` object. Full documentation for these functions are on separate man pages: see `?bpmapply`, `?bplapply`, `?bpvec`, `?bpiterate` and `?bpaggregate`.

```
bpmapply(FUN, ..., MoreArgs=NULL, SIMPLIFY=TRUE, USE.NAMES=TRUE, BPPARAM=bpparam())
bplapply(X, FUN, ..., BPPARAM=bpparam())
bpvec(X, FUN, ..., AGGREGATE=c, BPPARAM=bpparam())
bpiterate(ITER, FUN, ..., BPPARAM=bpparam())
bpaggregate(x, data, FUN, ..., BPPARAM=bpparam())
```

Methods: Other

In the code below `x` is a `SnowParam` object.

`show(x)`: Displays the `SnowParam` object.

`bpok(x)`: Returns a `logical()` vector: `FALSE` for any jobs that resulted in an error. `x` is the result list output by a `BiocParallel` function such as `bplapply` or `bpmapply`.

Coercion

`as(from, "SnowParam")`: Creates a `SnowParam` object from a `SOCKcluster` or `spawnedMPIcluster` object. Instances created in this way cannot be started or stopped.

Global Options

The global option `mc.cores` influences the number of workers determined by `snowWorkers()` (described above) or `multicoreWorkers()` (see [multicoreWorkers](#)).

Workers communicate to the master through socket connections. Socket connections require a hostname and port. These are determined by arguments `manager.hostname` and `manager.port`; default values are influenced by global options.

The default manager hostname is "localhost" when the number of workers are specified as a `numeric(1)`, and `Sys.info()[["nodename"]]` otherwise. The hostname can be over-ridden by the environment variable `MASTER`, or the global option `bphost` (e.g., `options(bphost=Sys.info()[["nodename"]])`).

The default port is chosen as a random value between 11000 and 11999. The port may be over-ridden by the environment variable `R_PARALLEL_PORT` or `PORT`, and by the option `ports`, e.g., `options(ports=12345L)`.

Author(s)

Martin Morgan and Valerie Obenchain.

See Also

- register for registering parameter classes for use in parallel evaluation.
- [MulticoreParam](#) for computing in shared memory
- [BatchJobsParam](#) for computing with cluster schedulers
- [DoparParam](#) for computing with foreach
- [SerialParam](#) for non-parallel evaluation

Examples

```
## -----
## Job configuration:
## -----

## SnowParam supports distributed memory computing. The object fields
## control the division of tasks, error handling, logging and result
## format.
bpparam <- SnowParam()
bpparam

## Fields are modified with accessors of the same name:
bplog(bpparam) <- TRUE
dir.create(resultdir <- tempfile())
bpresultdir(bpparam) <- resultdir
bpparam

## -----
## Logging:
## -----

## When 'log == TRUE' the workers use a custom script (in BiocParallel)
## that enables logging and access to other job statistics. Log messages
## are returned as each job completes rather than waiting for all to
## finish.

## In 'fun', a value of 'x = 1' will throw a warning, 'x = 2' is ok
## and 'x = 3' throws an error. Because 'x = 1' sleeps, the warning
## should return after the error.

X <- 1:3
fun <- function(x) {
  if (x == 1) {
    Sys.sleep(2)
    if (TRUE & c(TRUE, TRUE)) ## warning
      x
  } else if (x == 2) {
    x ## ok
  } else if (x == 3) {
    sqrt("FOO") ## error
  }
}

## By default logging is off. Turn it on with the bplog()<- setter
## or by specifying 'log = TRUE' in the constructor.
bpparam <- SnowParam(3, log = TRUE, stop.on.error = FALSE)
```

```

tryCatch({
  bplapply(X, fun, BPPARAM = bpparam)
}, error=identity)

## When a 'logdir' location is given the messages are redirected to a
## file:
## Not run:
dir.create(logdir <- tempfile())
bplogdir(bpparam) <- logdir
bplapply(X, fun, BPPARAM = bpparam)
list.files(bplogdir(bpparam))

## End(Not run)

## -----
## Managing results:
## -----

## By default results are returned as a list. When 'resultdir' is given
## files are saved in the directory specified by job, e.g., 'TASK1.Rda',
## 'TASK2.Rda', etc.
## Not run:
dir.create(resultdir <- tempfile())
bpparam <- SnowParam(2, resultdir = resultdir)
bplapply(X, fun, BPPARAM = bpparam)
list.files(bpresultdir(bpparam))

## End(Not run)

## -----
## Error handling:
## -----

## When 'stop.on.error' is TRUE the process returns as soon as an error
## is thrown.

## When 'stop.on.error' is FALSE all computations are attempted. Partial
## results are returned along with errors. Use bpttry() to see the
## partial results
bpparam <- SnowParam(2, stop.on.error = FALSE)
res <- bpttry(bplapply(list(1, "two", 3, 4), sqrt, BPPARAM = bpparam))
res

## Calling bpok() on the result list returns TRUE for elements with no
## error.
bpok(res)

## -----
## Random number generation:
## -----

## Random number generation is controlled with the 'RNGseed' field.
## This seed is passed to parallel::clusterSetRNGStream
## which uses the L'Ecuyer-CMRG random number generator and distributes
## streams to members of the cluster.

bpparam <- SnowParam(3, RNGseed = 7739465)

```



```
bplapply(seq_len(bpnworkers(bpparam)), function(i) rnorm(1),  
        BPPARAM = bpparam)
```

Index

* classes

BiocParallelParam-class, [8](#)
DoparParam-class, [30](#)
MulticoreParam-class, [33](#)
SerialParam-class, [41](#)
SnowParam-class, [42](#)

* interface

bpvectorize, [26](#)

* manip

bpiterate, [12](#)
bplapply, [15](#)
bpmapapply, [18](#)
bpschedule, [20](#)
bptry, [21](#)
bpvalidate, [22](#)
bpvec, [24](#)
register, [39](#)

* methods

BiocParallelParam-class, [8](#)
bpiterate, [12](#)
MulticoreParam-class, [33](#)
SnowParam-class, [42](#)

* package

BiocParallel-package, [2](#)
.BiocParallelParam_prototype
(DeveloperInterface), [27](#)
.bpiterate_impl (DeveloperInterface), [27](#)
.bplapply_impl (DeveloperInterface), [27](#)
.bpstart_impl (DeveloperInterface), [27](#)
.bpstop_impl (DeveloperInterface), [27](#)
.bpworker_impl (DeveloperInterface), [27](#)
.close (DeveloperInterface), [27](#)
.close, ANY-method (DeveloperInterface),
[27](#)
.close, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)
.prototype_update (DeveloperInterface),
[27](#)
.recv (DeveloperInterface), [27](#)
.recv, ANY-method (DeveloperInterface),
[27](#)
.recv, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)

.recv_all (DeveloperInterface), [27](#)
.recv_all, ANY-method
(DeveloperInterface), [27](#)
.recv_all, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)
.recv_any (DeveloperInterface), [27](#)
.recv_any, ANY-method
(DeveloperInterface), [27](#)
.recv_any, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)
.send (DeveloperInterface), [27](#)
.send, ANY-method (DeveloperInterface),
[27](#)
.send, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)
.send_all (DeveloperInterface), [27](#)
.send_all, ANY-method
(DeveloperInterface), [27](#)
.send_to (DeveloperInterface), [27](#)
.send_to, ANY-method
(DeveloperInterface), [27](#)
.send_to, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)

aggregate, [11](#), [12](#)

BatchJobsParam, [37](#), [47](#)
BatchJobsParam (BatchJobsParam-class), [3](#)
BatchJobsParam-class, [3](#)
batchtoolsCluster
(BatchtoolsParam-class), [5](#)
BatchtoolsParam, [10](#), [13](#)
BatchtoolsParam
(BatchtoolsParam-class), [5](#)
BatchtoolsParam-class, [5](#)
batchtoolsRegistryargs
(BatchtoolsParam-class), [5](#)
batchtoolsTemplate
(BatchtoolsParam-class), [5](#)
batchtoolsWorkers
(BatchtoolsParam-class), [5](#)
BiocParallel (BiocParallel-package), [2](#)
BiocParallel-package, [2](#)

- BiocParallelParam, [11](#), [13](#), [16](#), [18](#), [19](#), [21](#),
[25–27](#), [40](#)
- BiocParallelParam
(BiocParallelParam-class), [8](#)
- BiocParallelParam-class, [8](#)
- bpaggregate, [11](#)
- bpaggregate, ANY, missing-method
(bpaggregate), [11](#)
- bpaggregate, data.frame, BiocParallelParam-method
(bpaggregate), [11](#)
- bpaggregate, formula, BiocParallelParam-method
(bpaggregate), [11](#)
- bpaggregate, matrix, BiocParallelParam-method
(bpaggregate), [11](#)
- bpbackend, [4](#), [6](#), [30](#)
- bpbackend (BiocParallelParam-class), [8](#)
- bpbackend, BatchJobsParam-method
(BatchJobsParam-class), [3](#)
- bpbackend, BatchtoolsParam-method
(BatchtoolsParam-class), [5](#)
- bpbackend, DoparParam-method
(DoparParam-class), [30](#)
- bpbackend, missing-method
(BiocParallelParam-class), [8](#)
- bpbackend, SerialParam-method
(SerialParam-class), [41](#)
- bpbackend, SnowParam-method
(SnowParam-class), [42](#)
- bpbackend, TransientMulticoreParam-method
(MulticoreParam-class), [33](#)
- bpbackend<- (BiocParallelParam-class), [8](#)
- bpbackend<- , BatchJobsParam
(BatchJobsParam-class), [3](#)
- bpbackend<- , DoparParam, SOCKcluster-method
(DoparParam-class), [30](#)
- bpbackend<- , missing, ANY-method
(BiocParallelParam-class), [8](#)
- bpbackend<- , SnowParam, cluster-method
(SnowParam-class), [42](#)
- bpexportglobals
(BiocParallelParam-class), [8](#)
- bpexportglobals, BiocParallelParam-method
(BiocParallelParam-class), [8](#)
- bpexportglobals<-
(BiocParallelParam-class), [8](#)
- bpexportglobals<- , BiocParallelParam, logical-method
(BiocParallelParam-class), [8](#)
- bpisup, [4](#), [6](#), [30](#), [42](#)
- bpisup (BiocParallelParam-class), [8](#)
- bpisup, ANY-method
(BiocParallelParam-class), [8](#)
- bpisup, BatchJobsParam-method
(BatchJobsParam-class), [3](#)
- bpisup, BatchtoolsParam-method
(BatchtoolsParam-class), [5](#)
- bpisup, DoparParam-method
(DoparParam-class), [30](#)
- bpisup, missing-method
(BiocParallelParam-class), [8](#)
- bpisup, MulticoreParam-method
(MulticoreParam-class), [33](#)
- bpisup, SerialParam-method
(SerialParam-class), [41](#)
- bpisup, SnowParam-method
(SnowParam-class), [42](#)
- bpiterate, [12](#)
- bpiterate, ANY, ANY, BatchJobsParam-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, BatchtoolsParam-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, BiocParallelParam-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, DoparParam-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, missing-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, SerialParam-method
(bpiterate), [12](#)
- bpiterate, ANY, ANY, SnowParam-method
(bpiterate), [12](#)
- bpjobname (BiocParallelParam-class), [8](#)
- bpjobname, BiocParallelParam-method
(BiocParallelParam-class), [8](#)
- bpjobname<- (BiocParallelParam-class), [8](#)
- bpjobname<- , BiocParallelParam, character-method
(BiocParallelParam-class), [8](#)
- bplapply, [6](#), [13](#), [15](#), [22](#), [26](#), [42](#)
- bplapply, ANY, BatchJobsParam-method
(bplapply), [15](#)
- bplapply, ANY, BatchtoolsParam-method
(BatchtoolsParam-class), [5](#)
- bplapply, ANY, BiocParallelParam-method
(bplapply), [15](#)
- bplapply, ANY, DoparParam-method
(bplapply), [15](#)
- bplapply, ANY, list-method (bplapply), [15](#)
- bplapply, ANY, missing-method (bplapply),
[15](#)
- bplapply, ANY, SerialParam-method
(bplapply), [15](#)
- bplapply, ANY, SnowParam-method
(bplapply), [15](#)
- bplog (BiocParallelParam-class), [8](#)
- bplog, BiocParallelParam-method

- (BiocParallelParam-class), 8
- bplog, SerialParam-method
 - (SerialParam-class), 41
- bplog, SnowParam-method
 - (SnowParam-class), 42
- bplog<- (BiocParallelParam-class), 8
- bplog<-, SerialParam, logical-method
 - (SerialParam-class), 41
- bplog<-, SnowParam, logical-method
 - (SnowParam-class), 42
- bplogdir (BiocParallelParam-class), 8
- bplogdir, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bplogdir, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bplogdir, SerialParam-method
 - (SerialParam-class), 41
- bplogdir<- (BiocParallelParam-class), 8
- bplogdir<-, BatchtoolsParam, character-method
 - (BatchtoolsParam-class), 5
- bplogdir<-, BiocParallelParam, character-method
 - (BiocParallelParam-class), 8
- bplogdir<-, SerialParam, character-method
 - (SerialParam-class), 41
- bploop, 16
- bpmapply, 18
- bpmapply, ANY, BiocParallelParam-method
 - (bpmapply), 18
- bpmapply, ANY, list-method (bpmapply), 18
- bpmapply, ANY, missing-method (bpmapply), 18
- bpnworkers, 4, 6, 30
- bpnworkers (BiocParallelParam-class), 8
- bpok, 19
- bpparam (register), 39
- bpprogressbar
 - (BiocParallelParam-class), 8
- bpprogressbar, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpprogressbar<-
 - (BiocParallelParam-class), 8
- bpprogressbar<-, BiocParallelParam, logical-method
 - (BiocParallelParam-class), 8
- bpresultdir (BiocParallelParam-class), 8
- bpresultdir, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpresultdir<-
 - (BiocParallelParam-class), 8
- bpresultdir<-, BiocParallelParam, character-method
 - (BiocParallelParam-class), 8
- bpRNGseed (BiocParallelParam-class), 8
- bpRNGseed, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bpRNGseed, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpRNGseed<- (BiocParallelParam-class), 8
- bpRNGseed<-, BatchtoolsParam, numeric-method
 - (BatchtoolsParam-class), 5
- bpRNGseed<-, BiocParallelParam, NULL-method
 - (BiocParallelParam-class), 8
- bpRNGseed<-, BiocParallelParam, numeric-method
 - (BiocParallelParam-class), 8
- bprunMPIslave (bploop), 16
- bpschedule, 20
- bpschedule, ANY-method (bpschedule), 20
- bpschedule, BatchJobsParam-method
 - (BatchJobsParam-class), 3
- bpschedule, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bpschedule, missing-method (bpschedule), 20
- bpschedule, MulticoreParam-method
 - (MulticoreParam-class), 33
- bpstart, 4, 6, 30, 42
- bpstart (BiocParallelParam-class), 8
- bpstart, ANY-method
 - (BiocParallelParam-class), 8
- bpstart, BatchJobsParam-method
 - (BatchJobsParam-class), 3
- bpstart, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bpstart, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpstart, DoparParam-method
 - (DoparParam-class), 30
- bpstart, missing-method
 - (BiocParallelParam-class), 8
- bpstart, SerialParam-method
 - (SerialParam-class), 41
- bpstart, SnowParam-method
 - (SnowParam-class), 42
- bpstart, TransientMulticoreParam-method
 - (MulticoreParam-class), 33
- bpstop, 4, 6, 30, 42
- bpstop (BiocParallelParam-class), 8
- bpstop, ANY-method
 - (BiocParallelParam-class), 8
- bpstop, BatchJobsParam-method
 - (BatchJobsParam-class), 3
- bpstop, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bpstop, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpstop, DoparParam-method

- (DoparParam-class), 30
- bpstop, missing-method
 - (BiocParallelParam-class), 8
- bpstop, SerialParam-method
 - (SerialParam-class), 41
- bpstop, SnowParam-method
 - (SnowParam-class), 42
- bpstop, TransientMulticoreParam-method
 - (MulticoreParam-class), 33
- bpstopOnError
 - (BiocParallelParam-class), 8
- bpstopOnError, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpstopOnError<-
 - (BiocParallelParam-class), 8
- bpstopOnError<-, BiocParallelParam, logical-method
 - (BiocParallelParam-class), 8
- bpstopOnError<-, DoparParam, logical-method
 - (BiocParallelParam-class), 8
- bptasks (BiocParallelParam-class), 8
- bptasks, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bptasks<- (BiocParallelParam-class), 8
- bptasks<-, BiocParallelParam, numeric-method
 - (BiocParallelParam-class), 8
- bpthreshold (BiocParallelParam-class), 8
- bpthreshold, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpthreshold, SnowParam-method
 - (SnowParam-class), 42
- bpthreshold<-
 - (BiocParallelParam-class), 8
- bpthreshold<-, SerialParam, character-method
 - (SerialParam-class), 41
- bpthreshold<-, SnowParam, character-method
 - (SnowParam-class), 42
- bptimeout (BiocParallelParam-class), 8
- bptimeout, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bptimeout<- (BiocParallelParam-class), 8
- bptimeout<-, BiocParallelParam, numeric-method
 - (BiocParallelParam-class), 8
- bpttry, 21
- bpvalidate, 22
- bpvec, 13, 16, 19, 24, 27, 30, 42
- bpvec, ANY, BiocParallelParam-method
 - (bpvec), 24
- bpvec, ANY, list-method (bpvec), 24
- bpvec, ANY, missing-method (bpvec), 24
- bpvectorize, 26
- bpvectorize, ANY, ANY-method
 - (bpvectorize), 26
- bpvectorize, ANY, missing-method
 - (bpvectorize), 26
- bpworkers, 4, 6, 30, 42
- bpworkers (BiocParallelParam-class), 8
- bpworkers, BatchJobsParam-method
 - (BatchJobsParam-class), 3
- bpworkers, BatchtoolsParam-method
 - (BatchtoolsParam-class), 5
- bpworkers, BiocParallelParam-method
 - (BiocParallelParam-class), 8
- bpworkers, DoparParam-method
 - (DoparParam-class), 30
- bpworkers, missing-method
 - (BiocParallelParam-class), 8
- bpworkers, SerialParam-method
 - (SerialParam-class), 41
- bpworkers, SnowParam-method
 - (SnowParam-class), 42
- bpworkers<- (BiocParallelParam-class), 8
- bpworkers<-, MulticoreParam, numeric-method
 - (MulticoreParam-class), 33
- bpworkers<-, SnowParam, character-method
 - (SnowParam-class), 42
- bpworkers<-, SnowParam, numeric-method
 - (SnowParam-class), 42
- chunk, 3
- ClusterFunctions, 3
- coerce, SOCKcluster, DoparParam-method
 - (DoparParam-class), 30
- coerce, SOCKcluster, SnowParam-method
 - (SnowParam-class), 42
- coerce, spawnedMPIcluster, SnowParam-method
 - (SnowParam-class), 42
- DeveloperInterface, 27
- DoparParam, 10, 21, 37, 40, 47
- DoparParam (DoparParam-class), 30
- DoparParam-class, 30
- getwd, 3
- ipcid (ipcmutex), 31
- ipclock (ipcmutex), 31
- ipclocked (ipcmutex), 31
- ipcmutex, 31
- ipcremove (ipcmutex), 31
- ipcreset (ipcmutex), 31
- ipctrylock (ipcmutex), 31
- ipcunlock (ipcmutex), 31
- ipcvalue (ipcmutex), 31
- ipcyield (ipcmutex), 31
- lapply, 15, 16

length, TransientMulticoreParam-method
 (MulticoreParam-class), 33
loadRegistry, 3

makeCluster, 35, 44
makeRegistry, 3, 6
mapply, 18
mclapply, 16, 18
MulticoreParam, 10, 21, 40, 47
MulticoreParam (MulticoreParam-class),
 33
MulticoreParam-class, 33
multicoreWorkers, 46
multicoreWorkers
 (MulticoreParam-class), 33

parallel, 2
print.remote_error
 (BiocParallelParam-class), 8
pvec, 26

register, 21, 39
registered (register), 39

SerialParam, 10, 27, 37, 47
SerialParam (SerialParam-class), 41
SerialParam-class, 41
show, BatchJobsParam-method
 (BatchJobsParam-class), 3
show, BatchtoolsParam-method
 (BatchtoolsParam-class), 5
show, BiocParallel-method
 (BiocParallelParam-class), 8
show, DoparParam-method
 (DoparParam-class), 30
show, MulticoreParam-method
 (MulticoreParam-class), 33
show, SnowParam-method
 (SnowParam-class), 42
simplify2array, 11, 18
SnowParam, 10, 21, 35, 37, 40, 41
SnowParam (SnowParam-class), 42
SnowParam-class, 42
snowWorkers (SnowParam-class), 42
submitJobs, 3

tryCatch, 22