

Package ‘VIRF’

October 12, 2022

Type Package

Title Computation of Volatility Impulse Response Function of Multivariate Time Series

Version 0.1.0

Author Dr. Ranjit Kumar Paul and Mr. Ankit Tanwar

Maintainer Dr. Ranjit Kumar Paul <ranjitstat@gmail.com>

Description

Computation of volatility impulse response function for multivariate time series model using algorithm by Jin, Lin and Tamvakis (2012) <doi.org/10.1016/j.eneco.2012.03.003>.

License GPL

Imports stats, rmgarch, mgarchBEKK, gnm, expm, BigVAR, ks, matrixcalc, matlib

LazyData TRUE

NeedsCompilation no

Repository CRAN

Date/Publication 2019-05-01 06:50:03 UTC

R topics documented:

VIRF 1

Index 3

VIRF

Volatility Impulse Response Function

Description

Provide information about the impact of independent shocks on volatility.

Usage

```
VIRF(data, shock)
```

Arguments

data	log return multivariate time series
shock	shock time point from time series

Value

virfresult	List containing variance and covariance values
------------	--

References

Anthony, N.R. and Ahammad, S.M. 2016. Investigating the interdependency of agricultural production volatility spillovers between Bangladesh, India, and Pakistan. *Review of Urban and Regional Development Studies*, 28, 32 to 54 Jin, X., Lin, S.X. and Tamvakis, M. 2012. Volatility transmission and volatility impulse response functions in crude oil markets. *Energy Economics*, 34, 2125 to 2134

Examples

```
k=3 #number of series
p=6 # maximum lag order
ns=100 #number of simulations
B=matrix(0,nrow=k,ncol=p*k)
A1<- matrix(c(.4,-.02,.01,-.02,.3,.02,.01,.04,.3),ncol=3,nrow=3)
A2 <- matrix(c(.2,0,0,0,.3,0,0,0,.13),ncol=3,nrow=3)
B[,1:k]=A1
B[, (4*k+1):(5*k)]=A2
A <- BigVAR::VarptoVar1MC(B,p,k)
Y <-BigVAR::MultVarSim(k,A,p,.1*diag(k),ns)
lr<-VIRF(Y,40) # Y: multivariate time series data, shock time point: 40
print(lr)
```

Index

VIRF, 1