

Package ‘brickster’

September 4, 2025

Title R Toolkit for 'Databricks'

Version 0.2.9

Description Collection of utilities that improve using 'Databricks' from R.
Primarily functions that wrap specific 'Databricks' APIs
(<https://docs.databricks.com/api>), 'RStudio' connection pane support, quality
of life functions to make 'Databricks' simpler to use.

License Apache License (>= 2)

Encoding UTF-8

Depends R (>= 4.1.0)

Imports base64enc, cli, curl, DBI, dbplyr, dplyr, glue, httr2 (>= 1.0.4), ini, jsonlite, methods, nanoarrow, purrr, R6, rlang, tibble, utils

Suggests arrow, testthat (>= 3.0.0), grid, huxtable, htmltools, knitr, magick, rmarkdown, withr

RoxygenNote 7.3.2

VignetteBuilder knitr

URL <https://github.com/databrickslabs/brickster>

Config/testthat/edition 3

NeedsCompilation no

Author Zac Davies [aut, cre],
Rafi Kurlansik [aut],
Databricks [cph, fnd]

Maintainer Zac Davies <zac@databricks.com>

Repository CRAN

Date/Publication 2025-09-04 11:30:02 UTC

Contents

access_control_request	8
access_control_req_group	8

access_control_req_user	9
add_lib_path	10
aws_attributes	10
azure_attributes	12
close_workspace	13
cluster_autoscale	14
cluster_log_conf	14
condition_task	15
copy_to.DatabricksConnection	16
cron_schedule	17
databricks-dbi	17
databricks-dbplyr	17
DatabricksConnection-class	18
DatabricksDriver-class	18
DatabricksResult-class	18
DatabricksSQL	18
dbAppendTable,DatabricksConnection,character,data.frame-method	19
dbAppendTable,DatabricksConnection,Id,data.frame-method	19
dbBegin,DatabricksConnection-method	20
dbClearResult,DatabricksResult-method	20
dbColumnInfo,DatabricksResult-method	21
dbCommit,DatabricksConnection-method	21
dbConnect,DatabricksDriver-method	22
dbDataType,DatabricksConnection-method	23
dbDisconnect,DatabricksConnection-method	23
dbExecute,DatabricksConnection,character-method	24
dbExistsTable,DatabricksConnection,AsIs-method	24
dbExistsTable,DatabricksConnection,character-method	25
dbExistsTable,DatabricksConnection,Id-method	25
dbFetch,DatabricksResult-method	26
dbfs_storage_info	26
dbGetInfo,DatabricksConnection-method	27
dbGetQuery,DatabricksConnection,character-method	27
dbGetRowCount,DatabricksResult-method	28
dbGetRowsAffected,DatabricksResult-method	29
dbGetStatement,DatabricksResult-method	29
dbHasCompleted,DatabricksResult-method	30
dbIsValid,DatabricksConnection-method	30
dbListFields,DatabricksConnection,AsIs-method	31
dbListFields,DatabricksConnection,character-method	31
dbListTables,DatabricksConnection-method	32
dbplyr_edition.DatabricksConnection	32
dbQuoteIdentifier,DatabricksConnection,character-method	33
dbQuoteIdentifier,DatabricksConnection,Id-method	33
dbQuoteIdentifier,DatabricksConnection,SQL-method	34
dbRollback,DatabricksConnection-method	34
dbSendQuery,DatabricksConnection,character-method	35
dbSendStatement,DatabricksConnection,character-method	35

dbWriteTable,DatabricksConnection,AsIs,data.frame-method	36
dbWriteTable,DatabricksConnection,character,data.frame-method	37
dbWriteTable,DatabricksConnection,Id,data.frame-method	38
db_cluster_action	39
db_cluster_create	39
db_cluster_delete	42
db_cluster_edit	43
db_cluster_events	46
db_cluster_get	47
db_cluster_list	48
db_cluster_list_node_types	49
db_cluster_list_zones	50
db_cluster_perm_delete	51
db_cluster_pin	52
db_cluster_resize	53
db_cluster_restart	54
db_cluster_runtime_versions	54
db_cluster_start	55
db_cluster_terminate	56
db_cluster_unpin	57
db_collect.DatabricksConnection	58
db_context_command_cancel	59
db_context_command_run	59
db_context_command_run_and_wait	60
db_context_command_status	61
db_context_create	62
db_context_destroy	63
db_context_manager	64
db_context_status	65
db_current_cloud	66
db_current_user	66
db_current_workspace_id	67
db_dbfs_add_block	67
db_dbfs_close	68
db_dbfs_create	69
db_dbfs_delete	70
db_dbfs_get_status	71
db_dbfs_list	72
db_dbfs_mkdirs	73
db_dbfs_move	74
db_dbfs_put	75
db_dbfs_read	76
db_host	77
db_jobs_create	78
db_jobs_delete	79
db_jobs_get	80
db_jobs_list	81
db_jobs_repair_run	82

db_jobs_reset	83
db_jobs_runs_cancel	85
db_jobs_runs_delete	86
db_jobs_runs_export	86
db_jobs_runs_get	87
db_jobs_runs_get_output	88
db_jobs_runs_list	88
db_jobs_runs_submit	90
db_jobs_run_now	91
db_jobs_update	92
db_libs_all_cluster_statuses	93
db_libs_cluster_status	94
db_libs_install	95
db_libs_uninstall	96
db_mlflow_model_approve_transition_req	97
db_mlflow_model_delete_transition_req	98
db_mlflow_model_open_transition_reqs	99
db_mlflow_model_reject_transition_req	99
db_mlflow_model_transition_req	100
db_mlflow_model_transition_stage	101
db_mlflow_model_version_comment	103
db_mlflow_model_version_comment_delete	104
db_mlflow_model_version_comment_edit	104
db_mlflow_registered_model_details	105
db_perform_request	106
db_query_create	107
db_query_delete	108
db_query_get	109
db_query_list	109
db_query_update	110
db_read_netrc	111
db_repl	112
db_repo_create	113
db_repo_delete	113
db_repo_get	114
db_repo_get_all	115
db_repo_update	116
db_request	117
db_request_json	117
db_req_error_body	118
db_secrets_delete	118
db_secrets_list	119
db_secrets_put	120
db_secrets_scope_acl_delete	121
db_secrets_scope_acl_get	122
db_secrets_scope_acl_list	123
db_secrets_scope_acl_put	124
db_secrets_scope_create	125

db_secrets_scope_delete	127
db_secrets_scope_list_all	128
db_sql_exec_cancel	128
db_sql_exec_poll_for_success	129
db_sql_exec_query	130
db_sql_exec_result	132
db_sql_exec_status	133
db_sql_global_warehouse_get	134
db_sql_query	134
db_sql_query_history	136
db_sql_warehouse_create	137
db_sql_warehouse_delete	138
db_sql_warehouse_edit	139
db_sql_warehouse_get	141
db_sql_warehouse_list	141
db_sql_warehouse_start	142
db_sql_warehouse_stop	143
db_token	143
db_uc_catalogs_get	144
db_uc_catalogs_list	145
db_uc_schemas_get	146
db_uc_schemas_list	147
db_uc_tables_delete	148
db_uc_tables_exists	149
db_uc_tables_get	150
db_uc_tables_list	151
db_uc_tables_summaries	152
db_uc_volumes_create	153
db_uc_volumes_delete	154
db_uc_volumes_get	155
db_uc_volumes_list	156
db_uc_volumes_update	157
db_volume_delete	158
db_volume_dir_create	159
db_volume_dir_delete	159
db_volume_dir_exists	160
db_volume_file_exists	161
db_volume_list	162
db_volume_read	162
db_volume_upload_dir	163
db_volume_write	164
db_vs_endpoints_create	165
db_vs_endpoints_delete	166
db_vs_endpoints_get	167
db_vs_endpoints_list	167
db_vs_indexes_create	168
db_vs_indexes_delete	169
db_vs_indexes_delete_data	170

db_vs_indexes_get	171
db_vs_indexes_list	171
db_vs_indexes_query	172
db_vs_indexes_query_next_page	174
db_vs_indexes_scan	175
db_vs_indexes_sync	176
db_vs_indexes_upsert_data	177
db_workspace_delete	177
db_workspace_export	178
db_workspace_get_status	180
db_workspace_import	180
db_workspace_list	182
db_workspace_mkdirs	182
db_wsids	183
delta_sync_index_spec	184
direct_access_index_spec	185
docker_image	186
email_notifications	187
embedding_source_column	188
embedding_vector_column	188
file_storage_info	189
for_each_task	189
gcp_attributes	190
get_and_start_cluster	191
get_and_start_warehouse	192
get_latest_dbr	193
git_source	194
init_script_info	194
in_databricks_nb	195
is.access_control_request	195
is.access_control_req_group	196
is.access_control_req_user	196
is.aws_attributes	197
is.azure_attributes	197
is.cluster_autoscale	198
is.cluster_log_conf	198
is.condition_task	199
is.cron_schedule	199
is.dbfs_storage_info	200
is.delta_sync_index	200
is.direct_access_index	201
is.docker_image	201
is.email_notifications	202
is.embedding_source_column	202
is.embedding_vector_column	203
is.file_storage_info	203
is.for_each_task	204
is.gcp_attributes	204

is.git_source	205
is.init_script_info	205
is.job_task	206
is.libraries	206
is.library	207
is.lib_cran	207
is.lib_egg	208
is.lib_jar	208
is.lib_maven	209
is.lib_pypi	209
is.lib_whl	210
is.new_cluster	210
is.notebook_task	211
is.pipeline_task	211
is.python_wheel_task	212
is.run_job_task	212
is.s3_storage_info	213
is.spark_jar_task	213
is.spark_python_task	214
is.spark_submit_task	214
is.sql_file_task	215
is.sql_query_task	215
is.valid_task_type	216
is.vector_search_index_spec	216
job_task	217
job_tasks	218
libraries	219
lib_cran	219
lib_egg	220
lib_jar	220
lib_maven	221
lib_pypi	221
lib_whl	222
new_cluster	222
notebook_task	224
open_workspace	225
pipeline_task	226
python_wheel_task	226
remove_lib_path	227
run_job_task	227
s3_storage_info	228
show,DatabricksConnection-method	229
show,DatabricksDriver-method	229
show,DatabricksResult-method	230
spark_jar_task	230
spark_python_task	231
spark_submit_task	231
sql_file_task	232

sql_query_fields.DatabricksConnection 232

sql_query_save.DatabricksConnection 233

sql_query_task 234

sql_table_analyze.DatabricksConnection 234

wait_for_lib_installs 235

Index 236

access_control_request

Access Control Request

Description

Access Control Request

Usage

access_control_request(...)

Arguments

... Instances of [access_control_req_user\(\)](#) or [access_control_req_group\(\)](#).

See Also

[db_jobs_create\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_update\(\)](#)

access_control_req_group

Access Control Request for Group

Description

Access Control Request for Group

Usage

```
access_control_req_group(  
  group,  
  permission_level = c("CAN_MANAGE", "CAN_MANAGE_RUN", "CAN_VIEW")  
)
```

Arguments

group	Group name. There are two built-in groups: users for all users, and admins for administrators.
permission_level	Permission level to grant. One of CAN_MANAGE, CAN_MANAGE_RUN, CAN_VIEW.

See Also

[access_control_request\(\)](#)

Other Access Control Request Objects: [access_control_req_user\(\)](#)

access_control_req_user

Access Control Request For User

Description

Access Control Request For User

Usage

```
access_control_req_user(  
    user_name,  
    permission_level = c("CAN_MANAGE", "CAN_MANAGE_RUN", "CAN_VIEW", "IS_OWNER")  
)
```

Arguments

user_name	Email address for the user.
permission_level	Permission level to grant. One of CAN_MANAGE, CAN_MANAGE_RUN, CAN_VIEW, IS_OWNER.

See Also

[access_control_request\(\)](#)

Other Access Control Request Objects: [access_control_req_group\(\)](#)

add_lib_path	<i>Add Library Path</i>
--------------	-------------------------

Description

Add Library Path

Usage

```
add_lib_path(path, after, version = FALSE)
```

Arguments

path	Directory that will added as location for which packages are searched. Recursively creates the directory if it doesn't exist. On Databricks remember to use /dbfs/ or /Volumes/... as a prefix.
after	Location at which to append the path value after.
version	If TRUE will add the R version string to the end of path. This is recommended if using different R versions and sharing a common path between users.

Details

This functions primary use is when using Databricks notebooks or hosted RStudio, however, it works anywhere.

See Also

`base::libPaths()`, `remove_lib_path()`

aws_attributes	<i>AWS Attributes</i>
----------------	-----------------------

Description

AWS Attributes

Usage

```
aws_attributes(
  first_on_demand = 1,
  availability = c("SPOT_WITH_FALLBACK", "SPOT", "ON_DEMAND"),
  zone_id = NULL,
  instance_profile_arn = NULL,
  spot_bid_price_percent = 100,
  ebs_volume_type = c("GENERAL_PURPOSE_SSD", "THROUGHPUT_OPTIMIZED_HDD"),
```

```

    ebs_volume_count = 1,
    ebs_volume_size = NULL,
    ebs_volume_iops = NULL,
    ebs_volume_throughput = NULL
)

```

Arguments

`first_on_demand`

Number of nodes of the cluster that will be placed on on-demand instances. If this value is greater than 0, the cluster driver node will be placed on an on-demand instance. If this value is greater than or equal to the current cluster size, all nodes will be placed on on-demand instances. If this value is less than the current cluster size, `first_on_demand` nodes will be placed on on-demand instances and the remainder will be placed on availability instances. This value does not affect cluster size and cannot be mutated over the lifetime of a cluster.

`availability`

One of SPOT_WITH_FALLBACK, SPOT, ON_DEMAND. Type used for all subsequent nodes past the `first_on_demand` ones. If `first_on_demand` is zero, this availability type will be used for the entire cluster.

`zone_id`

Identifier for the availability zone/datacenter in which the cluster resides. You have three options: availability zone in same region as the Databricks deployment, `auto` which selects based on available IPs, `NULL` which will use the default availability zone.

`instance_profile_arn`

Nodes for this cluster will only be placed on AWS instances with this instance profile. If omitted, nodes will be placed on instances without an instance profile. The instance profile must have previously been added to the Databricks environment by an account administrator. This feature may only be available to certain customer plans.

`spot_bid_price_percent`

The max price for AWS spot instances, as a percentage of the corresponding instance type's on-demand price. For example, if this field is set to 50, and the cluster needs a new `i3.xlarge` spot instance, then the max price is half of the price of on-demand `i3.xlarge` instances. Similarly, if this field is set to 200, the max price is twice the price of on-demand `i3.xlarge` instances. If not specified, the default value is 100. When spot instances are requested for this cluster, only spot instances whose max price percentage matches this field will be considered. For safety, we enforce this field to be no more than 10000.

`ebs_volume_type`

Either `GENERAL_PURPOSE_SSD` or `THROUGHPUT_OPTIMIZED_HDD`

`ebs_volume_count`

The number of volumes launched for each instance. You can choose up to 10 volumes. This feature is only enabled for supported node types. Legacy node types cannot specify custom EBS volumes. For node types with no instance store, at least one EBS volume needs to be specified; otherwise, cluster creation will fail. These EBS volumes will be mounted at `/ebs0`, `/ebs1`, and etc. Instance store volumes will be mounted at `/local_disk0`, `/local_disk1`, and etc.

If EBS volumes are attached, Databricks will configure Spark to use only the EBS volumes for scratch storage because heterogeneously sized scratch devices can lead to inefficient disk utilization. If no EBS volumes are attached, Databricks will configure Spark to use instance store volumes.

If EBS volumes are specified, then the Spark configuration `spark.local.dir` will be overridden.

- ebs_volume_size

The size of each EBS volume (in GiB) launched for each instance. For general purpose SSD, this value must be within the range 100 - 4096. For throughput optimized HDD, this value must be within the range 500 - 4096.

Custom EBS volumes cannot be specified for the legacy node types (memory-optimized and compute-optimized).
- ebs_volume_iops

The number of IOPS per EBS gp3 volume. This value must be between 3000 and 16000. The value of IOPS and throughput is calculated based on AWS documentation to match the maximum performance of a gp2 volume with the same volume size.
- ebs_volume_throughput

The throughput per EBS gp3 volume, in MiB per second. This value must be between 125 and 1000.

Details

If `ebs_volume_iops`, `ebs_volume_throughput`, or both are not specified, the values will be inferred from the throughput and IOPS of a gp2 volume with the same disk size, by using the following calculation:

Disk size	IOPS	Throughput
Greater than 1000	3 times the disk size up to 16000	250
Between 170 and 1000	3000	250
Below 170	3000	128

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)

Other Cloud Attributes: [azure_attributes\(\)](#), [gcp_attributes\(\)](#)

azure_attributes	Azure Attributes
------------------	------------------

Description

Azure Attributes

Usage

```
azure_attributes(
  first_on_demand = 1,
  availability = c("SPOT_WITH_FALLBACK", "SPOT", "ON_DEMAND"),
  spot_bid_max_price = -1
)
```

Arguments

<code>first_on_demand</code>	Number of nodes of the cluster that will be placed on on-demand instances. If this value is greater than 0, the cluster driver node will be placed on an on-demand instance. If this value is greater than or equal to the current cluster size, all nodes will be placed on on-demand instances. If this value is less than the current cluster size, <code>first_on_demand</code> nodes will be placed on on-demand instances and the remainder will be placed on availability instances. This value does not affect cluster size and cannot be mutated over the lifetime of a cluster.
<code>availability</code>	One of SPOT_WITH_FALLBACK, SPOT, ON_DEMAND. Type used for all subsequent nodes past the <code>first_on_demand</code> ones. If <code>first_on_demand</code> is zero, this availability type will be used for the entire cluster.
<code>spot_bid_max_price</code>	The max bid price used for Azure spot instances. You can set this to greater than or equal to the current spot price. You can also set this to -1 (the default), which specifies that the instance cannot be evicted on the basis of price. The price for the instance will be the current price for spot instances or the price for a standard instance. You can view historical pricing and eviction rates in the Azure portal.

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)
 Other Cloud Attributes: [aws_attributes\(\)](#), [gcp_attributes\(\)](#)

close_workspace	<i>Close Databricks Workspace Connection</i>
-----------------	--

Description

Close Databricks Workspace Connection

Usage

```
close_workspace(host = db_host())
```

Arguments

<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
-------------------	---

Examples

```
## Not run:
close_workspace(host = db_host())

## End(Not run)
```

cluster_autoscale	<i>Cluster Autoscale</i>
-------------------	--------------------------

Description

Range defining the min and max number of cluster workers.

Usage

```
cluster_autoscale(min_workers, max_workers)
```

Arguments

min_workers	The minimum number of workers to which the cluster can scale down when underutilized. It is also the initial number of workers the cluster will have after creation.
max_workers	The maximum number of workers to which the cluster can scale up when overloaded. max_workers must be strictly greater than min_workers.

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)

cluster_log_conf	<i>Cluster Log Configuration</i>
------------------	----------------------------------

Description

Path to cluster log.

Usage

```
cluster_log_conf(dbfs = NULL, s3 = NULL)
```

Arguments

dbfs	Instance of dbfs_storage_info() .
s3	Instance of s3_storage_info() .

Details

dbfs and s3 are mutually exclusive, logs can only be sent to one destination.

See Also

Other Cluster Log Configuration Objects: [dbfs_storage_info\(\)](#), [s3_storage_info\(\)](#)

condition_task	<i>Condition Task</i>
----------------	-----------------------

Description

Condition Task

Usage

```
condition_task(  
  left,  
  right,  
  op = c("EQUAL_TO", "GREATER_THAN", "GREATER_THAN_OR_EQUAL", "LESS_THAN",  
        "LESS_THAN_OR_EQUAL", "NOT_EQUAL")  
)
```

Arguments

left	Left operand of the condition task. Either a string value or a job state or parameter reference.
right	Right operand of the condition task. Either a string value or a job state or parameter reference.
op	Operator, one of "EQUAL_TO", "GREATER_THAN", "GREATER_THAN_OR_EQUAL", "LESS_THAN", "LESS_THAN_OR_EQUAL", "NOT_EQUAL"

Details

The task evaluates a condition that can be used to control the execution of other tasks when the condition_task field is present. The condition task does not require a cluster to execute and does not support retries or notifications.

See Also

Other Task Objects: [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

copy_to.DatabricksConnection

Copy data frame to Databricks as table or view

Description

Copy data frame to Databricks as table or view

Usage

```
## S3 method for class 'DatabricksConnection'
copy_to(
  dest,
  df,
  name = deparse(substitute(df)),
  overwrite = FALSE,
  temporary = TRUE,
  ...
)
```

Arguments

dest	A DatabricksConnection object
df	Data frame to copy
name	Name for the table/view
overwrite	Whether to overwrite existing table/view
temporary	Whether to create as temporary view (default: TRUE, but NOT SUPPORTED - will error)
...	Additional arguments passed to dbWriteTable

Details

Note: temporary=TRUE will result in an error as temporary tables are not supported with the SQL Statement Execution API. Use temporary=FALSE to create regular tables.

Value

dbplyr table reference

cron_schedule	<i>Cron Schedule</i>
---------------	----------------------

Description

Cron Schedule

Usage

```
cron_schedule(  
  quartz_cron_expression,  
  timezone_id = "Etc/UTC",  
  pause_status = c("UNPAUSED", "PAUSED")  
)
```

Arguments

- quartz_cron_expression Cron expression using Quartz syntax that describes the schedule for a job. See [Cron Trigger](#) for details.
- timezone_id Java timezone ID. The schedule for a job is resolved with respect to this time-zone. See [Java TimeZone](#) for details.
- pause_status Indicate whether this schedule is paused or not. Either UNPAUSED (default) or PAUSED.

See Also

```
db\_jobs\_create\(\), db\_jobs\_reset\(\), db\_jobs\_update\(\)
```

databricks-dbi	<i>DBI Interface for Databricks SQL Warehouses</i>
----------------	--

Description

This file implements a standard DBI interface for Databricks SQL warehouses, built on top of the existing `db_sql_query()` infrastructure.

databricks-dbpolyr	<i>dbplyr Backend for Databricks SQL</i>
--------------------	--

Description

This file implements dbplyr backend support for Databricks SQL warehouses, enabling dplyr syntax to be translated to Databricks SQL.

DatabricksConnection-class DBI Connection for Databricks	
Description DBI Connection for Databricks	
DatabricksDriver-class DBI Driver for Databricks	
Description DBI Driver for Databricks	
DatabricksResult-class DBI Result for Databricks	
Description DBI Result for Databricks	
DatabricksSQL	Create Databricks SQL Driver
Description Create Databricks SQL Driver	
Usage DatabricksSQL()	
Value A DatabricksDriver object	
Examples ## Not run: drv <- DatabricksSQL() con <- dbConnect(drv, warehouse_id = "your_warehouse_id") ## End(Not run)	

dbAppendTable,DatabricksConnection,character,data.frame-method
Append rows to an existing Databricks table

Description

Append rows to an existing Databricks table

Usage

```
## S4 method for signature 'DatabricksConnection,character,data.frame'  
dbAppendTable(conn, name, value, ..., row.names = FALSE)
```

Arguments

conn	A DatabricksConnection object
name	Table name (character, Id, or SQL)
value	Data frame to append
...	Additional arguments
row.names	If TRUE, preserve row names as a column

Value

TRUE invisibly on success

dbAppendTable,DatabricksConnection,Id,data.frame-method
Append rows to an existing Databricks table (Id method)

Description

Append rows to an existing Databricks table (Id method)

Usage

```
## S4 method for signature 'DatabricksConnection,Id,data.frame'  
dbAppendTable(conn, name, value, ..., row.names = FALSE)
```

Arguments

conn	A DatabricksConnection object
name	Table name as Id object
value	Data frame to append
...	Additional arguments
row.names	If TRUE, preserve row names as a column

Value

TRUE invisibly on success

dbBegin,DatabricksConnection-method

Begin transaction (not supported)

Description

Begin transaction (not supported)

Usage

```
## S4 method for signature 'DatabricksConnection'
dbBegin(conn, ...)
```

Arguments

conn	A DatabricksConnection object
...	Additional arguments (ignored)

Value

Always throws an error (transactions not supported)

dbClearResult,DatabricksResult-method

Clear result set

Description

Clear result set

Usage

```
## S4 method for signature 'DatabricksResult'
dbClearResult(res, ...)
```

Arguments

res	A DatabricksResult object
...	Additional arguments (ignored)

Value

TRUE (invisibly)

`dbColumnInfo,DatabricksResult-method`*Get column information from result*

Description

Get column information from result

Usage

```
## S4 method for signature 'DatabricksResult'  
dbColumnInfo(res, ...)
```

Arguments

<code>res</code>	A DatabricksResult object
<code>...</code>	Additional arguments (ignored)

Value

A data.frame with column names and types

`dbCommit,DatabricksConnection-method`*Commit transaction (not supported)*

Description

Commit transaction (not supported)

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbCommit(conn, ...)
```

Arguments

<code>conn</code>	A DatabricksConnection object
<code>...</code>	Additional arguments (ignored)

Value

Always throws an error (transactions not supported)

`dbConnect,DatabricksDriver-method`*Connect to Databricks SQL Warehouse*

Description

Connect to Databricks SQL Warehouse

Usage

```
## S4 method for signature 'DatabricksDriver'
dbConnect(
  drv,
  warehouse_id,
  catalog = NULL,
  schema = NULL,
  staging_volume = NULL,
  token = db_token(),
  host = db_host(),
  ...
)
```

Arguments

<code>drv</code>	A DatabricksDriver object
<code>warehouse_id</code>	ID of the SQL warehouse to connect to
<code>catalog</code>	Optional catalog name to use as default
<code>schema</code>	Optional schema name to use as default
<code>staging_volume</code>	Optional volume path for large dataset staging
<code>token</code>	Authentication token (defaults to <code>db_token()</code>)
<code>host</code>	Databricks workspace host (defaults to <code>db_host()</code>)
<code>...</code>	Additional arguments (ignored)

Value

A DatabricksConnection object

dbDataType,DatabricksConnection-method
Map R data types to Databricks SQL types

Description

Map R data types to Databricks SQL types

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbDataType(dbObj, obj, ...)
```

Arguments

dbObj	A DatabricksConnection object
obj	R object(s) to get SQL types for
...	Additional arguments (ignored)

Value

Character vector of SQL type names

dbDisconnect,DatabricksConnection-method
Disconnect from Databricks

Description

Disconnect from Databricks

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbDisconnect(conn, ...)
```

Arguments

conn	A DatabricksConnection object
...	Additional arguments (ignored)

Value

TRUE (invisibly)

dbExecute,DatabricksConnection,character-method
Execute statement on Databricks

Description

Execute statement on Databricks

Usage

```
## S4 method for signature 'DatabricksConnection,character'  
dbExecute(conn, statement, ...)
```

Arguments

conn	A DatabricksConnection object
statement	SQL statement
...	Additional arguments (ignored)

Value

Number of rows in result set (from metadata, without loading data)

dbExistsTable,DatabricksConnection,AsIs-method
Check if table exists (AsIs method)

Description

Check if table exists (AsIs method)

Usage

```
## S4 method for signature 'DatabricksConnection,AsIs'  
dbExistsTable(conn, name, ...)
```

Arguments

conn	A DatabricksConnection object
name	Table name as AsIs object (from I())
...	Additional arguments (ignored)

Value

TRUE if table exists, FALSE otherwise

dbExistsTable,DatabricksConnection,character-method
<i>Check if table exists in Databricks</i>

Description

Check if table exists in Databricks

Usage

```
## S4 method for signature 'DatabricksConnection,character'  
dbExistsTable(conn, name, ...)
```

Arguments

conn	A DatabricksConnection object
name	Table name to check
...	Additional arguments (ignored)

Value

TRUE if table exists, FALSE otherwise

dbExistsTable,DatabricksConnection,Id-method
<i>Check if table exists (Id method)</i>

Description

Check if table exists (Id method)

Usage

```
## S4 method for signature 'DatabricksConnection,Id'  
dbExistsTable(conn, name, ...)
```

Arguments

conn	A DatabricksConnection object
name	Table name as Id object
...	Additional arguments (ignored)

Value

TRUE if table exists, FALSE otherwise

dbFetch,DatabricksResult-method

Fetch results from Databricks query

Description

Fetch results from Databricks query

Usage

```
## S4 method for signature 'DatabricksResult'
dbFetch(res, n = -1, ...)
```

Arguments

res	A DatabricksResult object
n	Maximum number of rows to fetch (-1 for all rows)
...	Additional arguments (ignored)

Value

A data.frame with query results

dbfs_storage_info	<i>DBFS Storage Information</i>
-------------------	---------------------------------

Description

DBFS Storage Information

Usage

```
dbfs_storage_info(destination)
```

Arguments

destination	DBFS destination. Example: dbfs:/my/path.
-------------	---

See Also

[cluster_log_conf\(\)](#), [init_script_info\(\)](#)

Other Cluster Log Configuration Objects: [cluster_log_conf\(\)](#), [s3_storage_info\(\)](#)

Other Init Script Info Objects: [file_storage_info\(\)](#), [s3_storage_info\(\)](#)

dbGetInfo,DatabricksConnection-method
Get connection information

Description

Get connection information

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbGetInfo(dbObj, ...)
```

Arguments

dbObj	A DatabricksConnection object
...	Additional arguments (ignored)

Value

A list with connection details

dbGetQuery,DatabricksConnection,character-method
Execute SQL query and return results

Description

Execute SQL query and return results

Usage

```
## S4 method for signature 'DatabricksConnection,character'  
dbGetQuery(  
  conn,  
  statement,  
  disposition = "EXTERNAL_LINKS",  
  show_progress = TRUE,  
  ...  
)
```

Arguments

conn	A DatabricksConnection object
statement	SQL statement to execute
disposition	Query disposition mode: "EXTERNAL_LINKS" (default) for large results, "IN-LINE" for small metadata queries (automatically chooses appropriate format)
show_progress	If TRUE, show progress updates during query execution (default: TRUE)
...	Additional arguments passed to underlying query execution

Value

A data.frame with query results

dbGetRowCount,DatabricksResult-method
Get number of rows fetched

Description

Get number of rows fetched

Usage

```
## S4 method for signature 'DatabricksResult'  
dbGetRowCount(res, ...)
```

Arguments

res	A DatabricksResult object
...	Additional arguments (ignored)

Value

Number of rows fetched so far

`dbGetRowsAffected,DatabricksResult-method`*Get number of rows affected (not applicable for SELECT)*

Description

Get number of rows affected (not applicable for SELECT)

Usage

```
## S4 method for signature 'DatabricksResult'  
dbGetRowsAffected(res, ...)
```

Arguments

<code>res</code>	A DatabricksResult object
<code>...</code>	Additional arguments (ignored)

Value

-1 (not applicable for SELECT queries)

`dbGetStatement,DatabricksResult-method`*Get SQL statement from result*

Description

Get SQL statement from result

Usage

```
## S4 method for signature 'DatabricksResult'  
dbGetStatement(res, ...)
```

Arguments

<code>res</code>	A DatabricksResult object
<code>...</code>	Additional arguments (ignored)

Value

The SQL statement as character

dbHasCompleted,DatabricksResult-method
Check if query has completed

Description

Check if query has completed

Usage

```
## S4 method for signature 'DatabricksResult'  
dbHasCompleted(res, ...)
```

Arguments

res	A DatabricksResult object
...	Additional arguments (ignored)

Value

TRUE if query is complete, FALSE otherwise

dbIsValid,DatabricksConnection-method
Check if connection is valid

Description

Check if connection is valid

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbIsValid(dbObj, ...)
```

Arguments

dbObj	A DatabricksConnection object
...	Additional arguments (ignored)

Value

TRUE if connection is valid, FALSE otherwise

dbListFields,DatabricksConnection,AsIs-method

List column names of a Databricks table (AsIs method)

Description

List column names of a Databricks table (AsIs method)

Usage

```
## S4 method for signature 'DatabricksConnection,AsIs'
dbListFields(conn, name, ...)
```

Arguments

conn	A DatabricksConnection object
name	Table name as AsIs object (from I())
...	Additional arguments (ignored)

Value

Character vector of column names

dbListFields,DatabricksConnection,character-method

List column names of a Databricks table

Description

List column names of a Databricks table

Usage

```
## S4 method for signature 'DatabricksConnection,character'
dbListFields(conn, name, ...)
```

Arguments

conn	A DatabricksConnection object
name	Table name to describe
...	Additional arguments (ignored)

Value

Character vector of column names

dbListTables,DatabricksConnection-method
List tables in Databricks catalog/schema

Description

List tables in Databricks catalog/schema

Usage

```
## S4 method for signature 'DatabricksConnection'  
dbListTables(conn, ...)
```

Arguments

conn	A DatabricksConnection object
...	Additional arguments (ignored)

Value

Character vector of table names

dbplyr_edition.DatabricksConnection
Declare dbplyr API version for Databricks connections

Description

Declare dbplyr API version for Databricks connections

Usage

```
## S3 method for class 'DatabricksConnection'  
dbplyr_edition(con)
```

Arguments

con	A DatabricksConnection object
-----	-------------------------------

Value

The dbplyr edition number (2L)

dbQuoteIdentifier,DatabricksConnection,character-method
Quote identifiers for Databricks SQL

Description

Quote identifiers for Databricks SQL

Usage

```
## S4 method for signature 'DatabricksConnection,character'  
dbQuoteIdentifier(conn, x, ...)
```

Arguments

conn	A DatabricksConnection object
x	Character vector of identifiers to quote
...	Additional arguments (ignored)

Value

SQL object with quoted identifiers

dbQuoteIdentifier,DatabricksConnection,Id-method
Quote complex identifiers (schema.table)

Description

Quote complex identifiers (schema.table)

Usage

```
## S4 method for signature 'DatabricksConnection,Id'  
dbQuoteIdentifier(conn, x, ...)
```

Arguments

conn	A DatabricksConnection object
x	Id object with catalog/schema/table components
...	Additional arguments (ignored)

Value

SQL object with quoted identifier components

dbQuoteIdentifier,DatabricksConnection,SQL-method
Quote SQL objects (passthrough)

Description

Quote SQL objects (passthrough)

Usage

```
## S4 method for signature 'DatabricksConnection,SQL'
dbQuoteIdentifier(conn, x, ...)
```

Arguments

conn	A DatabricksConnection object
x	SQL object (already quoted)
...	Additional arguments (ignored)

Value

The SQL object unchanged

dbRollback,DatabricksConnection-method
Rollback transaction (not supported)

Description

Rollback transaction (not supported)

Usage

```
## S4 method for signature 'DatabricksConnection'
dbRollback(conn, ...)
```

Arguments

conn	A DatabricksConnection object
...	Additional arguments (ignored)

Value

Always throws an error (transactions not supported)

dbSendQuery,DatabricksConnection,character-method
<i>Send query to Databricks (asynchronous)</i>

Description

Send query to Databricks (asynchronous)

Usage

S4 method for signature 'DatabricksConnection,character'
dbSendQuery(conn, statement, ...)

Arguments

conn	A DatabricksConnection object
statement	SQL statement to execute
...	Additional arguments (ignored)

Value

A DatabricksResult object

dbSendStatement,DatabricksConnection,character-method
<i>Send statement to Databricks</i>

Description

Send statement to Databricks

Usage

S4 method for signature 'DatabricksConnection,character'
dbSendStatement(conn, statement, ...)

Arguments

conn	A DatabricksConnection object
statement	SQL statement
...	Additional arguments (ignored)

Value

A DatabricksResult object

dbWriteTable,DatabricksConnection,AsIs,data.frame-method
<i>Write table to Databricks (AsIs name signature)</i>

Description

Write table to Databricks (AsIs name signature)

Usage

```
## S4 method for signature 'DatabricksConnection,AsIs,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = FALSE,
  temporary = FALSE,
  field.types = NULL,
  staging_volume = NULL,
  progress = TRUE,
  ...
)
```

Arguments

conn	DatabricksConnection object
name	Table name as AsIs object (from I())
value	Data frame to write
overwrite	If TRUE, overwrite existing table
append	If TRUE, append to existing table
row.names	If TRUE, preserve row names as a column
temporary	If TRUE, create temporary table (NOT SUPPORTED - will error)
field.types	Named character vector of SQL types for columns
staging_volume	Optional volume path for large dataset staging
progress	If TRUE, show progress bar for file uploads (default: TRUE)
...	Additional arguments

Value

TRUE invisibly on success

dbWriteTable,DatabricksConnection,character,data.frame-method
Write a data frame to Databricks table

Description

Write a data frame to Databricks table

Usage

```
## S4 method for signature 'DatabricksConnection,character,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = FALSE,
  temporary = FALSE,
  field.types = NULL,
  staging_volume = NULL,
  progress = TRUE,
  ...
)
```

Arguments

conn	A DatabricksConnection object
name	Table name (character, Id, or SQL)
value	Data frame to write
overwrite	If TRUE, overwrite existing table
append	If TRUE, append to existing table
row.names	If TRUE, preserve row names as a column
temporary	If TRUE, create temporary table (NOT SUPPORTED - will error)
field.types	Named character vector of SQL types for columns
staging_volume	Optional volume path for large dataset staging
progress	If TRUE, show progress bar for file uploads (default: TRUE)
...	Additional arguments

Value

TRUE invisibly on success

dbWriteTable,DatabricksConnection,Id,data.frame-method
<i>Write a data frame to Databricks table (Id method)</i>

Description

Write a data frame to Databricks table (Id method)

Usage

```
## S4 method for signature 'DatabricksConnection,Id,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  overwrite = FALSE,
  append = FALSE,
  row.names = FALSE,
  temporary = FALSE,
  field.types = NULL,
  staging_volume = NULL,
  progress = TRUE,
  ...
)
```

Arguments

conn	A DatabricksConnection object
name	Table name as Id object
value	Data frame to write
overwrite	If TRUE, overwrite existing table
append	If TRUE, append to existing table
row.names	If TRUE, preserve row names as a column
temporary	If TRUE, create temporary table (NOT SUPPORTED - will error)
field.types	Named character vector of SQL types for columns
staging_volume	Optional volume path for large dataset staging
progress	If TRUE, show progress bar for file uploads (default: TRUE)
...	Additional arguments

Value

TRUE invisibly on success

db_cluster_action	<i>Cluster Action Helper Function</i>
-------------------	---------------------------------------

Description

Cluster Action Helper Function

Usage

```
db_cluster_action(  
  cluster_id,  
  action = c("start", "restart", "delete", "permanent-delete", "pin", "unpin"),  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
action	One of start, restart, delete, permanent-delete, pin, unpin.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

db_cluster_create	<i>Create a Cluster</i>
-------------------	-------------------------

Description

Create a Cluster

Usage

```
db_cluster_create(  
  name,  
  spark_version,  
  node_type_id,  
  num_workers = NULL,  
  autoscale = NULL,  
  spark_conf = list(),  
  cloud_attrs = aws_attributes(),
```

```

driver_node_type_id = NULL,
custom_tags = list(),
init_scripts = list(),
spark_env_vars = list(),
autotermination_minutes = 120,
log_conf = NULL,
ssh_public_keys = NULL,
driver_instance_pool_id = NULL,
instance_pool_id = NULL,
idempotency_token = NULL,
enable_elastic_disk = TRUE,
apply_policy_default_values = TRUE,
enable_local_disk_encryption = TRUE,
docker_image = NULL,
policy_id = NULL,
kind = c("CLASSIC_PREVIEW"),
data_security_mode = c("NONE", "SINGLE_USER", "USER_ISOLATION", "LEGACY_TABLE_ACL",
    "LEGACY_PASSTHROUGH", "LEGACY_SINGLE_USER", "LEGACY_SINGLE_USER_STANDARD",
    "DATA_SECURITY_MODE_STANDARD", "DATA_SECURITY_MODE_DEDICATED",
    "DATA_SECURITY_MODE_AUTO"),
host = db_host(),
token = db_token(),
perform_request = TRUE
)

```

Arguments

name	Cluster name requested by the user. This doesn't have to be unique. If not specified at creation, the cluster name will be an empty string.
spark_version	The runtime version of the cluster. You can retrieve a list of available runtime versions by using db_cluster_runtime_versions() .
node_type_id	The node type for the worker nodes. db_cluster_list_node_types() can be used to see available node types.
num_workers	Number of worker nodes that this cluster should have. A cluster has one Spark driver and num_workers executors for a total of num_workers + 1 Spark nodes.
autoscale	Instance of cluster_autoscale() .
spark_conf	Named list. An object containing a set of optional, user-specified Spark configuration key-value pairs. You can also pass in a string of extra JVM options to the driver and the executors via spark.driver.extraJavaOptions and spark.executor.extraJavaOptions respectively. E.g. list("spark.speculation" = true, "spark.streaming.ui.retainedBatches" = 5).
cloud_attrs	Attributes related to clusters running on specific cloud provider. Defaults to aws_attributes() . Must be one of aws_attributes() , azure_attributes() , gcp_attributes() .
driver_node_type_id	The node type of the Spark driver. This field is optional; if unset, the driver node type will be set as the same value as node_type_id defined above. db_cluster_list_node_types() can be used to see available node types.

custom_tags	Named list. An object containing a set of tags for cluster resources. Databricks tags all cluster resources with these tags in addition to default_tags. Databricks allows at most 45 custom tags.
init_scripts	Instance of <code>init_script_info()</code> .
spark_env_vars	Named list. User-specified environment variable key-value pairs. In order to specify an additional set of SPARK_DAEMON_JAVA_OPTS, we recommend appending them to \$SPARK_DAEMON_JAVA_OPTS as shown in the following example. This ensures that all default Databricks managed environmental variables are included as well. E.g. {"SPARK_DAEMON_JAVA_OPTS": "\$SPARK_DAEMON_JAVA_OPTS -Dspark.shuffle.service.enabled=true"}
autotermination_minutes	Automatically terminates the cluster after it is inactive for this time in minutes. If not set, this cluster will not be automatically terminated. If specified, the threshold must be between 10 and 10000 minutes. You can also set this value to 0 to explicitly disable automatic termination. Defaults to 120.
log_conf	Instance of <code>cluster_log_conf()</code> .
ssh_public_keys	List. SSH public key contents that will be added to each Spark node in this cluster. The corresponding private keys can be used to login with the user name ubuntu on port 2200. Up to 10 keys can be specified.
driver_instance_pool_id	ID of the instance pool to use for the driver node. You must also specify instance_pool_id. Optional.
instance_pool_id	ID of the instance pool to use for cluster nodes. If driver_instance_pool_id is present, instance_pool_id is used for worker nodes only. Otherwise, it is used for both the driver and worker nodes. Optional.
idempotency_token	An optional token that can be used to guarantee the idempotency of cluster creation requests. If an active cluster with the provided token already exists, the request will not create a new cluster, but it will return the ID of the existing cluster instead. The existence of a cluster with the same token is not checked against terminated clusters. If you specify the idempotency token, upon failure you can retry until the request succeeds. Databricks guarantees that exactly one cluster will be launched with that idempotency token. This token should have at most 64 characters.
enable_elastic_disk	When enabled, this cluster will dynamically acquire additional disk space when its Spark workers are running low on disk space.
apply_policy_default_values	Boolean (Default: TRUE), whether to use policy default values for missing cluster attributes.
enable_local_disk_encryption	Boolean (Default: TRUE), whether encryption of disks locally attached to the cluster is enabled.
docker_image	Instance of <code>docker_image()</code> .

policy_id	String, ID of a cluster policy.
kind	The kind of compute described by this compute specification.
data_security_mode	Data security mode decides what data governance model to use when accessing data from a cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Create a new Apache Spark cluster. This method acquires new instances from the cloud provider if necessary. This method is asynchronous; the returned `cluster_id` can be used to poll the cluster state ([db_cluster_get\(\)](#)). When this method returns, the cluster is in a PENDING state. The cluster is usable once it enters a RUNNING state.

Databricks may not be able to acquire some of the requested nodes, due to cloud provider limitations or transient network issues. If Databricks acquires at least 85% of the requested on-demand nodes, cluster creation will succeed. Otherwise the cluster will terminate with an informative error message.

Cannot specify both `autoscale` and `num_workers`, must choose one.

[More Documentation.](#)

See Also

Other Clusters API: [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_delete	<i>Delete/Terminate a Cluster</i>
-------------------	-----------------------------------

Description

Delete/Terminate a Cluster

Usage

```
db_cluster_delete(
  cluster_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

The cluster must be in the RUNNING state.

db_cluster_edit	<i>Edit a Cluster</i>
-----------------	-----------------------

Description

Edit the configuration of a cluster to match the provided attributes and size.

Usage

```
db_cluster_edit(  
  cluster_id,  
  spark_version,  
  node_type_id,  
  num_workers = NULL,  
  autoscale = NULL,  
  name = NULL,  
  spark_conf = NULL,  
  cloud_attrs = NULL,  
  driver_node_type_id = NULL,  
  custom_tags = NULL,  
  init_scripts = NULL,  
  spark_env_vars = NULL,  
  autotermination_minutes = NULL,  
  log_conf = NULL,  
  ssh_public_keys = NULL,  
  driver_instance_pool_id = NULL,  
  instance_pool_id = NULL,  
  idempotency_token = NULL,  
  enable_elastic_disk = NULL,  
  apply_policy_default_values = NULL,  
  enable_local_disk_encryption = NULL,  
  docker_image = NULL,  
  policy_id = NULL,  
  kind = c("CLASSIC_PREVIEW"),
```

```

data_security_mode = c("NONE", "SINGLE_USER", "USER_ISOLATION", "LEGACY_TABLE_ACL",
    "LEGACY_PASSTHROUGH", "LEGACY_SINGLE_USER", "LEGACY_SINGLE_USER_STANDARD",
    "DATA_SECURITY_MODE_STANDARD", "DATA_SECURITY_MODE_DEDICATED",
    "DATA_SECURITY_MODE_AUTO"),
host = db_host(),
token = db_token(),
perform_request = TRUE
)

```

Arguments

cluster_id	Canonical identifier for the cluster.
spark_version	The runtime version of the cluster. You can retrieve a list of available runtime versions by using db_cluster_runtime_versions() .
node_type_id	The node type for the worker nodes. db_cluster_list_node_types() can be used to see available node types.
num_workers	Number of worker nodes that this cluster should have. A cluster has one Spark driver and num_workers executors for a total of num_workers + 1 Spark nodes.
autoscale	Instance of cluster_autoscale() .
name	Cluster name requested by the user. This doesn't have to be unique. If not specified at creation, the cluster name will be an empty string.
spark_conf	Named list. An object containing a set of optional, user-specified Spark configuration key-value pairs. You can also pass in a string of extra JVM options to the driver and the executors via spark.driver.extraJavaOptions and spark.executor.extraJavaOptions respectively. E.g. list("spark.speculation" = true, "spark.streaming.ui.retainedBatches" = 5).
cloud_attrs	Attributes related to clusters running on specific cloud provider. Defaults to aws_attributes() . Must be one of aws_attributes() , azure_attributes() , gcp_attributes() .
driver_node_type_id	The node type of the Spark driver. This field is optional; if unset, the driver node type will be set as the same value as node_type_id defined above. db_cluster_list_node_types() can be used to see available node types.
custom_tags	Named list. An object containing a set of tags for cluster resources. Databricks tags all cluster resources with these tags in addition to default_tags. Databricks allows at most 45 custom tags.
init_scripts	Instance of init_script_info() .
spark_env_vars	Named list. User-specified environment variable key-value pairs. In order to specify an additional set of SPARK_DAEMON_JAVA_OPTS, we recommend appending them to \$SPARK_DAEMON_JAVA_OPTS as shown in the following example. This ensures that all default Databricks managed environmental variables are included as well. E.g. {"SPARK_DAEMON_JAVA_OPTS": "\$SPARK_DAEMON_JAVA_OPTS -Dspark.shuffle.service.enabled=true"}
autotermination_minutes	Automatically terminates the cluster after it is inactive for this time in minutes. If not set, this cluster will not be automatically terminated. If specified, the

	threshold must be between 10 and 10000 minutes. You can also set this value to 0 to explicitly disable automatic termination. Defaults to 120.
log_conf	Instance of <code>cluster_log_conf()</code> .
ssh_public_keys	List. SSH public key contents that will be added to each Spark node in this cluster. The corresponding private keys can be used to login with the user name ubuntu on port 2200. Up to 10 keys can be specified.
driver_instance_pool_id	ID of the instance pool to use for the driver node. You must also specify instance_pool_id. Optional.
instance_pool_id	ID of the instance pool to use for cluster nodes. If driver_instance_pool_id is present, instance_pool_id is used for worker nodes only. Otherwise, it is used for both the driver and worker nodes. Optional.
idempotency_token	An optional token that can be used to guarantee the idempotency of cluster creation requests. If an active cluster with the provided token already exists, the request will not create a new cluster, but it will return the ID of the existing cluster instead. The existence of a cluster with the same token is not checked against terminated clusters. If you specify the idempotency token, upon failure you can retry until the request succeeds. Databricks guarantees that exactly one cluster will be launched with that idempotency token. This token should have at most 64 characters.
enable_elastic_disk	When enabled, this cluster will dynamically acquire additional disk space when its Spark workers are running low on disk space.
apply_policy_default_values	Boolean (Default: TRUE), whether to use policy default values for missing cluster attributes.
enable_local_disk_encryption	Boolean (Default: TRUE), whether encryption of disks locally attached to the cluster is enabled.
docker_image	Instance of <code>docker_image()</code> .
policy_id	String, ID of a cluster policy.
kind	The kind of compute described by this compute specification.
data_security_mode	Data security mode decides what data governance model to use when accessing data from a cluster.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You can edit a cluster if it is in a RUNNING or TERMINATED state. If you edit a cluster while it is in a RUNNING state, it will be restarted so that the new attributes can take effect. If you edit a cluster while it is in a TERMINATED state, it will remain TERMINATED. The next time it is started using the clusters/start API, the new attributes will take effect. An attempt to edit a cluster in any other state will be rejected with an INVALID_STATE error code.

Clusters created by the Databricks Jobs service cannot be edited.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_events	<i>List Cluster Activity Events</i>
-------------------	-------------------------------------

Description

List Cluster Activity Events

Usage

```
db_cluster_events(  
  cluster_id,  
  start_time = NULL,  
  end_time = NULL,  
  event_types = NULL,  
  order = c("DESC", "ASC"),  
  offset = 0,  
  limit = 50,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

cluster_id	The ID of the cluster to retrieve events about.
start_time	The start time in epoch milliseconds. If empty, returns events starting from the beginning of time.
end_time	The end time in epoch milliseconds. If empty, returns events up to the current time.
event_types	List. Optional set of event types to filter by. Default is to return all events. Event Types.

order	Either DESC (default) or ASC.
offset	The offset in the result set. Defaults to 0 (no offset). When an offset is specified and the results are requested in descending order, the end_time field is required.
limit	Maximum number of events to include in a page of events. Defaults to 50, and maximum allowed value is 500.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Retrieve a list of events about the activity of a cluster. You can retrieve events from active clusters (running, pending, or reconfiguring) and terminated clusters within 30 days of their last termination. This API is paginated. If there are more events to read, the response includes all the parameters necessary to request the next page of events.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_get	<i>Get Details of a Cluster</i>
----------------	---------------------------------

Description

Get Details of a Cluster

Usage

```
db_cluster_get(  
  cluster_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Retrieve the information for a cluster given its identifier. Clusters can be described while they are running or up to 30 days after they are terminated.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_list	<i>List Clusters</i>
-----------------	----------------------

Description

List Clusters

Usage

```
db_cluster_list(host = db_host(), token = db_token(), perform_request = TRUE)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Return information about all pinned clusters, active clusters, up to 150 of the most recently terminated all-purpose clusters in the past 30 days, and up to 30 of the most recently terminated job clusters in the past 30 days.

For example, if there is 1 pinned cluster, 4 active clusters, 45 terminated all-purpose clusters in the past 30 days, and 50 terminated job clusters in the past 30 days, then this API returns:

- the 1 pinned cluster
- 4 active clusters
- All 45 terminated all-purpose clusters
- The 30 most recently terminated job clusters

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_list_node_types

List Available Cluster Node Types

Description

List Available Cluster Node Types

Usage

```
db_cluster_list_node_types(
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Return a list of supported Spark node types. These node types can be used to launch a cluster.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_list_zones *List Availability Zones (AWS Only)*

Description

List Availability Zones (AWS Only)

Usage

```
db_cluster_list_zones(
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Amazon Web Services (AWS) ONLY! Return a list of availability zones where clusters can be created in (ex: us-west-2a). These zones can be used to launch a cluster.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

`db_cluster_perm_delete`*Permanently Delete a Cluster*

Description

Permanently Delete a Cluster

Usage

```
db_cluster_perm_delete(  
    cluster_id,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

<code>cluster_id</code>	Canonical identifier for the cluster.
<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
<code>token</code>	Databricks workspace token, defaults to calling db_token() .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If the cluster is running, it is terminated and its resources are asynchronously removed. If the cluster is terminated, then it is immediately removed.

You cannot perform *any action, including retrieve the cluster's permissions, on a permanently deleted cluster. A permanently deleted cluster is also no longer returned in the cluster list.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_pin	<i>Pin a Cluster</i>
----------------	----------------------

Description

Pin a Cluster

Usage

```
db_cluster_pin(  
  cluster_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- cluster_id Canonical identifier for the cluster.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http request is returned *without* being performed.

Details

Ensure that an all-purpose cluster configuration is retained even after a cluster has been terminated for more than 30 days. Pinning ensures that the cluster is always returned by [db_cluster_list\(\)](#). Pinning a cluster that is already pinned has no effect.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_resize	<i>Resize a Cluster</i>
-------------------	-------------------------

Description

Resize a Cluster

Usage

```
db_cluster_resize(
  cluster_id,
  num_workers = NULL,
  autoscale = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
num_workers	Number of worker nodes that this cluster should have. A cluster has one Spark driver and num_workers executors for a total of num_workers + 1 Spark nodes.
autoscale	Instance of cluster_autoscale() .
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

The cluster must be in the RUNNING state.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_restart	<i>Restart a Cluster</i>
--------------------	--------------------------

Description

Restart a Cluster

Usage

```
db_cluster_restart(  
  cluster_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- cluster_id Canonical identifier for the cluster.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Details

The cluster must be in the RUNNING state.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_runtime_versions	<i>List Available Databricks Runtime Versions</i>
-----------------------------	---

Description

List Available Databricks Runtime Versions

Usage

```
db_cluster_runtime_versions(
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Return the list of available runtime versions. These versions can be used to launch a cluster.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_start	<i>Start a Cluster</i>
------------------	------------------------

Description

Start a Cluster

Usage

```
db_cluster_start(
  cluster_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Start a terminated cluster given its ID.

This is similar to [db_cluster_create\(\)](#), except:

- The terminated cluster ID and attributes are preserved.
- The cluster starts with the last specified cluster size. If the terminated cluster is an autoscaling cluster, the cluster starts with the minimum number of nodes.
- If the cluster is in the RESTARTING state, a 400 error is returned.
- You cannot start a cluster launched to run a job.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_terminate *Delete/Terminate a Cluster*

Description

Delete/Terminate a Cluster

Usage

```
db_cluster_terminate(
  cluster_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

The cluster is removed asynchronously. Once the termination has completed, the cluster will be in the TERMINATED state. If the cluster is already in a TERMINATING or TERMINATED state, nothing will happen.

Unless a cluster is pinned, 30 days after the cluster is terminated, it is permanently deleted.

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#), [get_latest_dbr\(\)](#)

db_cluster_unpin	<i>Unpin a Cluster</i>
------------------	------------------------

Description

Unpin a Cluster

Usage

```
db_cluster_unpin(
  cluster_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Allows the cluster to eventually be removed from the list returned by `db_cluster_list()`. Unpinning a cluster that is not pinned has no effect.

See Also

Other Clusters API: `db_cluster_create()`, `db_cluster_edit()`, `db_cluster_events()`, `db_cluster_get()`, `db_cluster_list()`, `db_cluster_list_node_types()`, `db_cluster_list_zones()`, `db_cluster_perm_delete()`, `db_cluster_pin()`, `db_cluster_resize()`, `db_cluster_restart()`, `db_cluster_runtime_versions()`, `db_cluster_start()`, `db_cluster_terminate()`, `get_and_start_cluster()`, `get_latest_dbr()`

`db_collect.DatabricksConnection`

Collect query results with proper progress timing for Databricks

Description

Collect query results with proper progress timing for Databricks

Usage

```
## S3 method for class 'DatabricksConnection'
db_collect(con, sql, n = -1, warn_incomplete = TRUE, ...)
```

Arguments

<code>con</code>	A <code>DatabricksConnection</code> object
<code>sql</code>	SQL query to execute
<code>n</code>	Maximum number of rows to collect (-1 for all)
<code>warn_incomplete</code>	Whether to warn if results were truncated
<code>...</code>	Additional arguments

Value

A data frame with query results

`db_context_command_cancel`*Cancel a Command*

Description

Cancel a Command

Usage

```
db_context_command_cancel(  
  cluster_id,  
  context_id,  
  command_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

<code>cluster_id</code>	The ID of the cluster to create the context for.
<code>context_id</code>	The ID of the execution context.
<code>command_id</code>	The ID of the command to get information about.
<code>host</code>	Databricks workspace URL, defaults to calling <code>db_host()</code> .
<code>token</code>	Databricks workspace token, defaults to calling <code>db_token()</code> .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: `db_context_command_parse()`, `db_context_command_run()`, `db_context_command_run_`
`db_context_command_status()`, `db_context_create()`, `db_context_destroy()`, `db_context_status()`

`db_context_command_run`*Run a Command*

Description

Run a Command

Usage

```

db_context_command_run(
    cluster_id,
    context_id,
    language = c("python", "sql", "scala", "r"),
    command = NULL,
    command_file = NULL,
    options = list(),
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)

```

Arguments

cluster_id	The ID of the cluster to create the context for.
context_id	The ID of the execution context.
language	The language for the context. One of python, sql, scala, r.
command	The command string to run.
command_file	The path to a file containing the command to run.
options	Named list of values used downstream. For example, a 'displayRowLimit' override (used in testing).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run_and_wait\(\)](#), [db_context_command_status\(\)](#), [db_context_create\(\)](#), [db_context_destroy\(\)](#), [db_context_status\(\)](#)

db_context_command_run_and_wait

Run a Command and Wait For Results

Description

Run a Command and Wait For Results

Usage

```

db_context_command_run_and_wait(
    cluster_id,
    context_id,
    language = c("python", "sql", "scala", "r"),
    command = NULL,
    command_file = NULL,
    options = list(),
    parse_result = TRUE,
    host = db_host(),
    token = db_token()
)

```

Arguments

cluster_id	The ID of the cluster to create the context for.
context_id	The ID of the execution context.
language	The language for the context. One of python, sql, scala, r.
command	The command string to run.
command_file	The path to a file containing the command to run.
options	Named list of values used downstream. For example, a 'displayRowLimit' override (used in testing).
parse_result	Boolean, determines if results are parsed automatically.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run\(\)](#), [db_context_command_status\(\)](#), [db_context_create\(\)](#), [db_context_destroy\(\)](#), [db_context_status\(\)](#)

db_context_command_status

Get Information About a Command

Description

Get Information About a Command

Usage

```
db_context_command_status(
    cluster_id,
    context_id,
    command_id,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

cluster_id	The ID of the cluster to create the context for.
context_id	The ID of the execution context.
command_id	The ID of the command to get information about.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run\(\)](#), [db_context_command_run_and_wait\(\)](#), [db_context_create\(\)](#), [db_context_destroy\(\)](#), [db_context_status\(\)](#)

db_context_create	<i>Create an Execution Context</i>
-------------------	------------------------------------

Description

Create an Execution Context

Usage

```
db_context_create(
    cluster_id,
    language = c("python", "sql", "scala", "r"),
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

cluster_id	The ID of the cluster to create the context for.
language	The language for the context. One of python, sql, scala, r.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run\(\)](#), [db_context_command_run_and_wait\(\)](#), [db_context_command_status\(\)](#), [db_context_destroy\(\)](#), [db_context_status\(\)](#)

db_context_destroy	<i>Delete an Execution Context</i>
--------------------	------------------------------------

Description

Delete an Execution Context

Usage

```
db_context_destroy(
  cluster_id,
  context_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	The ID of the cluster to create the context for.
context_id	The ID of the execution context.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run\(\)](#), [db_context_command_run_and_wait\(\)](#), [db_context_command_status\(\)](#), [db_context_create\(\)](#), [db_context_status\(\)](#)

db_context_manager	<i>Databricks Execution Context Manager (R6 Class)</i>
--------------------	--

Description

Databricks Execution Context Manager (R6 Class)

Databricks Execution Context Manager (R6 Class)

Details

db_context_manager() provides a simple interface to send commands to Databricks cluster and return the results.

Methods

Public methods:

- [db_context_manager\\$new\(\)](#)
- [db_context_manager\\$close\(\)](#)
- [db_context_manager\\$cmd_run\(\)](#)
- [db_context_manager\\$clone\(\)](#)

Method new(): Create a new context manager object.

Usage:

```
db_context_manager$new(
  cluster_id,
  language = c("r", "py", "scala", "sql", "sh"),
  host = db_host(),
  token = db_token()
)
```

Arguments:

cluster_id The ID of the cluster to execute command on.

language One of r, py, scala, sql, or sh.

host Databricks workspace URL, defaults to calling [db_host\(\)](#).

token Databricks workspace token, defaults to calling [db_token\(\)](#).

Returns: A new databricks_context_manager object.

Method close(): Destroy the execution context

Usage:

```
db_context_manager$close()
```

Method cmd_run(): Execute a command against a Databricks cluster

Usage:

```
db_context_manager$cmd_run(cmd, language = c("r", "py", "scala", "sql", "sh"))
```

Arguments:

`cmd` code to execute against Databricks cluster
`language` One of r, py, scala, sql, or sh.

Returns: Command results

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
db_context_manager$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

db_context_status

*Get Information About an Execution Context***Description**

Get Information About an Execution Context

Usage

```
db_context_status(
  cluster_id,
  context_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

<code>cluster_id</code>	The ID of the cluster to create the context for.
<code>context_id</code>	The ID of the execution context.
<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
<code>token</code>	Databricks workspace token, defaults to calling db_token() .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Execution Context API: [db_context_command_cancel\(\)](#), [db_context_command_parse\(\)](#), [db_context_command_run\(\)](#), [db_context_command_run_and_wait\(\)](#), [db_context_command_status\(\)](#), [db_context_create\(\)](#), [db_context_destroy\(\)](#)

db_current_cloud	<i>Detect Current Workspaces Cloud</i>
------------------	--

Description

Detect Current Workspaces Cloud

Usage

db_current_cloud(host = db_host(), token = db_token(), perform_request = TRUE)

Arguments

- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

String

db_current_user	<i>Get Current User Info</i>
-----------------	------------------------------

Description

Get Current User Info

Usage

db_current_user(host = db_host(), token = db_token(), perform_request = TRUE)

Arguments

- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

list of user metadata

db_current_workspace_id	<i>Detect Current Workspace ID</i>
-------------------------	------------------------------------

Description

Detect Current Workspace ID

Usage

```
db_current_workspace_id(  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

String

db_dbfs_add_block	<i>DBFS Add Block</i>
-------------------	-----------------------

Description

Append a block of data to the stream specified by the input handle.

Usage

```
db_dbfs_add_block(  
  handle,  
  data,  
  convert_to_raw = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

handle	Handle on an open stream.
data	Either a path for file on local system or a character/raw vector that will be base64-encoded. This has a limit of 1 MB.
convert_to_raw	Boolean (Default: FALSE), if TRUE will convert character vector to raw via <code>base::as.raw()</code> .
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- If the handle does not exist, this call will throw an exception with `RESOURCE_DOES_NOT_EXIST`.
- If the block of data exceeds 1 MB, this call will throw an exception with `MAX_BLOCK_SIZE_EXCEEDED`.

Typical File Upload Flow

- Call create and get a handle via `db_dbfs_create()`
- Make one or more `db_dbfs_add_block()` calls with the handle you have
- Call `db_dbfs_close()` with the handle you have

See Also

Other DBFS API: `db_dbfs_close()`, `db_dbfs_create()`, `db_dbfs_delete()`, `db_dbfs_get_status()`, `db_dbfs_list()`, `db_dbfs_mkdirs()`, `db_dbfs_move()`, `db_dbfs_put()`, `db_dbfs_read()`

db_dbfs_close

DBFS Close

Description

Close the stream specified by the input handle.

Usage

```
db_dbfs_close(
  handle,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

handle	The handle on an open stream. This field is required.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If the handle does not exist, this call throws an exception with RESOURCE_DOES_NOT_EXIST.

Value

HTTP Response

Typical File Upload Flow

- Call create and get a handle via [db_dbfs_create\(\)](#)
- Make one or more [db_dbfs_add_block\(\)](#) calls with the handle you have
- Call [db_dbfs_close\(\)](#) with the handle you have

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_create

DBFS Create

Description

Open a stream to write to a file and returns a handle to this stream.

Usage

```
db_dbfs_create(
  path,
  overwrite = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
overwrite	Boolean, specifies whether to overwrite existing file or files.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

There is a 10 minute idle timeout on this handle. If a file or directory already exists on the given path and overwrite is set to FALSE, this call throws an exception with RESOURCE_ALREADY_EXISTS.

Value

Handle which should subsequently be passed into [db_dbfs_add_block\(\)](#) and [db_dbfs_close\(\)](#) when writing to a file through a stream.

Typical File Upload Flow

- Call create and get a handle via [db_dbfs_create\(\)](#)
- Make one or more [db_dbfs_add_block\(\)](#) calls with the handle you have
- Call [db_dbfs_close\(\)](#) with the handle you have

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_delete	<i>DBFS Delete</i>
----------------	--------------------

Description

DBFS Delete

Usage

```
db_dbfs_delete(  
  path,  
  recursive = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
recursive	Whether or not to recursively delete the directory's contents. Deleting empty directories can be done without providing the recursive flag.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_get_status	<i>DBFS Get Status</i>
--------------------	------------------------

Description

Get the file information of a file or directory.

Usage

```
db_dbfs_get_status(
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- If the file or directory does not exist, this call throws an exception with RESOURCE_DOES_NOT_EXIST.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_list

*DBFS List***Description**

List the contents of a directory, or details of the file.

Usage

```
db_dbfs_list(
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example <code>/mnt/my-file.txt</code>).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

When calling list on a large directory, the list operation will time out after approximately 60 seconds.

We **strongly** recommend using list only on directories containing less than 10K files and discourage using the DBFS REST API for operations that list more than 10K files. Instead, we recommend that you perform such operations in the context of a cluster, using the File system utility (`dbutils.fs`), which provides the same functionality without timing out.

- If the file or directory does not exist, this call throws an exception with `RESOURCE_DOES_NOT_EXIST`.

Value

data.frame

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_mkdirs	<i>DBFS mkdirs</i>
----------------	--------------------

Description

Create the given directory and necessary parent directories if they do not exist.

Usage

```
db_dbfs_mkdirs(  
    path,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- If there exists a file (not a directory) at any prefix of the input path, this call throws an exception with RESOURCE_ALREADY_EXISTS.
- If this operation fails it may have succeeded in creating some of the necessary parent directories.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_move

*DBFS Move***Description**

Move a file from one location to another location within DBFS.

Usage

```
db_dbfs_move(
    source_path,
    destination_path,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

source_path	The source path of the file or directory. The path should be the absolute DBFS path (for example, /mnt/my-source-folder/).
destination_path	The destination path of the file or directory. The path should be the absolute DBFS path (for example, /mnt/my-destination-folder/).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If the given source path is a directory, this call always recursively moves all files.

When moving a large number of files, the API call will time out after approximately 60 seconds, potentially resulting in partially moved data. Therefore, for operations that move more than 10K files, we **strongly** discourage using the DBFS REST API. Instead, we recommend that you perform such operations in the context of a cluster, using the File system utility (`dbutils.fs`) from a notebook, which provides the same functionality without timing out.

- If the source file does not exist, this call throws an exception with `RESOURCE_DOES_NOT_EXIST`.
- If there already exists a file in the destination path, this call throws an exception with `RESOURCE_ALREADY_EXISTS`.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_put\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_put

*DBFS Put***Description**

Upload a file through the use of multipart form post.

Usage

```
db_dbfs_put(
    path,
    file = NULL,
    contents = NULL,
    overwrite = FALSE,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
file	Path to a file on local system, takes precedent over path.
contents	String that is base64 encoded.
overwrite	Flag (Default: FALSE) that specifies whether to overwrite existing files.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http request is returned <i>without</i> being performed.

Details

Either contents or file must be specified. file takes precedent over contents if both are specified.

Mainly used for streaming uploads, but can also be used as a convenient single call for data upload.

The amount of data that can be passed using the contents parameter is limited to 1 MB if specified as a string (MAX_BLOCK_SIZE_EXCEEDED is thrown if exceeded) and 2 GB as a file.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_read\(\)](#)

db_dbfs_read

*DBFS Read***Description**

Return the contents of a file.

Usage

```
db_dbfs_read(
    path,
    offset = 0,
    length = NULL,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

path	The path of the new file. The path should be the absolute DBFS path (for example /mnt/my-file.txt).
offset	Offset to read from in bytes.
length	Number of bytes to read starting from the offset. This has a limit of 1 MB, and a default value of 0.5 MB.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If offset + length exceeds the number of bytes in a file, reads contents until the end of file.

- If the file does not exist, this call throws an exception with RESOURCE_DOES_NOT_EXIST.
- If the path is a directory, the read length is negative, or if the offset is negative, this call throws an exception with INVALID_PARAMETER_VALUE.
- If the read length exceeds 1 MB, this call throws an exception with MAX_READ_SIZE_EXCEEDED.

See Also

Other DBFS API: [db_dbfs_add_block\(\)](#), [db_dbfs_close\(\)](#), [db_dbfs_create\(\)](#), [db_dbfs_delete\(\)](#), [db_dbfs_get_status\(\)](#), [db_dbfs_list\(\)](#), [db_dbfs_mkdirs\(\)](#), [db_dbfs_move\(\)](#), [db_dbfs_put\(\)](#)

db_host	<i>Generate/Fetch Databricks Host</i>
---------	---------------------------------------

Description

If both `id` and `prefix` are `NULL` then the function will check for the `DATABRICKS_HOST` environment variable. `.databrickscfg` will be searched if `db_profile` and `use_databrickscfg` are set or if Posit Workbench managed OAuth credentials are detected.

When defining `id` and `prefix` you do not need to specify the whole URL. E.g. `https://<prefix>.<id>.cloud.databricks` is the form to follow.

Usage

```
db_host(id = NULL, prefix = NULL, profile = default_config_profile())
```

Arguments

<code>id</code>	The workspace string
<code>prefix</code>	Workspace prefix
<code>profile</code>	Profile to use when fetching from environment variable (e.g. <code>.Renviron</code>) or <code>.databrickscfg</code> file

Details

The behaviour is subject to change depending if `db_profile` and `use_databrickscfg` options are set.

- `use_databrickscfg`: Boolean (default: `FALSE`), determines if credentials are fetched from profile of `.databrickscfg` or `.Renviron`
- `db_profile`: String (default: `NULL`), determines profile used. `.databrickscfg` will automatically be used when Posit Workbench managed OAuth credentials are detected.

See vignette on authentication for more details.

Value

workspace URL

See Also

Other Databricks Authentication Helpers: [db_read_netrc\(\)](#), [db_token\(\)](#), [db_ws_id\(\)](#)

db_jobs_create	Create Job
----------------	------------

Description

Create Job

Usage

```
db_jobs_create(  
  name,  
  tasks,  
  schedule = NULL,  
  job_clusters = NULL,  
  parameters = list(),  
  email_notifications = NULL,  
  timeout_seconds = NULL,  
  max_concurrent_runs = 1,  
  access_control_list = NULL,  
  git_source = NULL,  
  queue = TRUE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

name	Name for the job.
tasks	Task specifications to be executed by this job. Use job_tasks() .
schedule	Instance of cron_schedule() .
job_clusters	Named list of job cluster specifications (using new_cluster()) that can be shared and reused by tasks of this job. Libraries cannot be declared in a shared job cluster. You must declare dependent libraries in task settings.
parameters	Named list of job level parameters. Values of the list represent default values.
email_notifications	Instance of email_notifications() .
timeout_seconds	An optional timeout applied to each run of this job. The default behavior is to have no timeout.
max_concurrent_runs	Maximum allowed number of concurrent runs of the job. Set this value if you want to be able to execute multiple runs of the same job concurrently. This setting affects only new runs. This value cannot exceed 1000. Setting this value to 0 causes all new runs to be skipped. The default behavior is to allow only 1 concurrent run.

access_control_list	Instance of access_control_request() .
git_source	Optional specification for a remote repository containing the notebooks used by this job's notebook tasks. Instance of git_source() .
queue	If true, enable queueing for the job.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

[Full Documentation](#)

See Also

[job_tasks\(\)](#), [job_task\(\)](#), [email_notifications\(\)](#), [cron_schedule\(\)](#), [access_control_request\(\)](#), [access_control_req_user\(\)](#), [access_control_req_group\(\)](#), [git_source\(\)](#)

Other Jobs API: [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_delete	<i>Delete a Job</i>
----------------	---------------------

Description

Delete a Job

Usage

```
db_jobs_delete(  
  job_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

job_id	The canonical identifier of the job.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_get	<i>Get Job Details</i>
-------------	------------------------

Description

Get Job Details

Usage

```
db_jobs_get(  
  job_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- job_id The canonical identifier of the job.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_list	List Jobs
--------------	-----------

Description

List Jobs

Usage

```
db_jobs_list(  
  limit = 25,  
  offset = 0,  
  expand_tasks = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

limit	Number of jobs to return. This value must be greater than 0 and less or equal to 25. The default value is 25. If a request specifies a limit of 0, the service instead uses the maximum limit.
offset	The offset of the first job to return, relative to the most recently created job.
expand_tasks	Whether to include task and cluster details in the response.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_repair_run	<i>Repair A Job Run</i>
--------------------	-------------------------

Description

Repair A Job Run

Usage

```
db_jobs_repair_run(  
  run_id,  
  rerun_tasks = NULL,  
  job_parameters = list(),  
  latest_repair_id = NULL,  
  performance_target = NULL,  
  pipeline_full_refresh = NULL,  
  rerun_all_failed_tasks = NULL,  
  rerun_dependent_tasks = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- run_id Job run ID of the run to repair. The run must not be in progress.
- rerun_tasks Character vector. Task keys of the task runs to repair.
- job_parameters Named list of job level parameters used in the run.
- latest_repair_id The ID of the latest repair. This parameter is not required when repairing a run for the first time, but must be provided on subsequent requests to repair the same run.
- performance_target The performance mode on a serverless job (either 'PERFORMANCE_OPTIMIZED' or 'STANDARD'). The performance target determines the level of compute performance or cost-efficiency for the run. This field overrides the performance target defined on the job level.
- pipeline_full_refresh Boolean. Controls whether the pipeline should perform a full refresh.
- rerun_all_failed_tasks Boolean. If TRUE, repair all failed tasks. Only one of rerun_tasks or rerun_all_failed_tasks can be used.
- rerun_dependent_tasks Boolean. If TRUE, repair all tasks that depend on the tasks in rerun_tasks, even if they were previously successful. Can be also used in combination with rerun_all_failed_tasks.

host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Parameters which are shared with `db_jobs_create()` are optional, only specify those that are changing.

See Also

Other Jobs API: `db_jobs_create()`, `db_jobs_delete()`, `db_jobs_get()`, `db_jobs_list()`, `db_jobs_reset()`, `db_jobs_run_now()`, `db_jobs_runs_cancel()`, `db_jobs_runs_delete()`, `db_jobs_runs_export()`, `db_jobs_runs_get()`, `db_jobs_runs_get_output()`, `db_jobs_runs_list()`, `db_jobs_runs_submit()`, `db_jobs_update()`

db_jobs_reset	<i>Overwrite All Settings For A Job</i>
---------------	---

Description

Overwrite All Settings For A Job

Usage

```
db_jobs_reset(
  job_id,
  name,
  schedule,
  tasks,
  job_clusters = NULL,
  parameters = list(),
  email_notifications = NULL,
  timeout_seconds = NULL,
  max_concurrent_runs = 1,
  access_control_list = NULL,
  git_source = NULL,
  queue = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

job_id	The canonical identifier of the job.
name	Name for the job.
schedule	Instance of cron_schedule() .
tasks	Task specifications to be executed by this job. Use job_tasks() .
job_clusters	Named list of job cluster specifications (using new_cluster()) that can be shared and reused by tasks of this job. Libraries cannot be declared in a shared job cluster. You must declare dependent libraries in task settings.
parameters	Named list of job level parameters. Values of the list represent default values.
email_notifications	Instance of email_notifications() .
timeout_seconds	An optional timeout applied to each run of this job. The default behavior is to have no timeout.
max_concurrent_runs	Maximum allowed number of concurrent runs of the job. Set this value if you want to be able to execute multiple runs of the same job concurrently. This setting affects only new runs. This value cannot exceed 1000. Setting this value to 0 causes all new runs to be skipped. The default behavior is to allow only 1 concurrent run.
access_control_list	Instance of access_control_request() .
git_source	Optional specification for a remote repository containing the notebooks used by this job's notebook tasks. Instance of git_source() .
queue	If true, enable queueing for the job.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_cancel	<i>Cancel Job Run</i>
---------------------	-----------------------

Description

Cancels a run.

Usage

```
db_jobs_runs_cancel(  
    run_id,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

run_id	The canonical identifier of the run.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

The run is canceled asynchronously, so when this request completes, the run may still be running. The run are terminated shortly. If the run is already in a terminal `life_cycle_state`, this method is a no-op.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_delete *Delete Job Run*

Description

Delete Job Run

Usage

```
db_jobs_runs_delete(
  run_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

run_id	The canonical identifier of the run.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_export *Export Job Run Output*

Description

Export and retrieve the job run task.

Usage

```
db_jobs_runs_export(
  run_id,
  views_to_export = c("CODE", "DASHBOARDS", "ALL"),
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

run_id	The canonical identifier of the run.
views_to_export	Which views to export. One of CODE, DASHBOARDS, ALL. Defaults to CODE.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_get

*Get Job Run Details***Description**

Retrieve the metadata of a run.

Usage

```
db_jobs_runs_get(
  run_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

run_id	The canonical identifier of the run.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_get_output	<i>Get Job Run Output</i>
-------------------------	---------------------------

Description

Get Job Run Output

Usage

```
db_jobs_runs_get_output(  
  run_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

run_id	The canonical identifier of the run.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_runs_list	<i>List Job Runs</i>
-------------------	----------------------

Description

List runs in descending order by start time.

Usage

```
db_jobs_runs_list(
  job_id,
  active_only = FALSE,
  completed_only = FALSE,
  offset = 0,
  limit = 25,
  run_type = c("JOB_RUN", "WORKFLOW_RUN", "SUBMIT_RUN"),
  expand_tasks = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

<code>job_id</code>	The canonical identifier of the job.
<code>active_only</code>	Boolean (Default: FALSE). If TRUE only active runs are included in the results; otherwise, lists both active and completed runs. An active run is a run in the PENDING, RUNNING, or TERMINATING. This field cannot be true when <code>completed_only</code> is TRUE.
<code>completed_only</code>	Boolean (Default: FALSE). If TRUE, only completed runs are included in the results; otherwise, lists both active and completed runs. This field cannot be true when <code>active_only</code> is TRUE.
<code>offset</code>	The offset of the first job to return, relative to the most recently created job.
<code>limit</code>	Number of jobs to return. This value must be greater than 0 and less or equal to 25. The default value is 25. If a request specifies a limit of 0, the service instead uses the maximum limit.
<code>run_type</code>	The type of runs to return. One of JOB_RUN, WORKFLOW_RUN, SUBMIT_RUN.
<code>expand_tasks</code>	Whether to include task and cluster details in the response.
<code>host</code>	Databricks workspace URL, defaults to calling <code>db_host()</code> .
<code>token</code>	Databricks workspace token, defaults to calling <code>db_token()</code> .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Jobs API: `db_jobs_create()`, `db_jobs_delete()`, `db_jobs_get()`, `db_jobs_list()`, `db_jobs_repair_run()`, `db_jobs_reset()`, `db_jobs_run_now()`, `db_jobs_runs_cancel()`, `db_jobs_runs_delete()`, `db_jobs_runs_export()`, `db_jobs_runs_get()`, `db_jobs_runs_get_output()`, `db_jobs_runs_submit()`, `db_jobs_update()`

 db_jobs_runs_submit *Create And Trigger A One-Time Run*

Description

Create And Trigger A One-Time Run

Usage

```
db_jobs_runs_submit(
  tasks,
  run_name,
  timeout_seconds = NULL,
  idempotency_token = NULL,
  access_control_list = NULL,
  git_source = NULL,
  job_clusters = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

tasks	Task specifications to be executed by this job. Use job_tasks() .
run_name	Name for the run.
timeout_seconds	An optional timeout applied to each run of this job. The default behavior is to have no timeout.
idempotency_token	An optional token that can be used to guarantee the idempotency of job run requests. If an active run with the provided token already exists, the request does not create a new run, but returns the ID of the existing run instead. If you specify the idempotency token, upon failure you can retry until the request succeeds. Databricks guarantees that exactly one run is launched with that idempotency token. This token must have at most 64 characters.
access_control_list	Instance of access_control_request() .
git_source	Optional specification for a remote repository containing the notebooks used by this job's notebook tasks. Instance of git_source() .
job_clusters	Named list of job cluster specifications (using new_cluster()) that can be shared and reused by tasks of this job. Libraries cannot be declared in a shared job cluster. You must declare dependent libraries in task settings.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

perform_request

If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_update\(\)](#)

db_jobs_run_now

Trigger A New Job Run

Description

Trigger A New Job Run

Usage

```
db_jobs_run_now(
  job_id,
  parameters = list(),
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

job_id	The canonical identifier of the job.
parameters	Named list of job level parameters.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- *_params parameters cannot exceed 10,000 bytes when serialized to JSON.
- jar_params and notebook_params are mutually exclusive.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#), [db_jobs_update\(\)](#)

db_jobs_update	<i>Partially Update A Job</i>
----------------	-------------------------------

Description

Partially Update A Job

Usage

```
db_jobs_update(  
  job_id,  
  fields_to_remove = list(),  
  name = NULL,  
  schedule = NULL,  
  tasks = NULL,  
  job_clusters = NULL,  
  email_notifications = NULL,  
  timeout_seconds = NULL,  
  max_concurrent_runs = NULL,  
  access_control_list = NULL,  
  git_source = NULL,  
  queue = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

job_id	The canonical identifier of the job.
fields_to_remove	Remove top-level fields in the job settings. Removing nested fields is not supported. This field is optional. Must be a <code>list()</code> .
name	Name for the job.
schedule	Instance of <code>cron_schedule()</code> .
tasks	Task specifications to be executed by this job. Use <code>job_tasks()</code> .
job_clusters	Named list of job cluster specifications (using <code>new_cluster()</code>) that can be shared and reused by tasks of this job. Libraries cannot be declared in a shared job cluster. You must declare dependent libraries in task settings.
email_notifications	Instance of <code>email_notifications()</code> .
timeout_seconds	An optional timeout applied to each run of this job. The default behavior is to have no timeout.

max_concurrent_runs	Maximum allowed number of concurrent runs of the job. Set this value if you want to be able to execute multiple runs of the same job concurrently. This setting affects only new runs. This value cannot exceed 1000. Setting this value to 0 causes all new runs to be skipped. The default behavior is to allow only 1 concurrent run.
access_control_list	Instance of access_control_request() .
git_source	Optional specification for a remote repository containing the notebooks used by this job's notebook tasks. Instance of git_source() .
queue	If true, enable queueing for the job.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Parameters which are shared with [db_jobs_create\(\)](#) are optional, only specify those that are changing.

See Also

Other Jobs API: [db_jobs_create\(\)](#), [db_jobs_delete\(\)](#), [db_jobs_get\(\)](#), [db_jobs_list\(\)](#), [db_jobs_repair_run\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_run_now\(\)](#), [db_jobs_runs_cancel\(\)](#), [db_jobs_runs_delete\(\)](#), [db_jobs_runs_export\(\)](#), [db_jobs_runs_get\(\)](#), [db_jobs_runs_get_output\(\)](#), [db_jobs_runs_list\(\)](#), [db_jobs_runs_submit\(\)](#)

db_libs_all_cluster_statuses

Get Status of All Libraries on All Clusters

Description

Get Status of All Libraries on All Clusters

Usage

```
db_libs_all_cluster_statuses(  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

A status will be available for all libraries installed on clusters via the API or the libraries UI as well as libraries set to be installed on all clusters via the libraries UI.

If a library has been set to be installed on all clusters, `is_library_for_all_clusters` will be true, even if the library was also installed on this specific cluster.

See Also

Other Libraries API: [db_libs_cluster_status\(\)](#), [db_libs_install\(\)](#), [db_libs_uninstall\(\)](#)

`db_libs_cluster_status`*Get Status of Libraries on Cluster*

Description

Get Status of Libraries on Cluster

Usage

```
db_libs_cluster_status(  
  cluster_id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

cluster_id	Unique identifier of a Databricks cluster.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also[wait_for_lib_installs\(\)](#)Other Libraries API: [db_libs_all_cluster_statuses\(\)](#), [db_libs_install\(\)](#), [db_libs_uninstall\(\)](#)

db_libs_install

Install Library on Cluster

Description

Install Library on Cluster

Usage

```

db_libs_install(
    cluster_id,
    libraries,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)

```

Arguments

cluster_id	Unique identifier of a Databricks cluster.
libraries	An object created by libraries() and the appropriate <code>lib_*()</code> functions.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Installation is asynchronous - it completes in the background after the request.

This call will fail if the cluster is terminated. Installing a wheel library on a cluster is like running the pip command against the wheel file directly on driver and executors.

Installing a wheel library on a cluster is like running the pip command against the wheel file directly on driver and executors. All the dependencies specified in the library setup.py file are installed and this requires the library name to satisfy the wheel file name convention.

The installation on the executors happens only when a new task is launched. With Databricks Runtime 7.1 and below, the installation order of libraries is nondeterministic. For wheel libraries, you can ensure a deterministic installation order by creating a zip file with suffix `.wheelhouse.zip` that includes all the wheel files.

See Also

[lib_egg\(\)](#), [lib_cran\(\)](#), [lib_jar\(\)](#), [lib_maven\(\)](#), [lib_pypi\(\)](#), [lib_whl\(\)](#)

Other Libraries API: [db_libs_all_cluster_statuses\(\)](#), [db_libs_cluster_status\(\)](#), [db_libs_uninstall\(\)](#)

db_libs_uninstall	<i>Uninstall Library on Cluster</i>
-------------------	-------------------------------------

Description

Uninstall Library on Cluster

Usage

```
db_libs_uninstall(
  cluster_id,
  libraries,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

cluster_id	Unique identifier of a Databricks cluster.
libraries	An object created by libraries() and the appropriate lib_*() functions.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

The libraries aren't uninstalled until the cluster is restarted.

Uninstalling libraries that are not installed on the cluster has no impact but is not an error.

See Also

Other Libraries API: [db_libs_all_cluster_statuses\(\)](#), [db_libs_cluster_status\(\)](#), [db_libs_install\(\)](#)

db_mlflow_model_approve_transition_req

Approve Model Version Stage Transition Request

Description

Approve Model Version Stage Transition Request

Usage

```
db_mlflow_model_approve_transition_req(  
  name,  
  version,  
  stage = c("None", "Staging", "Production", "Archived"),  
  archive_existing_versions = TRUE,  
  comment = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

name	Name of the model.
version	Version of the model.
stage	Target stage of the transition. Valid values are: None, Staging, Production, Archived.
archive_existing_versions	Boolean (Default: TRUE). Specifies whether to archive all current model versions in the target stage.
comment	User-provided comment on the action.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http request is returned <i>without</i> being performed.

See Also

Other Model Registry API: `db_mlflow_model_delete_transition_req()`,`db_mlflow_model_open_transition_reqs()`
`db_mlflow_model_reject_transition_req()`,`db_mlflow_model_transition_req()`,`db_mlflow_model_transition_reqs()`
`db_mlflow_model_version_comment()`,`db_mlflow_model_version_comment_delete()`,`db_mlflow_model_version_delete()`
`db_mlflow_registered_model_details()`

db_mlflow_model_delete_transition_req
<i>Delete a Model Version Stage Transition Request</i>

Description

Delete a Model Version Stage Transition Request

Usage

```
db_mlflow_model_delete_transition_req(  
  name,  
  version,  
  stage = c("None", "Staging", "Production", "Archived"),  
  creator,  
  comment = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

name	Name of the model.
version	Version of the model.
stage	Target stage of the transition. Valid values are: None, Staging, Production, Archived.
creator	Username of the user who created this request. Of the transition requests matching the specified details, only the one transition created by this user will be deleted.
comment	User-provided comment on the action.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_req\(\)](#), [db_mlflow_model_transition_reqs\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comment_delete\(\)](#), [db_mlflow_model_version_delete\(\)](#), [db_mlflow_model_version_details\(\)](#), [db_mlflow_registered_model_details\(\)](#)

db_mflow_model_open_transition_reqs

Get All Open Stage Transition Requests for the Model Version

Description

Get All Open Stage Transition Requests for the Model Version

Usage

```
db_mlflow_model_open_transition_reqs(  
    name,  
    version,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

name	Name of the model.
version	Version of the model.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: `db_mlflow_model_approve_transition_req()`,`db_mlflow_model_delete_transition_req`
`db_mlflow_model_reject_transition_req()`,`db_mlflow_model_transition_req()`,`db_mlflow_model_transition`,
`db_mlflow_model_version_comment()`,`db_mlflow_model_version_comment_delete()`,`db_mlflow_model_version_`
`db_mlflow_registered_model_details()`

db_mlflow_model_reject_transition_req

Reject Model Version Stage Transition Request

Description

Reject Model Version Stage Transition Request

Usage

```
db_mlflow_model_transition_req(  
  name,  
  version,  
  stage = c("None", "Staging", "Production", "Archived"),  
  comment = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

name	Name of the model.
version	Version of the model.
stage	Target stage of the transition. Valid values are: None, Staging, Production, Archived.
comment	User-provided comment on the action.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_delete_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_req\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comment_delete\(\)](#), [db_mlflow_model_version_delete\(\)](#), [db_mlflow_model_version_details\(\)](#), [db_mlflow_registered_model_details\(\)](#)

db_mlflow_model_transition_stage
<i>Transition a Model Version's Stage</i>

Description

Transition a Model Version's Stage

Usage

```

db_mlflow_model_transition_stage(
    name,
    version,
    stage = c("None", "Staging", "Production", "Archived"),
    archive_existing_versions = TRUE,
    comment = NULL,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)

```

Arguments

name	Name of the model.
version	Version of the model.
stage	Target stage of the transition. Valid values are: None, Staging, Production, Archived.
archive_existing_versions	Boolean (Default: TRUE). Specifies whether to archive all current model versions in the target stage.
comment	User-provided comment on the action.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

This is a Databricks version of the MLflow endpoint that also accepts a comment associated with the transition to be recorded.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_delete_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_req\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comment_delete\(\)](#), [db_mlflow_model_version_delete\(\)](#), [db_mlflow_model_version_details\(\)](#), [db_mlflow_registered_model_details\(\)](#)

db_mlflow_model_version_comment_delete
<i>Delete a Comment on a Model Version</i>

Description

Delete a Comment on a Model Version

Usage

```
db_mlflow_model_version_comment_delete(  
  id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	Unique identifier of an activity.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_delete_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_req\(\)](#), [db_mlflow_model_transition_stage\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comments\(\)](#), [db_mlflow_registered_model_details\(\)](#)

db_mlflow_model_version_comment_edit
<i>Edit a Comment on a Model Version</i>

Description

Edit a Comment on a Model Version

Usage

```
db_mlflow_model_version_comment_edit(  
  id,  
  comment,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	Unique identifier of an activity.
comment	User-provided comment on the action.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_delete_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_stage\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comment_edit\(\)](#), [db_mlflow_registered_model_details\(\)](#)

`db_mlflow_registered_model_details`*Get Registered Model Details*

Description

Get Registered Model Details

Usage

```
db_mlflow_registered_model_details(  
  name,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

name	Name of the model.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Model Registry API: [db_mlflow_model_approve_transition_req\(\)](#), [db_mlflow_model_delete_transition_req\(\)](#), [db_mlflow_model_open_transition_reqs\(\)](#), [db_mlflow_model_reject_transition_req\(\)](#), [db_mlflow_model_transition_stage\(\)](#), [db_mlflow_model_version_comment\(\)](#), [db_mlflow_model_version_comment_edit\(\)](#)

db_perform_request	<i>Perform Databricks API Request</i>
--------------------	---------------------------------------

Description

Perform Databricks API Request

Usage

db_perform_request(req, ...)

Arguments

req	{http2} request.
...	Parameters passed to http2::resp_body_json()

See Also

Other Request Helpers: [db_req_error_body\(\)](#), [db_request\(\)](#), [db_request_json\(\)](#)

db_query_create	Create a SQL Query
-----------------	--------------------

Description

Create a SQL Query

Usage

```
db_query_create(  
    warehouse_id,  
    query_text,  
    display_name,  
    description = NULL,  
    catalog = NULL,  
    schema = NULL,  
    parent_path = NULL,  
    run_as_mode = c("OWNER", "VIEWER"),  
    apply_auto_limit = FALSE,  
    auto_resolve_display_name = TRUE,  
    tags = list(),  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

warehouse_id	description
query_text	Text of the query to be run.
display_name	Display name of the query that appears in list views, widget headings, and on the query page.
description	General description that conveys additional information about this query such as usage notes.
catalog	Name of the catalog where this query will be executed.
schema	Name of the schema where this query will be executed.
parent_path	Workspace path of the workspace folder containing the object.
run_as_mode	Sets the "Run as" role for the object.
apply_auto_limit	Whether to apply a 1000 row limit to the query result.
auto_resolve_display_name	Automatically resolve query display name conflicts. Otherwise, fail the request if the query's display name conflicts with an existing query's display name.

tags	Named list that describes the warehouse. Databricks tags all warehouse resources with these tags.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other SQL Queries API: [db_query_delete\(\)](#), [db_query_get\(\)](#), [db_query_list\(\)](#), [db_query_update\(\)](#)

db_query_delete	<i>Delete a SQL Query</i>
-----------------	---------------------------

Description

Delete a SQL Query

Usage

```
db_query_delete(  
  id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	String, ID for the query.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Moves a query to the trash. Trashed queries immediately disappear from searches and list views, and cannot be used for alerts. You can restore a trashed query through the UI. A trashed query is permanently deleted after 30 days.

See Also

Other SQL Queries API: [db_query_create\(\)](#), [db_query_get\(\)](#), [db_query_list\(\)](#), [db_query_update\(\)](#)

db_query_get	<i>Get a SQL Query</i>
--------------	------------------------

Description

Returns the repo with the given repo ID.

Usage

```
db_query_get(id, host = db_host(), token = db_token(), perform_request = TRUE)
```

Arguments

id	String, ID for the query.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other SQL Queries API: [db_query_create\(\)](#), [db_query_delete\(\)](#), [db_query_list\(\)](#), [db_query_update\(\)](#)

db_query_list	<i>List SQL Queries</i>
---------------	-------------------------

Description

List SQL Queries

Usage

```
db_query_list(  
  page_size = 20,  
  page_token = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

page_size	Integer, number of results to return for each request.
page_token	Token used to get the next page of results. If not specified, returns the first page of results as well as a next page token if there are more results.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Gets a list of queries accessible to the user, ordered by creation time. Warning: Calling this API concurrently 10 or more times could result in throttling, service degradation, or a temporary ban.

See Also

Other SQL Queries API: `db_query_create()`, `db_query_delete()`, `db_query_get()`, `db_query_update()`

db_query_update	<i>Update a SQL Query</i>
-----------------	---------------------------

Description

Update a SQL Query

Usage

```
db_query_update(  
  id,  
  warehouse_id = NULL,  
  query_text = NULL,  
  display_name = NULL,  
  description = NULL,  
  catalog = NULL,  
  schema = NULL,  
  parent_path = NULL,  
  run_as_mode = NULL,  
  apply_auto_limit = NULL,  
  auto_resolve_display_name = NULL,  
  tags = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	Query id
warehouse_id	description
query_text	Text of the query to be run.
display_name	Display name of the query that appears in list views, widget headings, and on the query page.
description	General description that conveys additional information about this query such as usage notes.
catalog	Name of the catalog where this query will be executed.
schema	Name of the schema where this query will be executed.
parent_path	Workspace path of the workspace folder containing the object.
run_as_mode	Sets the "Run as" role for the object.
apply_auto_limit	Whether to apply a 1000 row limit to the query result.
auto_resolve_display_name	Automatically resolve query display name conflicts. Otherwise, fail the request if the query's display name conflicts with an existing query's display name.
tags	Named list that describes the warehouse. Databricks tags all warehouse resources with these tags.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other SQL Queries API: [db_query_create\(\)](#), [db_query_delete\(\)](#), [db_query_get\(\)](#), [db_query_list\(\)](#)

db_read_netrc

Read .netrc File

Description

Read .netrc File

Usage

```
db_read_netrc(path = "~/ .netrc")
```

Arguments

path path of .netrc file, default is ~/ .netrc.

Value

named list of .netrc entries

See Also

Other Databricks Authentication Helpers: [db_host\(\)](#), [db_token\(\)](#), [db_wsuid\(\)](#)

db_repl	<i>Remote REPL to Databricks Cluster</i>
---------	--

Description

Remote REPL to Databricks Cluster

Usage

```
db_repl(  
  cluster_id,  
  language = c("r", "py", "scala", "sql", "sh"),  
  host = db_host(),  
  token = db_token()  
)
```

Arguments

- | | |
|------------|--|
| cluster_id | Cluster Id to create REPL context against. |
| language | for REPL ('r', 'py', 'scala', 'sql', 'sh') are supported. |
| host | Databricks workspace URL, defaults to calling db_host() . |
| token | Databricks workspace token, defaults to calling db_token() . |

Details

db_repl() will take over the existing console and allow execution of commands against a Databricks cluster. For RStudio users there are Addins which can be bound to keyboard shortcuts to improve usability.

db_repo_create	Create Repo
----------------	-------------

Description

Creates a repo in the workspace and links it to the remote Git repo specified.

Usage

```
db_repo_create(
  url,
  provider,
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

url	URL of the Git repository to be linked.
provider	Git provider. This field is case-insensitive. The available Git providers are <code>github</code> , <code>bitbucketCloud</code> , <code>gitLab</code> , <code>azureDevOpsServices</code> , <code>githubEnterprise</code> , <code>bitbucketServer</code> and <code>gitLabEnterpriseEdition</code> .
path	Desired path for the repo in the workspace. Must be in the format <code>/Repos/{folder}/{repo-name}</code> .
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Repos API: `db_repo_delete()`, `db_repo_get()`, `db_repo_get_all()`, `db_repo_update()`

db_repo_delete	Delete Repo
----------------	-------------

Description

Deletes the specified repo

Usage

```
db_repo_delete(
  repo_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

repo_id	The ID for the corresponding repo to access.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Repos API: [db_repo_create\(\)](#), [db_repo_get\(\)](#), [db_repo_get_all\(\)](#), [db_repo_update\(\)](#)

db_repo_get	<i>Get Repo</i>
-------------	-----------------

Description

Returns the repo with the given repo ID.

Usage

```
db_repo_get(
  repo_id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

repo_id	The ID for the corresponding repo to access.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Repos API: [db_repo_create\(\)](#), [db_repo_delete\(\)](#), [db_repo_get_all\(\)](#), [db_repo_update\(\)](#)

db_repo_get_all	<i>Get All Repos</i>
-----------------	----------------------

Description

Get All Repos

Usage

```
db_repo_get_all(  
    path_prefix,  
    next_page_token = NULL,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

path_prefix	Filters repos that have paths starting with the given path prefix.
next_page_token	Token used to get the next page of results. If not specified, returns the first page of results as well as a next page token if there are more results.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Returns repos that the calling user has Manage permissions on. Results are paginated with each page containing twenty repos.

See Also

Other Repos API: [db_repo_create\(\)](#), [db_repo_delete\(\)](#), [db_repo_get\(\)](#), [db_repo_update\(\)](#)

db_repo_update	<i>Update Repo</i>
----------------	--------------------

Description

Updates the repo to the given branch or tag.

Usage

```
db_repo_update(  
    repo_id,  
    branch = NULL,  
    tag = NULL,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

repo_id	The ID for the corresponding repo to access.
branch	Branch that the local version of the repo is checked out to.
tag	Tag that the local version of the repo is checked out to.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Specify either branch or tag, not both.

Updating the repo to a tag puts the repo in a detached HEAD state. Before committing new changes, you must update the repo to a branch instead of the detached HEAD.

See Also

Other Repos API: [db_repo_create\(\)](#), [db_repo_delete\(\)](#), [db_repo_get\(\)](#), [db_repo_get_all\(\)](#)

db_request	<i>Databricks Request Helper</i>
------------	----------------------------------

Description

Databricks Request Helper

Usage

```
db_request(endpoint, method, version = NULL, body = NULL, host, token, ...)
```

Arguments

endpoint	Databricks REST API Endpoint
method	Passed to httr2::req_method()
version	String, API version of endpoint. E.g. 2.0.
body	Named list, passed to httr2::req_body_json() .
host	Databricks host, defaults to db_host() .
token	Databricks token, defaults to db_token() .
...	Parameters passed on to httr2::req_body_json() when body is not NULL.

Value

request

See Also

Other Request Helpers: [db_perform_request\(\)](#), [db_req_error_body\(\)](#), [db_request_json\(\)](#)

db_request_json	<i>Generate Request JSON</i>
-----------------	------------------------------

Description

Generate Request JSON

Usage

```
db_request_json(req)
```

Arguments

req	a httr2 request, ideally from db_request() .
-----	--

Value

JSON string

See Also

Other Request Helpers: [db_perform_request\(\)](#), [db_req_error_body\(\)](#), [db_request\(\)](#)

<code>db_req_error_body</code>	<i>Propagate Databricks API Errors</i>
--------------------------------	--

Description

Propagate Databricks API Errors

Usage

`db_req_error_body(resp)`

Arguments

`resp` Object with class `httr2_response`.

See Also

Other Request Helpers: [db_perform_request\(\)](#), [db_request\(\)](#), [db_request_json\(\)](#)

<code>db_secrets_delete</code>	<i>Delete Secret in Secret Scope</i>
--------------------------------	--------------------------------------

Description

Delete Secret in Secret Scope

Usage

```
db_secrets_delete(  
  scope,  
  key,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Name of the scope that contains the secret to delete.
key	Name of the secret to delete.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You must have WRITE or MANAGE permission on the secret scope.

- Throws RESOURCE_DOES_NOT_EXIST if no such secret scope or secret exists.
- Throws PERMISSION_DENIED if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_list	<i>List Secrets in Secret Scope</i>
-----------------	-------------------------------------

Description

List Secrets in Secret Scope

Usage

```
db_secrets_list(  
  scope,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Name of the scope whose secrets you want to list
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

This is a metadata-only operation; you cannot retrieve secret data using this API. You must have READ permission to make this call.

The last_updated_timestamp returned is in milliseconds since epoch.

- Throws RESOURCE_DOES_NOT_EXIST if no such secret scope exists.
- Throws PERMISSION_DENIED if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_put	<i>Put Secret in Secret Scope</i>
----------------	-----------------------------------

Description

Insert a secret under the provided scope with the given name.

Usage

```
db_secrets_put(  
  scope,  
  key,  
  value,  
  as_bytes = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Name of the scope to which the secret will be associated with
key	Unique name to identify the secret.
value	Contents of the secret to store, must be a string.
as_bytes	Boolean (default: FALSE). Determines if value is stored as bytes.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If a secret already exists with the same name, this command overwrites the existing secret's value.

The server encrypts the secret using the secret scope's encryption settings before storing it. You must have WRITE or MANAGE permission on the secret scope.

The secret key must consist of alphanumeric characters, dashes, underscores, and periods, and cannot exceed 128 characters. The maximum allowed secret value size is 128 KB. The maximum number of secrets in a given scope is 1000.

You can read a secret value only from within a command on a cluster (for example, through a notebook); there is no API to read a secret value outside of a cluster. The permission applied is based on who is invoking the command and you must have at least READ permission.

The input fields `string_value` or `bytes_value` specify the type of the secret, which will determine the value returned when the secret value is requested. Exactly one must be specified, this function interfaces these parameters via `as_bytes` which defaults to FALSE.

- Throws `RESOURCE_DOES_NOT_EXIST` if no such secret scope exists.
- Throws `RESOURCE_LIMIT_EXCEEDED` if maximum number of secrets in scope is exceeded.
- Throws `INVALID_PARAMETER_VALUE` if the key name or value length is invalid.
- Throws `PERMISSION_DENIED` if the user does not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_acl_delete
Delete Secret Scope ACL

Description

Delete the given ACL on the given scope.

Usage

```
db_secrets_scope_acl_delete(
  scope,
  principal,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

scope	Name of the scope to remove permissions.
principal	Principal to remove an existing ACL.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You must have the MANAGE permission to invoke this API.

- Throws RESOURCE_DOES_NOT_EXIST if no such secret scope, principal, or ACL exists.
- Throws PERMISSION_DENIED if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_acl_get

Get Secret Scope ACL

Description

Get Secret Scope ACL

Usage

```
db_secrets_scope_acl_get(  
  scope,  
  principal,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Name of the scope to fetch ACL information from.
principal	Principal to fetch ACL information from.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You must have the MANAGE permission to invoke this

- Throws RESOURCE_DOES_NOT_EXIST if no such secret scope exists.
- Throws PERMISSION_DENIED if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_acl_list

List Secret Scope ACL's

Description

List Secret Scope ACL's

Usage

```
db_secrets_scope_acl_list(
  scope,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

scope	Name of the scope to fetch ACL information from.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You must have the `MANAGE` permission to invoke this API.

- Throws `RESOURCE_DOES_NOT_EXIST` if no such secret scope exists.
- Throws `PERMISSION_DENIED` if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_acl_put
<i>Put ACL on Secret Scope</i>

Description

Put ACL on Secret Scope

Usage

```
db_secrets_scope_acl_put(  
  scope,  
  principal,  
  permission = c("READ", "WRITE", "MANAGE"),  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Name of the scope to apply permissions.
principal	Principal to which the permission is applied
permission	Permission level applied to the principal. One of <code>READ</code> , <code>WRITE</code> , <code>MANAGE</code> .
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If <code>TRUE</code> (default) the request is performed, if <code>FALSE</code> the http2 request is returned <i>without</i> being performed.

Details

Create or overwrite the ACL associated with the given principal (user or group) on the specified scope point. In general, a user or group will use the most powerful permission available to them, and permissions are ordered as follows:

- **MANAGE** - Allowed to change ACLs, and read and write to this secret scope.
- **WRITE** - Allowed to read and write to this secret scope.
- **READ** - Allowed to read this secret scope and list what secrets are available.

You must have the **MANAGE** permission to invoke this API.

The principal is a user or group name corresponding to an existing Databricks principal to be granted or revoked access.

- Throws **RESOURCE_DOES_NOT_EXIST** if no such secret scope exists.
- Throws **RESOURCE_ALREADY_EXISTS** if a permission for the principal already exists.
- Throws **INVALID_PARAMETER_VALUE** if the permission is invalid.
- Throws **PERMISSION_DENIED** if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_create

Create Secret Scope

Description

Create Secret Scope

Usage

```
db_secrets_scope_create(  
  scope,  
  initial_manage_principal = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

scope	Scope name requested by the user. Scope names are unique.
initial_manage_principal	The principal that is initially granted MANAGE permission to the created scope.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Create a Databricks-backed secret scope in which secrets are stored in Databricks-managed storage and encrypted with a cloud-based specific encryption key.

The scope name:

- Must be unique within a workspace.
- Must consist of alphanumeric characters, dashes, underscores, and periods, and may not exceed 128 characters.

The names are considered non-sensitive and are readable by all users in the workspace. A workspace is limited to a maximum of 100 secret scopes.

If `initial_manage_principal` is specified, the initial ACL applied to the scope is applied to the supplied principal (user or group) with MANAGE permissions. The only supported principal for this option is the group users, which contains all users in the workspace. If `initial_manage_principal` is not specified, the initial ACL with MANAGE permission applied to the scope is assigned to the API request issuer's user identity.

- Throws `RESOURCE_ALREADY_EXISTS` if a scope with the given name already exists.
- Throws `RESOURCE_LIMIT_EXCEEDED` if maximum number of scopes in the workspace is exceeded.
- Throws `INVALID_PARAMETER_VALUE` if the scope name is invalid.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_delete\(\)](#), [db_secrets_scope_list_all\(\)](#)

`db_secrets_scope_delete`*Delete Secret Scope*

Description

Delete Secret Scope

Usage

```
db_secrets_scope_delete(  
    scope,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

<code>scope</code>	Name of the scope to delete.
<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
<code>token</code>	Databricks workspace token, defaults to calling db_token() .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- Throws RESOURCE_DOES_NOT_EXIST if the scope does not exist.
- Throws PERMISSION_DENIED if the user does not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_list_all\(\)](#)

db_secrets_scope_list_all	
	<i>List Secret Scopes</i>

Description

List Secret Scopes

Usage

```
db_secrets_scope_list_all(  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

- Throws PERMISSION_DENIED if you do not have permission to make this API call.

See Also

Other Secrets API: [db_secrets_delete\(\)](#), [db_secrets_list\(\)](#), [db_secrets_put\(\)](#), [db_secrets_scope_acl_delete\(\)](#), [db_secrets_scope_acl_get\(\)](#), [db_secrets_scope_acl_list\(\)](#), [db_secrets_scope_acl_put\(\)](#), [db_secrets_scope_create\(\)](#), [db_secrets_scope_delete\(\)](#)

db_sql_exec_cancel	<i>Cancel SQL Query</i>
--------------------	-------------------------

Description

Cancel SQL Query

Usage

```
db_sql_exec_cancel(  
    statement_id,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

statement_id	String, query execution statement_id
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Requests that an executing statement be canceled. Callers must poll for status to see the terminal state.

[Read more on Databricks API docs](#)

See Also

Other SQL Execution APIs: [db_sql_exec_query\(\)](#), [db_sql_exec_result\(\)](#), [db_sql_exec_status\(\)](#)

db_sql_exec_poll_for_success

Poll a Query Until Successful

Description

Poll a Query Until Successful

Usage

```
db_sql_exec_poll_for_success(  
    statement_id,  
    interval = 1,  
    show_progress = TRUE,  
    host = db_host(),  
    token = db_token()  
)
```

Arguments

statement_id	String, query execution statement_id
interval	Number of seconds between status checks.
show_progress	If TRUE, show progress updates during polling (default: TRUE)
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

db_sql_exec_query	<i>Execute SQL Query</i>
-------------------	--------------------------

Description

Execute SQL Query

Usage

```
db_sql_exec_query(  
  statement,  
  warehouse_id,  
  catalog = NULL,  
  schema = NULL,  
  parameters = NULL,  
  row_limit = NULL,  
  byte_limit = NULL,  
  disposition = c("INLINE", "EXTERNAL_LINKS"),  
  format = c("JSON_ARRAY", "ARROW_STREAM", "CSV"),  
  wait_timeout = "0s",  
  on_wait_timeout = c("CONTINUE", "CANCEL"),  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

statement	String, the SQL statement to execute. The statement can optionally be parameterized, see parameters.
warehouse_id	String, ID of warehouse upon which to execute a statement.
catalog	String, sets default catalog for statement execution, similar to USE CATALOG in SQL.
schema	String, sets default schema for statement execution, similar to USE SCHEMA in SQL.

parameters	List of Named Lists, parameters to pass into a SQL statement containing parameter markers. A parameter consists of a name, a value, and <i>optionally</i> a type. To represent a NULL value, the value field may be omitted or set to NULL explicitly. See docs for more details.
row_limit	Integer, applies the given row limit to the statement's result set, but unlike the LIMIT clause in SQL, it also sets the truncated field in the response to indicate whether the result was trimmed due to the limit or not.
byte_limit	Integer, applies the given byte limit to the statement's result size. Byte counts are based on internal data representations and might not match the final size in the requested format. If the result was truncated due to the byte limit, then truncated in the response is set to true. When using EXTERNAL_LINKS disposition, a default byte_limit of 100 GiB is applied if byte_limit is not explicitly set.
disposition	One of "INLINE" (default) or "EXTERNAL_LINKS". See docs for details.
format	One of "JSON_ARRAY" (default), "ARROW_STREAM", or "CSV". See docs for details.
wait_timeout	String, default is "10s". The time in seconds the call will wait for the statement's result set as Ns, where N can be set to 0 or to a value between 5 and 50. When set to 0s, the statement will execute in asynchronous mode and the call will not wait for the execution to finish. In this case, the call returns directly with PENDING state and a statement ID which can be used for polling with db_sql_exec_status(). When set between 5 and 50 seconds, the call will behave synchronously up to this timeout and wait for the statement execution to finish. If the execution finishes within this time, the call returns immediately with a manifest and result data (or a FAILED state in case of an execution error). If the statement takes longer to execute, on_wait_timeout determines what should happen after the timeout is reached.
on_wait_timeout	One of "CONTINUE" (default) or "CANCEL". When wait_timeout > 0s, the call will block up to the specified time. If the statement execution doesn't finish within this time, on_wait_timeout determines whether the execution should continue or be canceled. When set to CONTINUE, the statement execution continues asynchronously and the call returns a statement ID which can be used for polling with db_sql_exec_status(). When set to CANCEL, the statement execution is canceled and the call returns with a CANCELED state.
host	Databricks workspace URL, defaults to calling db_host().
token	Databricks workspace token, defaults to calling db_token().
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Refer to the [web documentation](#) for detailed material on interaction of the various parameters and general recommendations

See Also

Other SQL Execution APIs: [db_sql_exec_cancel\(\)](#), [db_sql_exec_result\(\)](#), [db_sql_exec_status\(\)](#)

db_sql_exec_result	<i>Get SQL Query Results</i>
--------------------	------------------------------

Description

Get SQL Query Results

Usage

```
db_sql_exec_result(
    statement_id,
    chunk_index,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

statement_id	String, query execution statement_id
chunk_index	Integer, chunk index to fetch result. Starts from 0.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

After the statement execution has SUCCEEDED, this request can be used to fetch any chunk by index.

Whereas the first chunk with chunk_index = 0 is typically fetched with [db_sql_exec_result\(\)](#) or [db_sql_exec_status\(\)](#), this request can be used to fetch subsequent chunks

The response structure is identical to the nested result element described in the [db_sql_exec_result\(\)](#) request, and similarly includes the next_chunk_index and next_chunk_internal_link fields for simple iteration through the result set.

[Read more on Databricks API docs](#)

See Also

Other SQL Execution APIs: [db_sql_exec_cancel\(\)](#), [db_sql_exec_query\(\)](#), [db_sql_exec_status\(\)](#)

db_sql_exec_status	<i>Get SQL Query Status</i>
--------------------	-----------------------------

Description

Get SQL Query Status

Usage

```
db_sql_exec_status(  
    statement_id,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

statement_id	String, query execution statement_id
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

This request can be used to poll for the statement's status. When the status.state field is SUCCEEDED it will also return the result manifest and the first chunk of the result data.

When the statement is in the terminal states CANCELED, CLOSED or FAILED, it returns HTTP 200 with the state set.

After at least 12 hours in terminal state, the statement is removed from the warehouse and further calls will receive an HTTP 404 response.

[Read more on Databricks API docs](#)

See Also

Other SQL Execution APIs: [db_sql_exec_cancel\(\)](#), [db_sql_exec_query\(\)](#), [db_sql_exec_result\(\)](#)

db_sql_global_warehouse_get
Get Global Warehouse Config

Description

Get Global Warehouse Config

Usage

```
db_sql_global_warehouse_get(  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

db_sql_query	<i>Execute query with SQL Warehouse</i>
--------------	---

Description

Execute query with SQL Warehouse

Usage

```
db_sql_query(  
    warehouse_id,  
    statement,  
    schema = NULL,  
    catalog = NULL,  
    parameters = NULL,
```

```

    row_limit = NULL,
    byte_limit = NULL,
    return_arrow = FALSE,
    max_active_connections = 30,
    disposition = "EXTERNAL_LINKS",
    host = db_host(),
    token = db_token(),
    show_progress = TRUE
)

```

Arguments

warehouse_id	String, ID of warehouse upon which to execute a statement.
statement	String, the SQL statement to execute. The statement can optionally be parameterized, see parameters.
schema	String, sets default schema for statement execution, similar to <code>USE SCHEMA</code> in SQL.
catalog	String, sets default catalog for statement execution, similar to <code>USE CATALOG</code> in SQL.
parameters	List of Named Lists, parameters to pass into a SQL statement containing parameter markers. A parameter consists of a name, a value, and <i>optionally</i> a type. To represent a NULL value, the value field may be omitted or set to NULL explicitly. See docs for more details.
row_limit	Integer, applies the given row limit to the statement's result set, but unlike the LIMIT clause in SQL, it also sets the truncated field in the response to indicate whether the result was trimmed due to the limit or not.
byte_limit	Integer, applies the given byte limit to the statement's result size. Byte counts are based on internal data representations and might not match the final size in the requested format. If the result was truncated due to the byte limit, then truncated in the response is set to true. When using EXTERNAL_LINKS disposition, a default byte_limit of 100 GiB is applied if byte_limit is not explicitly set.
return_arrow	Boolean, determine if result is tibble::tibble or arrow::Table .
max_active_connections	Integer to decide on concurrent downloads.
disposition	Disposition mode ("INLINE" or "EXTERNAL_LINKS")
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
show_progress	If TRUE, show progress updates during query execution (default: TRUE)

Value

[tibble::tibble](#) or [arrow::Table](#).

 db_sql_query_history *List Warehouse Query History*

Description

For more details refer to the [query history documentation](#). This function elevates the sub-components of `filter_by` parameter to the R function directly.

Usage

```
db_sql_query_history(
  statuses = NULL,
  user_ids = NULL,
  endpoint_ids = NULL,
  start_time_ms = NULL,
  end_time_ms = NULL,
  max_results = 100,
  page_token = NULL,
  include_metrics = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

<code>statuses</code>	Allows filtering by query status. Possible values are: QUEUED, RUNNING, CANCELED, FAILED, FINISHED. Multiple permitted.
<code>user_ids</code>	Allows filtering by user ID's. Multiple permitted.
<code>endpoint_ids</code>	Allows filtering by endpoint ID's. Multiple permitted.
<code>start_time_ms</code>	Integer, limit results to queries that started after this time.
<code>end_time_ms</code>	Integer, limit results to queries that started before this time.
<code>max_results</code>	Limit the number of results returned in one page. Default is 100.
<code>page_token</code>	Opaque token used to get the next page of results. Optional.
<code>include_metrics</code>	Whether to include metrics about query execution.
<code>host</code>	Databricks workspace URL, defaults to calling <code>db_host()</code> .
<code>token</code>	Databricks workspace token, defaults to calling <code>db_token()</code> .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

By default the filter parameters `statuses`, `user_ids`, and `endpoints_ids` are NULL.

db_sql_warehouse_create

Create Warehouse

Description

Create Warehouse

Usage

```
db_sql_warehouse_create(
    name,
    cluster_size,
    min_num_clusters = 1,
    max_num_clusters = 1,
    auto_stop_mins = 30,
    tags = list(),
    spot_instance_policy = c("COST_OPTIMIZED", "RELIABILITY_OPTIMIZED"),
    enable_photon = TRUE,
    warehouse_type = c("CLASSIC", "PRO"),
    enable_serverless_compute = NULL,
    disable_uc = FALSE,
    channel = c("CHANNEL_NAME_CURRENT", "CHANNEL_NAME_PREVIEW"),
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

name	Name of the SQL warehouse. Must be unique.
cluster_size	Size of the clusters allocated to the warehouse. One of 2X-Small, X-Small, Small, Medium, Large, X-Large, 2X-Large, 3X-Large, 4X-Large.
min_num_clusters	Minimum number of clusters available when a SQL warehouse is running. The default is 1.
max_num_clusters	Maximum number of clusters available when a SQL warehouse is running. If multi-cluster load balancing is not enabled, this is limited to 1.
auto_stop_mins	Time in minutes until an idle SQL warehouse terminates all clusters and stops. Defaults to 30. For Serverless SQL warehouses (enable_serverless_compute = TRUE), set this to 10.
tags	Named list that describes the warehouse. Databricks tags all warehouse resources with these tags.

spot_instance_policy	The spot policy to use for allocating instances to clusters. This field is not used if the SQL warehouse is a Serverless SQL warehouse.
enable_photon	Whether queries are executed on a native vectorized engine that speeds up query execution. The default is TRUE.
warehouse_type	Either "CLASSIC" (default), or "PRO"
enable_serverless_compute	Whether this SQL warehouse is a Serverless warehouse. To use a Serverless SQL warehouse, you must enable Serverless SQL warehouses for the workspace. If Serverless SQL warehouses are disabled for the workspace, the default is FALSE. If Serverless SQL warehouses are enabled for the workspace, the default is TRUE.
disable_uc	If TRUE will use Hive Metastore (HMS). If FALSE (default), then it will be enabled for Unity Catalog (UC).
channel	Whether to use the current SQL warehouse compute version or the preview version. Databricks does not recommend using preview versions for production workloads. The default is CHANNEL_NAME_CURRENT.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

db_sql_warehouse_delete

Delete Warehouse

Description

Delete Warehouse

Usage

```
db_sql_warehouse_delete(
  id,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

id	ID of the SQL warehouse.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

db_sql_warehouse_edit	<i>Edit Warehouse</i>
-----------------------	-----------------------

Description

Edit Warehouse

Usage

```
db_sql_warehouse_edit(  
  id,  
  name = NULL,  
  cluster_size = NULL,  
  min_num_clusters = NULL,  
  max_num_clusters = NULL,  
  auto_stop_mins = NULL,  
  tags = NULL,  
  spot_instance_policy = NULL,  
  enable_photon = NULL,  
  warehouse_type = NULL,  
  enable_serverless_compute = NULL,  
  channel = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	ID of the SQL warehouse.
name	Name of the SQL warehouse. Must be unique.

cluster_size	Size of the clusters allocated to the warehouse. One of 2X-Small, X-Small, Small, Medium, Large, X-Large, 2X-Large, 3X-Large, 4X-Large.
min_num_clusters	Minimum number of clusters available when a SQL warehouse is running. The default is 1.
max_num_clusters	Maximum number of clusters available when a SQL warehouse is running. If multi-cluster load balancing is not enabled, this is limited to 1.
auto_stop_mins	Time in minutes until an idle SQL warehouse terminates all clusters and stops. Defaults to 30. For Serverless SQL warehouses (enable_serverless_compute = TRUE), set this to 10.
tags	Named list that describes the warehouse. Databricks tags all warehouse resources with these tags.
spot_instance_policy	The spot policy to use for allocating instances to clusters. This field is not used if the SQL warehouse is a Serverless SQL warehouse.
enable_photon	Whether queries are executed on a native vectorized engine that speeds up query execution. The default is TRUE.
warehouse_type	Either "CLASSIC" (default), or "PRO"
enable_serverless_compute	Whether this SQL warehouse is a Serverless warehouse. To use a Serverless SQL warehouse, you must enable Serverless SQL warehouses for the workspace. If Serverless SQL warehouses are disabled for the workspace, the default is FALSE. If Serverless SQL warehouses are enabled for the workspace, the default is TRUE.
channel	Whether to use the current SQL warehouse compute version or the preview version. Databricks does not recommend using preview versions for production workloads. The default is CHANNEL_NAME_CURRENT.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Modify a SQL warehouse. All fields are optional. Missing fields default to the current values.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

`db_sql_warehouse_get` *Get Warehouse*

Description

Get Warehouse

Usage

```
db_sql_warehouse_get(  
    id,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

<code>id</code>	ID of the SQL warehouse.
<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
<code>token</code>	Databricks workspace token, defaults to calling db_token() .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

`db_sql_warehouse_list` *List Warehouses*

Description

List Warehouses

Usage

```
db_sql_warehouse_list(  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_start\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

db_sql_warehouse_start
<i>Start Warehouse</i>

Description

Start Warehouse

Usage

```
db_sql_warehouse_start(  
  id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

id	ID of the SQL warehouse.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_stop\(\)](#), [get_and_start_warehouse\(\)](#)

db_sql_warehouse_stop	<i>Stop Warehouse</i>
-----------------------	-----------------------

Description

Stop Warehouse

Usage

```
db_sql_warehouse_stop(  
  id,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- id ID of the SQL warehouse.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

See Also

Other Warehouse API: [db_sql_global_warehouse_get\(\)](#), [db_sql_warehouse_create\(\)](#), [db_sql_warehouse_delete\(\)](#), [db_sql_warehouse_edit\(\)](#), [db_sql_warehouse_get\(\)](#), [db_sql_warehouse_list\(\)](#), [db_sql_warehouse_start\(\)](#), [get_and_start_warehouse\(\)](#)

db_token	<i>Fetch Databricks Token</i>
----------	-------------------------------

Description

The function will check for a token in the DATABRICKS_HOST environment variable. .databrickscfg will be searched if db_profile and use_databrickscfg are set or if Posit Workbench managed OAuth credentials are detected. If none of the above are found then will default to using OAuth U2M flow.
Refer to [api authentication docs](#)

Usage

```
db_token(profile = default_config_profile())
```

Arguments

profile Profile to use when fetching from environment variable (e.g. `.Renviron`) or `.databricksfcg` file

Details

The behaviour is subject to change depending if `db_profile` and `use_databricksfcg` options are set.

- `use_databricksfcg`: Boolean (default: `FALSE`), determines if credentials are fetched from profile of `.databricksfcg` or `.Renviron`
- `db_profile`: String (default: `NULL`), determines profile used. `.databricksfcg` will automatically be used when Posit Workbench managed OAuth credentials are detected.

See vignette on authentication for more details.

Value

databricks token

See Also

Other Databricks Authentication Helpers: `db_host()`, `db_read_netrc()`, `db_wsid()`

db_uc_catalogs_get	<i>Get Catalog (Unity Catalog)</i>
--------------------	------------------------------------

Description

Get Catalog (Unity Catalog)

Usage

```
db_uc_catalogs_get(
  catalog,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

catalog The name of the catalog.

host Databricks workspace URL, defaults to calling `db_host()`.

token Databricks workspace token, defaults to calling `db_token()`.

perform_request If `TRUE` (default) the request is performed, if `FALSE` the http2 request is returned *without* being performed.

Value

List

See Also

Other Unity Catalog Management: [db_uc_catalogs_list\(\)](#), [db_uc_schemas_get\(\)](#), [db_uc_schemas_list\(\)](#)

db_uc_catalogs_list	<i>List Catalogs (Unity Catalog)</i>
---------------------	--------------------------------------

Description

List Catalogs (Unity Catalog)

Usage

```
db_uc_catalogs_list(  
    max_results = 1000,  
    include_browse = TRUE,  
    page_token = NULL,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

max_results	Maximum number of catalogs to return (default: 1000).
include_browse	Whether to include catalogs in the response for which the principal can only access selective metadata for.
page_token	Opaque token used to get the next page of results. Optional.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Management: [db_uc_catalogs_get\(\)](#), [db_uc_schemas_get\(\)](#), [db_uc_schemas_list\(\)](#)

db_uc_schemas_get	<i>Get Schema (Unity Catalog)</i>
-------------------	-----------------------------------

Description

Get Schema (Unity Catalog)

Usage

```
db_uc_schemas_get(  
  catalog,  
  schema,  
  include_browse = TRUE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog for schema of interest.
schema	Schema of interest.
include_browse	Whether to include catalogs in the response for which the principal can only access selective metadata for.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Management: [db_uc_catalogs_get\(\)](#), [db_uc_catalogs_list\(\)](#), [db_uc_schemas_list\(\)](#)

db_uc_schemas_list	<i>List Schemas (Unity Catalog)</i>
--------------------	-------------------------------------

Description

List Schemas (Unity Catalog)

Usage

```
db_uc_schemas_list(  
  catalog,  
  max_results = 1000,  
  page_token = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- catalog Parent catalog for schemas of interest.
- max_results Maximum number of schemas to return (default: 1000).
- page_token Opaque token used to get the next page of results. Optional.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

List

See Also

Other Unity Catalog Management: [db_uc_catalogs_get\(\)](#), [db_uc_catalogs_list\(\)](#), [db_uc_schemas_get\(\)](#)

db_uc_tables_delete	<i>Delete Table (Unity Catalog)</i>
---------------------	-------------------------------------

Description

Delete Table (Unity Catalog)

Usage

```
db_uc_tables_delete(  
  catalog,  
  schema,  
  table,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog of table.
schema	Parent schema of table.
table	Table name.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

Boolean

See Also

Other Unity Catalog Table Management: [db_uc_tables_exists\(\)](#), [db_uc_tables_get\(\)](#), [db_uc_tables_list\(\)](#), [db_uc_tables_summaries\(\)](#)

db_uc_tables_exists	<i>Check Table Exists (Unity Catalog)</i>
---------------------	---

Description

Check Table Exists (Unity Catalog)

Usage

```
db_uc_tables_exists(  
  catalog,  
  schema,  
  table,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog of table.
schema	Parent schema of table.
table	Table name.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List with fields table_exists and supports_foreign_metadata_update

See Also

Other Unity Catalog Table Management: [db_uc_tables_delete\(\)](#), [db_uc_tables_get\(\)](#), [db_uc_tables_list\(\)](#), [db_uc_tables_summaries\(\)](#)

db_uc_tables_get	<i>Get Table (Unity Catalog)</i>
------------------	----------------------------------

Description

Get Table (Unity Catalog)

Usage

```
db_uc_tables_get(  
  catalog,  
  schema,  
  table,  
  omit_columns = TRUE,  
  omit_properties = TRUE,  
  omit_username = TRUE,  
  include_browse = TRUE,  
  include_delta_metadata = TRUE,  
  include_manifest_capabilities = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog of table.
schema	Parent schema of table.
table	Table name.
omit_columns	Whether to omit the columns of the table from the response or not.
omit_properties	Whether to omit the properties of the table from the response or not.
omit_username	Whether to omit the username of the table (e.g. owner, updated_by, created_by) from the response or not.
include_browse	Whether to include tables in the response for which the principal can only access selective metadata for.
include_delta_metadata	Whether delta metadata should be included in the response.
include_manifest_capabilities	Whether to include a manifest containing capabilities the table has.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Table Management: [db_uc_tables_delete\(\)](#), [db_uc_tables_exists\(\)](#), [db_uc_tables_list\(\)](#), [db_uc_tables_summaries\(\)](#)

db_uc_tables_list	<i>List Tables (Unity Catalog)</i>
-------------------	------------------------------------

Description

List Tables (Unity Catalog)

Usage

```
db_uc_tables_list(  
  catalog,  
  schema,  
  max_results = 50,  
  omit_columns = TRUE,  
  omit_properties = TRUE,  
  omit_username = TRUE,  
  include_browse = TRUE,  
  include_delta_metadata = FALSE,  
  include_manifest_capabilities = FALSE,  
  page_token = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Name of parent catalog for tables of interest.
schema	Parent schema of tables.
max_results	Maximum number of tables to return (default: 50, max: 50).
omit_columns	Whether to omit the columns of the table from the response or not.
omit_properties	Whether to omit the properties of the table from the response or not.
omit_username	Whether to omit the username of the table (e.g. owner, updated_by, created_by) from the response or not.
include_browse	Whether to include tables in the response for which the principal can only access selective metadata for.

include_delta_metadata	Whether delta metadata should be included in the response.
include_manifest_capabilities	Whether to include a manifest containing capabilities the table has.
page_token	Opaque token used to get the next page of results. Optional.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Table Management: [db_uc_tables_delete\(\)](#), [db_uc_tables_exists\(\)](#), [db_uc_tables_get\(\)](#), [db_uc_tables_summaries\(\)](#)

db_uc_tables_summaries

List Table Summaries (Unity Catalog)

Description

List Table Summaries (Unity Catalog)

Usage

```
db_uc_tables_summaries(
  catalog,
  schema_name_pattern = NULL,
  table_name_pattern = NULL,
  max_results = 10000,
  include_manifest_capabilities = FALSE,
  page_token = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

catalog	Name of parent catalog for tables of interest.
schema_name_pattern	A sql LIKE pattern (% and _) for schema names. All schemas will be returned if not set or empty.
table_name_pattern	A sql LIKE pattern (% and _) for table names. All tables will be returned if not set or empty.
max_results	Maximum number of summaries for tables to return (default: 10000, max: 10000). If not set, the page length is set to a server configured value.
include_manifest_capabilities	Whether to include a manifest containing capabilities the table has.
page_token	Opaque token used to get the next page of results. Optional.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Table Management: [db_uc_tables_delete\(\)](#), [db_uc_tables_exists\(\)](#), [db_uc_tables_get\(\)](#), [db_uc_tables_list\(\)](#)

db_uc_volumes_create	<i>Update Volume (Unity Catalog)</i>
----------------------	--------------------------------------

Description

Update Volume (Unity Catalog)

Usage

```
db_uc_volumes_create(  
  catalog,  
  schema,  
  volume,  
  volume_type = c("MANAGED", "EXTERNAL"),  
  storage_location = NULL,  
  comment = NULL,  
  host = db_host(),
```

```
token = db_token(),
perform_request = TRUE
)
```

Arguments

catalog	Parent catalog of volume
schema	Parent schema of volume
volume	Volume name.
volume_type	Either 'MANAGED' or 'EXTERNAL'.
storage_location	The storage location on the cloud, only specified when volume_type is 'EXTERNAL'.
comment	The comment attached to the volume.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Volume Management: [db_uc_volumes_delete\(\)](#), [db_uc_volumes_get\(\)](#), [db_uc_volumes_list\(\)](#), [db_uc_volumes_update\(\)](#)

db_uc_volumes_delete	<i>Delete Volume (Unity Catalog)</i>
----------------------	--------------------------------------

Description

Delete Volume (Unity Catalog)

Usage

```
db_uc_volumes_delete(
  catalog,
  schema,
  volume,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

catalog	Parent catalog of volume
schema	Parent schema of volume
volume	Volume name.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

Boolean

See Also

Other Unity Catalog Volume Management: [db_uc_volumes_create\(\)](#), [db_uc_volumes_get\(\)](#), [db_uc_volumes_list\(\)](#), [db_uc_volumes_update\(\)](#)

db_uc_volumes_get	<i>Get Volume (Unity Catalog)</i>
-------------------	-----------------------------------

Description

Get Volume (Unity Catalog)

Usage

```
db_uc_volumes_get(  
  catalog,  
  schema,  
  volume,  
  include_browse = TRUE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog of volume
schema	Parent schema of volume
volume	Volume name.
include_browse	Whether to include volumes in the response for which the principal can only access selective metadata for.

host Databricks workspace URL, defaults to calling `db_host()`.
token Databricks workspace token, defaults to calling `db_token()`.
perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

List

See Also

Other Unity Catalog Volume Management: `db_uc_volumes_create()`, `db_uc_volumes_delete()`, `db_uc_volumes_list()`, `db_uc_volumes_update()`

db_uc_volumes_list	<i>List Volumes (Unity Catalog)</i>
--------------------	-------------------------------------

Description

List Volumes (Unity Catalog)

Usage

```
db_uc_volumes_list(  
  catalog,  
  schema,  
  max_results = 10000,  
  include_browse = TRUE,  
  page_token = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog Parent catalog of volume
schema Parent schema of volume
max_results Maximum number of volumes to return (default: 10000).
include_browse Whether to include volumes in the response for which the principal can only access selective metadata for.
page_token Opaque token used to get the next page of results. Optional.
host Databricks workspace URL, defaults to calling `db_host()`.
token Databricks workspace token, defaults to calling `db_token()`.
perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Value

List

See Also

Other Unity Catalog Volume Management: [db_uc_volumes_create\(\)](#), [db_uc_volumes_delete\(\)](#), [db_uc_volumes_get\(\)](#), [db_uc_volumes_update\(\)](#)

db_uc_volumes_update	<i>Update Volume (Unity Catalog)</i>
----------------------	--------------------------------------

Description

Update Volume (Unity Catalog)

Usage

```
db_uc_volumes_update(  
  catalog,  
  schema,  
  volume,  
  owner = NULL,  
  comment = NULL,  
  new_name = NULL,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

catalog	Parent catalog of volume
schema	Parent schema of volume
volume	Volume name.
owner	The identifier of the user who owns the volume (Optional).
comment	The comment attached to the volume (Optional).
new_name	New name for the volume (Optional).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Value

List

See Also

Other Unity Catalog Volume Management: [db_uc_volumes_create\(\)](#), [db_uc_volumes_delete\(\)](#), [db_uc_volumes_get\(\)](#), [db_uc_volumes_list\(\)](#)

db_volume_delete	<i>Volume FileSystem Delete</i>
------------------	---------------------------------

Description

Volume FileSystem Delete

Usage

```
db_volume_delete(  
  path,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- path Absolute path of the file in the Files API, omitting the initial slash.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

See Also

Other Volumes FileSystem API: [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_dir_create	<i>Volume FileSystem Create Directory</i>
----------------------	---

Description

Volume FileSystem Create Directory

Usage

```
db_volume_dir_create(  
    path,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_dir_delete	<i>Volume FileSystem Delete Directory</i>
----------------------	---

Description

Volume FileSystem Delete Directory

Usage

```
db_volume_dir_delete(
  path,
  recursive = FALSE,
  verbose = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
recursive	If TRUE, recursively delete directory contents (default: FALSE)
verbose	If TRUE, announce each file/directory deletion (default: FALSE)
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_dir_exists *Volume FileSystem Check Directory Exists*

Description

Volume FileSystem Check Directory Exists

Usage

```
db_volume_dir_exists(
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_file_exists *Volume FileSystem File Status*

Description

Volume FileSystem File Status

Usage

```
db_volume_file_exists(
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_list	<i>Volume FileSystem List Directory Contents</i>
----------------	--

Description

Volume FileSystem List Directory Contents

Usage

```
db_volume_list(  
  path,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- path Absolute path of the file in the Files API, omitting the initial slash.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_read	<i>Volume FileSystem Read</i>
----------------	-------------------------------

Description

Return the contents of a file within a volume (up to 5GiB).

Usage

```

db_volume_read(
  path,
  destination,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE,
  progress = TRUE
)

```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
destination	Path to write downloaded file to.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.
progress	If TRUE, show progress bar for file operations (default: TRUE for uploads/downloads, FALSE for other operations)

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_upload_dir\(\)](#), [db_volume_write\(\)](#)

db_volume_upload_dir *Upload Directory to Volume in Parallel*

Description

Upload all files from a local directory to a volume directory using parallel requests.

Usage

```

db_volume_upload_dir(
  local_dir,
  volume_dir,
  overwrite = TRUE,
  preserve_structure = TRUE,
  host = db_host(),
  token = db_token()
)

```

Arguments

local_dir	Path to local directory containing files to upload
volume_dir	Volume directory path (must start with /Volumes/)
overwrite	Flag to overwrite existing files (default: TRUE)
preserve_structure	If TRUE, preserve subdirectory structure (default: TRUE)
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

Value

TRUE if all uploads successful

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_write\(\)](#)

db_volume_write	<i>Volume FileSystem Write</i>
-----------------	--------------------------------

Description

Upload a file to volume filesystem.

Usage

```
db_volume_write(  
  path,  
  file = NULL,  
  overwrite = FALSE,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE,  
  progress = TRUE  
)
```

Arguments

path	Absolute path of the file in the Files API, omitting the initial slash.
file	Path to a file on local system, takes precedent over path.
overwrite	Flag (Default: FALSE) that specifies whether to overwrite existing files.
host	Databricks workspace URL, defaults to calling db_host() .

token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.
progress	If TRUE, show progress bar for file operations (default: TRUE for uploads/downloads, FALSE for other operations)

Details

Uploads a file of up to 5 GiB.

See Also

Other Volumes FileSystem API: [db_volume_delete\(\)](#), [db_volume_dir_create\(\)](#), [db_volume_dir_delete\(\)](#), [db_volume_dir_exists\(\)](#), [db_volume_file_exists\(\)](#), [db_volume_list\(\)](#), [db_volume_read\(\)](#), [db_volume_upload_dir\(\)](#)

db_vs_endpoints_create

Create a Vector Search Endpoint

Description

Create a Vector Search Endpoint

Usage

```
db_vs_endpoints_create(
  name,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

name	Name of vector search endpoint
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

This function can take a few moments to run.

See Also

Other Vector Search API: [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_endpoints_delete

Delete a Vector Search Endpoint

Description

Delete a Vector Search Endpoint

Usage

```
db_vs_endpoints_delete(
    endpoint,
    host = db_host(),
    token = db_token(),
    perform_request = TRUE
)
```

Arguments

endpoint	Name of vector search endpoint
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_endpoints_get	<i>Get a Vector Search Endpoint</i>
---------------------	-------------------------------------

Description

Get a Vector Search Endpoint

Usage

```
db_vs_endpoints_get(  
  endpoint,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

endpoint	Name of vector search endpoint
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_endpoints_list	<i>List Vector Search Endpoints</i>
----------------------	-------------------------------------

Description

List Vector Search Endpoints

Usage

```
db_vs_endpoints_list(
  page_token = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

page_token	Token for pagination
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_create *Create a Vector Search Index*

Description

Create a Vector Search Index

Usage

```
db_vs_indexes_create(
  name,
  endpoint,
  primary_key,
  spec,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

name	Name of vector search index
endpoint	Name of vector search endpoint
primary_key	Vector search primary key column name
spec	Either delta_sync_index_spec() or direct_access_index_spec() .
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_delete *Delete a Vector Search Index*

Description

Delete a Vector Search Index

Usage

```
db_vs_indexes_delete(
  index,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

index	Name of vector search index
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_delete_data
<i>Delete Data from a Vector Search Index</i>

Description

Delete Data from a Vector Search Index

Usage

```
db_vs_indexes_delete_data(  
  index,  
  primary_keys,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

index	Name of vector search index
primary_keys	primary keys to be deleted from index
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_get	<i>Get a Vector Search Index</i>
-------------------	----------------------------------

Description

Get a Vector Search Index

Usage

```
db_vs_indexes_get(  
  index,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

index	Name of vector search index
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_list	<i>List Vector Search Indexes</i>
--------------------	-----------------------------------

Description

List Vector Search Indexes

Usage

```
db_vs_indexes_list(
  endpoint,
  page_token = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

endpoint	Name of vector search endpoint
page_token	page_token returned from prior query
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_query	<i>Query a Vector Search Index</i>
---------------------	------------------------------------

Description

Query a Vector Search Index

Usage

```
db_vs_indexes_query(
  index,
  columns,
  filters_json,
  query_vector = NULL,
  query_text = NULL,
  score_threshold = 0,
  query_type = c("ANN", "HYBRID"),
  num_results = 10,
  host = db_host(),
```

```

    token = db_token(),
    perform_request = TRUE
)

```

Arguments

index	Name of vector search index
columns	Column names to include in response
filters_json	JSON string representing query filters, see details.
query_vector	Numeric vector. Required for direct vector access index and delta sync index using self managed vectors.
query_text	Required for delta sync index using model endpoint.
score_threshold	Numeric score threshold for the approximate nearest neighbour (ANN) search. Defaults to 0.0.
query_type	One of ANN (default) or HYBRID
num_results	Number of returns to return (default: 10).
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

You cannot specify both `query_vector` and `query_text` at the same time.

`filter_jsons` examples:

- `'{"id <": 5}'`: Filter for id less than 5
- `'{"id >": 5}'`: Filter for id greater than 5
- `'{"id <=": 5}'`: Filter for id less than equal to 5
- `'{"id >=": 5}'`: Filter for id greater than equal to 5
- `'{"id": 5}'`: Filter for id equal to 5
- `'{"id": 5, "age >=": 18}'`: Filter for id equal to 5 and age greater than equal to 18

`filter_jsons` will convert attempt to use `jsonlite::toJSON` on any non character vectors.

Refer to docs for [Vector Search](#).

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

Examples

```
## Not run:
db_vs_indexes_sync(
  index = "myindex",
  columns = c("id", "text"),
  query_vector = c(1, 2, 3)
)

## End(Not run)
```

db_vs_indexes_query_next_page

Query Vector Search Next Page

Description

Query Vector Search Next Page

Usage

```
db_vs_indexes_query_next_page(
  index,
  endpoint,
  page_token = NULL,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

index	Name of vector search index
endpoint	Name of vector search endpoint
page_token	page_token returned from prior query
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_scan	<i>Scan a Vector Search Index</i>
--------------------	-----------------------------------

Description

Scan a Vector Search Index

Usage

```
db_vs_indexes_scan(  
  endpoint,  
  index,  
  last_primary_key,  
  num_results = 10,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

endpoint	Name of vector search endpoint to scan
index	Name of vector search index to scan
last_primary_key	Primary key of the last entry returned in previous scan
num_results	Number of returns to return (default: 10)
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Scan the specified vector index and return the first num_results entries after the exclusive primary_key.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_sync	<i>Synchronize a Vector Search Index</i>
--------------------	--

Description

Synchronize a Vector Search Index

Usage

```
db_vs_indexes_sync(  
  index,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

index	Name of vector search index
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Triggers a synchronization process for a specified vector index. The index must be a 'Delta Sync' index.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_vs_indexes_upsert_data	<i>Upsert Data into a Vector Search Index</i>
---------------------------	---

Description

Upsert Data into a Vector Search Index

Usage

```
db_vs_indexes_upsert_data(  
  index,  
  df,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

index	Name of vector search index
df	data.frame containing data to upsert
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

db_workspace_delete	<i>Delete Object/Directory (Workspaces)</i>
---------------------	---

Description

Delete Object/Directory (Workspaces)

Usage

```
db_workspace_delete(
  path,
  recursive = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the notebook or directory.
recursive	Flag that specifies whether to delete the object recursively. False by default.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Delete an object or a directory (and optionally recursively deletes all objects in the directory). If path does not exist, this call returns an error RESOURCE_DOES_NOT_EXIST. If path is a non-empty directory and recursive is set to false, this call returns an error DIRECTORY_NOT_EMPTY.

Object deletion cannot be undone and deleting a directory recursively is not atomic.

See Also

Other Workspace API: [db_workspace_export\(\)](#), [db_workspace_get_status\(\)](#), [db_workspace_import\(\)](#), [db_workspace_list\(\)](#), [db_workspace_mkdirs\(\)](#)

db_workspace_export	<i>Export Notebook or Directory (Workspaces)</i>
---------------------	--

Description

Export Notebook or Directory (Workspaces)

Usage

```
db_workspace_export(
  path,
  format = c("AUTO", "SOURCE", "HTML", "JUPYTER", "DBC", "R_MARKDOWN"),
  host = db_host(),
  token = db_token(),
  output_path = NULL,
```

```
    direct_download = FALSE,  
    perform_request = TRUE  
)
```

Arguments

path	Absolute path of the notebook or directory.
format	One of AUTO, SOURCE, HTML, JUPYTER, DBC, R_MARKDOWN. Default is SOURCE.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
output_path	Path to export file to, ensure to include correct suffix.
direct_download	Boolean (default: FALSE), if TRUE download file contents directly to file. Must also specify output_path.
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Export a notebook or contents of an entire directory. If path does not exist, this call returns an error RESOURCE_DOES_NOT_EXIST.

You can export a directory only in DBC format. If the exported data exceeds the size limit, this call returns an error MAX_NOTEBOOK_SIZE_EXCEEDED. This API does not support exporting a library.

At this time we do not support the direct_download parameter and returns a base64 encoded string.

[See More.](#)

Value

base64 encoded string

See Also

Other Workspace API: [db_workspace_delete\(\)](#), [db_workspace_get_status\(\)](#), [db_workspace_import\(\)](#), [db_workspace_list\(\)](#), [db_workspace_mkdirs\(\)](#)

`db_workspace_get_status`*Get Object Status (Workspaces)*

Description

Gets the status of an object or a directory.

Usage

```
db_workspace_get_status(  
    path,  
    host = db_host(),  
    token = db_token(),  
    perform_request = TRUE  
)
```

Arguments

<code>path</code>	Absolute path of the notebook or directory.
<code>host</code>	Databricks workspace URL, defaults to calling db_host() .
<code>token</code>	Databricks workspace token, defaults to calling db_token() .
<code>perform_request</code>	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

If path does not exist, this call returns an error `RESOURCE_DOES_NOT_EXIST`.

See Also

Other Workspace API: [db_workspace_delete\(\)](#), [db_workspace_export\(\)](#), [db_workspace_import\(\)](#), [db_workspace_list\(\)](#), [db_workspace_mkdirs\(\)](#)

`db_workspace_import`*Import Notebook/Directory (Workspaces)*

Description

Import a notebook or the contents of an entire directory.

Usage

```
db_workspace_import(
  path,
  file = NULL,
  content = NULL,
  format = c("AUTO", "SOURCE", "HTML", "JUPYTER", "DBC", "R_MARKDOWN"),
  language = NULL,
  overwrite = FALSE,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the notebook or directory.
file	Path of local file to upload. See <code>formats</code> parameter.
content	Content to upload, this will be base64-encoded and has a limit of 10MB.
format	One of AUTO, SOURCE, HTML, JUPYTER, DBC, R_MARKDOWN. Default is SOURCE.
language	One of R, PYTHON, SCALA, SQL. Required when format is SOURCE otherwise ignored.
overwrite	Flag that specifies whether to overwrite existing object. FALSE by default. For DBC overwrite is not supported since it may contain a directory.
host	Databricks workspace URL, defaults to calling <code>db_host()</code> .
token	Databricks workspace token, defaults to calling <code>db_token()</code> .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

`file` and `content` are mutually exclusive. If both are specified content will be ignored.

If path already exists and `overwrite` is set to FALSE, this call returns an error `RESOURCE_ALREADY_EXISTS`. You can use only DBC format to import a directory.

See Also

Other Workspace API: `db_workspace_delete()`, `db_workspace_export()`, `db_workspace_get_status()`, `db_workspace_list()`, `db_workspace_mkdirs()`

db_workspace_list	<i>List Directory Contents (Workspaces)</i>
-------------------	---

Description

List Directory Contents (Workspaces)

Usage

```
db_workspace_list(  
  path,  
  host = db_host(),  
  token = db_token(),  
  perform_request = TRUE  
)
```

Arguments

- path Absolute path of the notebook or directory.
- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- perform_request If TRUE (default) the request is performed, if FALSE the http2 request is returned *without* being performed.

Details

List the contents of a directory, or the object if it is not a directory. If the input path does not exist, this call returns an error RESOURCE_DOES_NOT_EXIST.

See Also

Other Workspace API: [db_workspace_delete\(\)](#), [db_workspace_export\(\)](#), [db_workspace_get_status\(\)](#), [db_workspace_import\(\)](#), [db_workspace_mkdirs\(\)](#)

db_workspace_mkdirs	<i>Make a Directory (Workspaces)</i>
---------------------	--------------------------------------

Description

Make a Directory (Workspaces)

Usage

```
db_workspace_mkdirs(
  path,
  host = db_host(),
  token = db_token(),
  perform_request = TRUE
)
```

Arguments

path	Absolute path of the directory.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
perform_request	If TRUE (default) the request is performed, if FALSE the http2 request is returned <i>without</i> being performed.

Details

Create the given directory and necessary parent directories if they do not exist. If there exists an object (not a directory) at any prefix of the input path, this call returns an error `RESOURCE_ALREADY_EXISTS`. If this operation fails it may have succeeded in creating some of the necessary parent directories.

See Also

Other Workspace API: [db_workspace_delete\(\)](#), [db_workspace_export\(\)](#), [db_workspace_get_status\(\)](#), [db_workspace_import\(\)](#), [db_workspace_list\(\)](#)

db_wsid	<i>Fetch Databricks Workspace ID</i>
---------	--------------------------------------

Description

Workspace ID, optionally specified to make connections pane more powerful. Specified as an environment variable `DATABRICKS_WSID`. `.databrickscfg` will be searched if `db_profile` and `use_databrickscfg` are set or if Posit Workbench managed OAuth credentials are detected.

Refer to [api authentication docs](#)

Usage

```
db_wsid(profile = default_config_profile())
```

Arguments

profile	Profile to use when fetching from environment variable (e.g. <code>.Renviron</code>) or <code>.databrickscfg</code> file
---------	---

Details

The behaviour is subject to change depending if `db_profile` and `use_databrickscfg` options are set.

- `use_databrickscfg`: Boolean (default: FALSE), determines if credentials are fetched from profile of `.databrickscfg` or `.Renviron`
- `db_profile`: String (default: NULL), determines profile used. `.databrickscfg` will automatically be used when Posit Workbench managed OAuth credentials are detected.

See vignette on authentication for more details.

Value

databricks workspace ID

See Also

Other Databricks Authentication Helpers: [db_host\(\)](#), [db_read_netrc\(\)](#), [db_token\(\)](#)

`delta_sync_index_spec` *Delta Sync Vector Search Index Specification*

Description

Delta Sync Vector Search Index Specification

Usage

```
delta_sync_index_spec(
  source_table,
  embedding_writeback_table = NULL,
  embedding_source_columns = NULL,
  embedding_vector_columns = NULL,
  pipeline_type = c("TRIGGERED", "CONTINUOUS")
)
```

Arguments

`source_table` The name of the source table.

`embedding_writeback_table`
 Name of table to sync index contents and computed embeddings back to delta table, see details.

`embedding_source_columns`
 The columns that contain the embedding source, must be one or list of [embedding_source_column\(\)](#)

`embedding_vector_columns`
 The columns that contain the embedding, must be one or list of [embedding_vector_column\(\)](#)

`pipeline_type` Pipeline execution mode, see details.

Details

pipeline_type is either:

- "TRIGGERED": If the pipeline uses the triggered execution mode, the system stops processing after successfully refreshing the source table in the pipeline once, ensuring the table is updated based on the data available when the update started.
- "CONTINUOUS": If the pipeline uses continuous execution, the pipeline processes new data as it arrives in the source table to keep vector index fresh.

The only supported naming convention for embedding_writeback_table is "<index_name>_writeback_table".

See Also

[db_vs_indexes_create\(\)](#)

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

direct_access_index_spec

Delta Sync Vector Search Index Specification

Description

Delta Sync Vector Search Index Specification

Usage

```
direct_access_index_spec(
  embedding_source_columns = NULL,
  embedding_vector_columns = NULL,
  schema
)
```

Arguments

embedding_source_columns	The columns that contain the embedding source, must be one or list of embedding_source_column()
embedding_vector_columns	The columns that contain the embedding, must be one or list of embedding_vector_column() vectors.
schema	Named list, names are column names, values are types. See details.

Details

The supported types are:

- "integer"
- "long"
- "float"
- "double"
- "boolean"
- "string"
- "date"
- "timestamp"
- "array<float>": supported for vector columns
- "array<double>": supported for vector columns

See Also

[db_vs_indexes_create\(\)](#)

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [embedding_source_column\(\)](#), [embedding_vector_column\(\)](#)

<code>docker_image</code>	<i>Docker Image</i>
---------------------------	---------------------

Description

Docker image connection information.

Usage

```
docker_image(url, username, password)
```

Arguments

- | | |
|-----------------------|--------------------------------------|
| <code>url</code> | URL for the Docker image. |
| <code>username</code> | User name for the Docker repository. |
| <code>password</code> | Password for the Docker repository. |

Details

Uses basic authentication, **strongly** recommended that credentials are not stored in any scripts and environment variables should be used.

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)

email_notifications	<i>Email Notifications</i>
---------------------	----------------------------

Description

Email Notifications

Usage

```
email_notifications(
    on_start = NULL,
    on_success = NULL,
    on_failure = NULL,
    no_alert_for_skipped_runs = TRUE
)
```

Arguments

on_start	List of email addresses to be notified when a run begins. If not specified on job creation, reset, or update, the list is empty, and notifications are not sent.
on_success	List of email addresses to be notified when a run successfully completes. A run is considered to have completed successfully if it ends with a <code>TERMINATED</code> <code>life_cycle_state</code> and a <code>SUCCESSFUL</code> <code>result_state</code> . If not specified on job creation, reset, or update, the list is empty, and notifications are not sent.
on_failure	List of email addresses to be notified when a run unsuccessfully completes. A run is considered to have completed unsuccessfully if it ends with an <code>INTERNAL_ERROR</code> <code>life_cycle_state</code> or a <code>SKIPPED</code> , <code>FAILED</code> , or <code>TIMED_OUT</code> <code>result_state</code> . If this is not specified on job creation, reset, or update the list is empty, and notifications are not sent.
no_alert_for_skipped_runs	If <code>TRUE</code> (default), do not send email to recipients specified in <code>on_failure</code> if the run is skipped.

See Also

[job_task\(\)](#)

Other Task Objects: [condition_task\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

embedding_source_column
<i>Embedding Source Column</i>

Description

Embedding Source Column

Usage

embedding_source_column(name, model_endpoint_name)

Arguments

- | | |
|---------------------|--------------------------------------|
| name | Name of the column |
| model_endpoint_name | Name of the embedding model endpoint |

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_vector_column\(\)](#)

embedding_vector_column
<i>Embedding Vector Column</i>

Description

Embedding Vector Column

Usage

embedding_vector_column(name, dimension)

Arguments

- | | |
|-----------|-----------------------------------|
| name | Name of the column |
| dimension | dimension of the embedding vector |

See Also

Other Vector Search API: [db_vs_endpoints_create\(\)](#), [db_vs_endpoints_delete\(\)](#), [db_vs_endpoints_get\(\)](#), [db_vs_endpoints_list\(\)](#), [db_vs_indexes_create\(\)](#), [db_vs_indexes_delete\(\)](#), [db_vs_indexes_delete_data\(\)](#), [db_vs_indexes_get\(\)](#), [db_vs_indexes_list\(\)](#), [db_vs_indexes_query\(\)](#), [db_vs_indexes_query_next_page\(\)](#), [db_vs_indexes_scan\(\)](#), [db_vs_indexes_sync\(\)](#), [db_vs_indexes_upsert_data\(\)](#), [delta_sync_index_spec\(\)](#), [direct_access_index_spec\(\)](#), [embedding_source_column\(\)](#)

file_storage_info	<i>File Storage Information</i>
-------------------	---------------------------------

Description

File Storage Information

Usage

`file_storage_info(destination)`

Arguments

`destination` File destination. Example: `file:/my/file.sh`.

Details

The file storage type is only available for clusters set up using Databricks Container Services.

See Also

[init_script_info\(\)](#)
Other Init Script Info Objects: [dbfs_storage_info\(\)](#), [s3_storage_info\(\)](#)

for_each_task	<i>For Each Task</i>
---------------	----------------------

Description

For Each Task

Usage

`for_each_task(inputs, task, concurrency = 1)`

Arguments

inputs	Array for task to iterate on. This can be a JSON string or a reference to an array parameter.
task	Must be a job_task() .
concurrency	Maximum allowed number of concurrent runs of the task.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

<code>gcp_attributes</code>	<i>GCP Attributes</i>
-----------------------------	-----------------------

Description

GCP Attributes

Usage

```
gcp_attributes(use_preemptible_executors = TRUE, google_service_account = NULL)
```

Arguments

use_preemptible_executors	Boolean (Default: TRUE). If TRUE Uses preemptible executors
google_service_account	Google service account email address that the cluster uses to authenticate with Google Identity. This field is used for authentication with the GCS and BigQuery data sources.

Details

For use with GCS and BigQuery, your Google service account that you use to access the data source must be in the same project as the SA that you specified when setting up your Databricks account.

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)
Other Cloud Attributes: [aws_attributes\(\)](#), [azure_attributes\(\)](#)

get_and_start_cluster *Get and Start Cluster*

Description

Get and Start Cluster

Usage

```
get_and_start_cluster(  
    cluster_id,  
    polling_interval = 5,  
    host = db_host(),  
    token = db_token(),  
    silent = FALSE  
)
```

Arguments

cluster_id	Canonical identifier for the cluster.
polling_interval	Number of seconds to wait between status checks
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .
silent	Boolean (default: FALSE), will emit cluster state progress if TRUE.

Details

Get information regarding a Databricks cluster. If the cluster is inactive it will be started and wait until the cluster is active.

Value

[db_cluster_get\(\)](#)

See Also

[db_cluster_get\(\)](#) and [db_cluster_start\(\)](#).

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_latest_dbr\(\)](#)

Other Cluster Helpers: [get_latest_dbr\(\)](#)

`get_and_start_warehouse`*Get and Start Warehouse*

Description

Get and Start Warehouse

Usage

```
get_and_start_warehouse(  
    id,  
    polling_interval = 5,  
    host = db_host(),  
    token = db_token()  
)
```

Arguments

<code>id</code>	ID of the SQL warehouse.
<code>polling_interval</code>	Number of seconds to wait between status checks
<code>host</code>	Databricks workspace URL, defaults to calling <code>db_host()</code> .
<code>token</code>	Databricks workspace token, defaults to calling <code>db_token()</code> .

Details

Get information regarding a Databricks cluster. If the cluster is inactive it will be started and wait until the cluster is active.

Value

`db_sql_warehouse_get()`

See Also

`db_sql_warehouse_get()` and `db_sql_warehouse_start()`.

Other Warehouse API: `db_sql_global_warehouse_get()`, `db_sql_warehouse_create()`, `db_sql_warehouse_delete()`, `db_sql_warehouse_edit()`, `db_sql_warehouse_get()`, `db_sql_warehouse_list()`, `db_sql_warehouse_start()`, `db_sql_warehouse_stop()`

get_latest_dbr	<i>Get Latest Databricks Runtime (DBR)</i>
----------------	--

Description

Get Latest Databricks Runtime (DBR)

Usage

get_latest_dbr(lts, ml, gpu, photon, host = db_host(), token = db_token())

Arguments

lts	Boolean, if TRUE returns only LTS runtimes
ml	Boolean, if TRUE returns only ML runtimes
gpu	Boolean, if TRUE returns only ML GPU runtimes
photon	Boolean, if TRUE returns only photon runtimes
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

Details

There are runtime combinations that are not possible, such as GPU/ML and photon. This function does not permit invalid combinations.

Value

Named list

See Also

Other Clusters API: [db_cluster_create\(\)](#), [db_cluster_edit\(\)](#), [db_cluster_events\(\)](#), [db_cluster_get\(\)](#), [db_cluster_list\(\)](#), [db_cluster_list_node_types\(\)](#), [db_cluster_list_zones\(\)](#), [db_cluster_perm_delete\(\)](#), [db_cluster_pin\(\)](#), [db_cluster_resize\(\)](#), [db_cluster_restart\(\)](#), [db_cluster_runtime_versions\(\)](#), [db_cluster_start\(\)](#), [db_cluster_terminate\(\)](#), [db_cluster_unpin\(\)](#), [get_and_start_cluster\(\)](#)

Other Cluster Helpers: [get_and_start_cluster\(\)](#)

git_source	<i>Git Source for Job Notebook Tasks</i>
------------	--

Description

Git Source for Job Notebook Tasks

Usage

```
git_source(  
  git_url,  
  git_provider,  
  reference,  
  type = c("branch", "tag", "commit")  
)
```

Arguments

git_url	URL of the repository to be cloned by this job. The maximum length is 300 characters.
git_provider	Unique identifier of the service used to host the Git repository. Must be one of: github,bitbucketcloud,azuredevopsservices,githubenterprise,bitbucketserver,gitlab,gitlabenterpriseedition,awscodecommit.
reference	Branch, tag, or commit to be checked out and used by this job.
type	Type of reference being used, one of: branch, tag, commit.

init_script_info	<i>Init Script Info</i>
------------------	-------------------------

Description

Init Script Info

Usage

```
init_script_info(...)
```

Arguments

...	Accepts multiple instances s3_storage_info() , file_storage_info() , or dbfs_storage_info() .
-----	---

Details

[file_storage_info\(\)](#) is only available for clusters set up using Databricks Container Services. For instructions on using init scripts with Databricks Container Services, see [Use an init script](#).

See Also

[db_cluster_create\(\)](#), [db_cluster_edit\(\)](#)

in_databricks_nb	<i>Detect if running within Databricks Notebook</i>
------------------	---

Description

Detect if running within Databricks Notebook

Usage

```
in_databricks_nb()
```

Details

R sessions on Databricks can be detected via various environment variables and directories.

Value

Boolean

is.access_control_request	<i>Test if object is of class AccessControlRequest</i>
---------------------------	--

Description

Test if object is of class AccessControlRequest

Usage

```
is.access_control_request(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the AccessControlRequest class.

is.access_control_req_group

Test if object is of class AccessControlRequestForGroup

Description

Test if object is of class AccessControlRequestForGroup

Usage

is.access_control_req_group(x)

Arguments

x An object

Value

TRUE if the object inherits from the AccessControlRequestForGroup class.

is.access_control_req_user

Test if object is of class AccessControlRequestForUser

Description

Test if object is of class AccessControlRequestForUser

Usage

is.access_control_req_user(x)

Arguments

x An object

Value

TRUE if the object inherits from the AccessControlRequestForUser class.

is.aws_attributes	<i>Test if object is of class AwsAttributes</i>
-------------------	---

Description

Test if object is of class AwsAttributes

Usage

```
is.aws_attributes(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the AwsAttributes class.

is.azure_attributes	<i>Test if object is of class AzureAttributes</i>
---------------------	---

Description

Test if object is of class AzureAttributes

Usage

```
is.azure_attributes(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the AzureAttributes class.

<code>is.cluster_autoscale</code>	<i>Test if object is of class <code>AutoScale</code></i>
-----------------------------------	--

Description

Test if object is of class `AutoScale`

Usage

`is.cluster_autoscale(x)`

Arguments

x An object

Value

TRUE if the object inherits from the `AutoScale` class.

<code>is.cluster_log_conf</code>	<i>Test if object is of class <code>ClusterLogConf</code></i>
----------------------------------	---

Description

Test if object is of class `ClusterLogConf`

Usage

`is.cluster_log_conf(x)`

Arguments

x An object

Value

TRUE if the object inherits from the `ClusterLogConf` class.

is.condition_task	<i>Test if object is of class ConditionTask</i>
-------------------	---

Description

Test if object is of class ConditionTask

Usage

is.condition_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the ConditionTask class.

is.cron_schedule	<i>Test if object is of class CronSchedule</i>
------------------	--

Description

Test if object is of class CronSchedule

Usage

is.cron_schedule(x)

Arguments

x An object

Value

TRUE if the object inherits from the CronSchedule class.

is.dbfs_storage_info	Test if object is of class DbfsStorageInfo
----------------------	--

Description

Test if object is of class DbfsStorageInfo

Usage

is.dbfs_storage_info(x)

Arguments

x An object

Value

TRUE if the object inherits from the DbfsStorageInfo class.

is.delta_sync_index	Test if object is of class DeltaSyncIndex
---------------------	---

Description

Test if object is of class DeltaSyncIndex

Usage

is.delta_sync_index(x)

Arguments

x An object

Value

TRUE if the object inherits from the DeltaSyncIndex class.

`is.direct_access_index`*Test if object is of class DirectAccessIndex*

Description

Test if object is of class DirectAccessIndex

Usage

```
is.direct_access_index(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the DirectAccessIndex class.

`is.docker_image`*Test if object is of class DockerImage*

Description

Test if object is of class DockerImage

Usage

```
is.docker_image(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the DockerImage class.

<code>is.email_notifications</code>
<i>Test if object is of class JobEmailNotifications</i>

Description

Test if object is of class JobEmailNotifications

Usage

`is.email_notifications(x)`

Arguments

<code>x</code>	An object
----------------	-----------

Value

TRUE if the object inherits from the JobEmailNotifications class.

<code>is.embedding_source_column</code>
<i>Test if object is of class EmbeddingSourceColumn</i>

Description

Test if object is of class EmbeddingSourceColumn

Usage

`is.embedding_source_column(x)`

Arguments

<code>x</code>	An object
----------------	-----------

Value

TRUE if the object inherits from the EmbeddingSourceColumn class.

`is.embedding_vector_column`*Test if object is of class EmbeddingVectorColumn*

Description

Test if object is of class EmbeddingVectorColumn

Usage

```
is.embedding_vector_column(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the EmbeddingVectorColumn class.

`is.file_storage_info` *Test if object is of class FileStorageInfo*

Description

Test if object is of class FileStorageInfo

Usage

```
is.file_storage_info(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the FileStorageInfo class.

is.for_each_task	<i>Test if object is of class ForEachTask</i>
------------------	---

Description

Test if object is of class ForEachTask

Usage

is.for_each_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the ForEachTask class.

is.gcp_attributes	<i>Test if object is of class GcpAttributes</i>
-------------------	---

Description

Test if object is of class GcpAttributes

Usage

is.gcp_attributes(x)

Arguments

x An object

Value

TRUE if the object inherits from the GcpAttributes class.

is.git_source	<i>Test if object is of class GitSource</i>
---------------	---

Description

Test if object is of class GitSource

Usage

```
is.git_source(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the GitSource class.

is.init_script_info	<i>Test if object is of class InitScriptInfo</i>
---------------------	--

Description

Test if object is of class InitScriptInfo

Usage

```
is.init_script_info(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the InitScriptInfo class.

is.job_task	<i>Test if object is of class JobTaskSettings</i>
-------------	---

Description

Test if object is of class JobTaskSettings

Usage

is.job_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the JobTaskSettings class.

is.libraries	<i>Test if object is of class Libraries</i>
--------------	---

Description

Test if object is of class Libraries

Usage

is.libraries(x)

Arguments

x An object

Value

TRUE if the object inherits from the Libraries class.

is.library	<i>Test if object is of class Library</i>
------------	---

Description

Test if object is of class Library

Usage

```
is.library(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the Library class.

is.lib_cran	<i>Test if object is of class CranLibrary</i>
-------------	---

Description

Test if object is of class CranLibrary

Usage

```
is.lib_cran(x)
```

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the CranLibrary class.

<code>is.lib_egg</code>	<i>Test if object is of class EggLibrary</i>
-------------------------	--

Description

Test if object is of class EggLibrary

Usage

`is.lib_egg(x)`

Arguments

x An object

Value

TRUE if the object inherits from the EggLibrary class.

<code>is.lib_jar</code>	<i>Test if object is of class JarLibrary</i>
-------------------------	--

Description

Test if object is of class JarLibrary

Usage

`is.lib_jar(x)`

Arguments

x An object

Value

TRUE if the object inherits from the JarLibrary class.

is.lib_maven	<i>Test if object is of class MavenLibrary</i>
--------------	--

Description

Test if object is of class MavenLibrary

Usage

is.lib_maven(x)

Arguments

x An object

Value

TRUE if the object inherits from the MavenLibrary class.

is.lib_pypi	<i>Test if object is of class PyPiLibrary</i>
-------------	---

Description

Test if object is of class PyPiLibrary

Usage

is.lib_pypi(x)

Arguments

x An object

Value

TRUE if the object inherits from the PyPiLibrary class.

<code>is.lib_whl</code>	<i>Test if object is of class WhlLibrary</i>
-------------------------	--

Description

Test if object is of class WhlLibrary

Usage

`is.lib_whl(x)`

Arguments

`x` An object

Value

TRUE if the object inherits from the WhlLibrary class.

<code>is.new_cluster</code>	<i>Test if object is of class NewCluster</i>
-----------------------------	--

Description

Test if object is of class NewCluster

Usage

`is.new_cluster(x)`

Arguments

`x` An object

Value

TRUE if the object inherits from the NewCluster class.

is.notebook_task	<i>Test if object is of class NotebookTask</i>
------------------	--

Description

Test if object is of class NotebookTask

Usage

is.notebook_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the NotebookTask class.

is.pipeline_task	<i>Test if object is of class PipelineTask</i>
------------------	--

Description

Test if object is of class PipelineTask

Usage

is.pipeline_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the PipelineTask class.

is.python_wheel_task	<i>Test if object is of class PythonWheelTask</i>
----------------------	---

Description

Test if object is of class PythonWheelTask

Usage

is.python_wheel_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the PythonWheelTask class.

is.run_job_task	<i>Test if object is of class RunJobTask</i>
-----------------	--

Description

Test if object is of class RunJobTask

Usage

is.run_job_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the RunJobTask class.

is.s3_storage_info	<i>Test if object is of class S3StorageInfo</i>
--------------------	---

Description

Test if object is of class S3StorageInfo

Usage

is.s3_storage_info(x)

Arguments

x An object

Value

TRUE if the object inherits from the S3StorageInfo class.

is.spark_jar_task	<i>Test if object is of class SparkJarTask</i>
-------------------	--

Description

Test if object is of class SparkJarTask

Usage

is.spark_jar_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the SparkJarTask class.

is.spark_python_task	<i>Test if object is of class SparkPythonTask</i>
----------------------	---

Description

Test if object is of class SparkPythonTask

Usage

is.spark_python_task(x)

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the SparkPythonTask class.

is.spark_submit_task	<i>Test if object is of class SparkSubmitTask</i>
----------------------	---

Description

Test if object is of class SparkSubmitTask

Usage

is.spark_submit_task(x)

Arguments

x	An object
---	-----------

Value

TRUE if the object inherits from the SparkSubmitTask class.

is.sql_file_task	<i>Test if object is of class SqlFileTask</i>
------------------	---

Description

Test if object is of class SqlFileTask

Usage

is.sql_file_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the SqlFileTask class.

is.sql_query_task	<i>Test if object is of class SqlQueryTask</i>
-------------------	--

Description

Test if object is of class SqlQueryTask

Usage

is.sql_query_task(x)

Arguments

x An object

Value

TRUE if the object inherits from the SqlQueryTask class.

is.valid_task_type	<i>Test if object is of class JobTask</i>
--------------------	---

Description

Test if object is of class JobTask

Usage

is.valid_task_type(x)

Arguments

x An object

Value

TRUE if the object inherits from the JobTask class.

is.vector_search_index_spec	<i>Test if object is of class VectorSearchIndexSpec</i>
-----------------------------	---

Description

Test if object is of class VectorSearchIndexSpec

Usage

is.vector_search_index_spec(x)

Arguments

x An object

Value

TRUE if the object inherits from the VectorSearchIndexSpec class.

job_task

*Job Task***Description**

Job Task

Usage

```

job_task(
  task_key,
  description = NULL,
  depends_on = c(),
  existing_cluster_id = NULL,
  new_cluster = NULL,
  job_cluster_key = NULL,
  task,
  libraries = NULL,
  email_notifications = NULL,
  timeout_seconds = NULL,
  max_retries = 0,
  min_retry_interval_millis = 0,
  retry_on_timeout = FALSE,
  run_if = c("ALL_SUCCESS", "ALL_DONE", "NONE_FAILED", "AT_LEAST_ONE_SUCCESS",
    "ALL_FAILED", "AT_LEAST_ONE_FAILED")
)

```

Arguments

task_key	A unique name for the task. This field is used to refer to this task from other tasks. This field is required and must be unique within its parent job. On db_jobs_update() or db_jobs_reset() , this field is used to reference the tasks to be updated or reset. The maximum length is 100 characters.
description	An optional description for this task. The maximum length is 4096 bytes.
depends_on	Vector of task_key's specifying the dependency graph of the task. All task_key's specified in this field must complete successfully before executing this task. This field is required when a job consists of more than one task.
existing_cluster_id	ID of an existing cluster that is used for all runs of this task.
new_cluster	Instance of new_cluster() .
job_cluster_key	Task is executed reusing the cluster specified in db_jobs_create() with job_clusters parameter.
task	One of notebook_task() , spark_jar_task() , spark_python_task() , spark_submit_task() , pipeline_task() , python_wheel_task() .

libraries	Instance of libraries() .
email_notifications	Instance of email_notifications .
timeout_seconds	An optional timeout applied to each run of this job task. The default behavior is to have no timeout.
max_retries	An optional maximum number of times to retry an unsuccessful run. A run is considered to be unsuccessful if it completes with the FAILED result_state or INTERNAL_ERROR life_cycle_state. The value -1 means to retry indefinitely and the value 0 means to never retry. The default behavior is to never retry.
min_retry_interval_millis	Optional minimal interval in milliseconds between the start of the failed run and the subsequent retry run. The default behavior is that unsuccessful runs are immediately retried.
retry_on_timeout	Optional policy to specify whether to retry a task when it times out. The default behavior is to not retry on timeout.
run_if	The condition determining whether the task is run once its dependencies have been completed.

job_tasks	<i>Job Tasks</i>
-----------	------------------

Description

Job Tasks

Usage

`job_tasks(...)`

Arguments

... Multiple Instance of tasks [job_task\(\)](#).

See Also

[db_jobs_create\(\)](#), [db_jobs_reset\(\)](#), [db_jobs_update\(\)](#)

libraries	<i>Libraries</i>
-----------	------------------

Description

Libraries

Usage

libraries(...)

Arguments

... Accepts multiple instances of `lib_jar()`, `lib_cran()`, `lib_maven()`, `lib_pypi()`, `lib_whl()`, `lib_egg()`.

Details

Optional list of libraries to be installed on the cluster that executes the task.

See Also

`job_task()`, `lib_jar()`, `lib_cran()`, `lib_maven()`, `lib_pypi()`, `lib_whl()`, `lib_egg()`
Other Task Objects: `condition_task()`, `email_notifications()`, `for_each_task()`, `new_cluster()`, `notebook_task()`, `pipeline_task()`, `python_wheel_task()`, `run_job_task()`, `spark_jar_task()`, `spark_python_task()`, `spark_submit_task()`, `sql_file_task()`, `sql_query_task()`
Other Library Objects: `lib_cran()`, `lib_egg()`, `lib_jar()`, `lib_maven()`, `lib_pypi()`, `lib_whl()`

lib_cran	<i>Cran Library (R)</i>
----------	-------------------------

Description

Cran Library (R)

Usage

lib_cran(package, repo = NULL)

Arguments

package The name of the CRAN package to install.
repo The repository where the package can be found. If not specified, the default CRAN repo is used.

See Also

[libraries\(\)](#)

Other Library Objects: [lib_egg\(\)](#), [lib_jar\(\)](#), [lib_maven\(\)](#), [lib_pypi\(\)](#), [lib_whl\(\)](#), [libraries\(\)](#)

lib_egg	<i>Egg Library (Python)</i>
---------	-----------------------------

Description

Egg Library (Python)

Usage

```
lib_egg(egg)
```

Arguments

egg	URI of the egg to be installed. DBFS and S3 URIs are supported. For example: dbfs:/my/egg or s3://my-bucket/egg. If S3 is used, make sure the cluster has read access on the library. You may need to launch the cluster with an instance profile to access the S3 URI.
-----	---

See Also

[libraries\(\)](#)

Other Library Objects: [lib_cran\(\)](#), [lib_jar\(\)](#), [lib_maven\(\)](#), [lib_pypi\(\)](#), [lib_whl\(\)](#), [libraries\(\)](#)

lib_jar	<i>Jar Library (Scala)</i>
---------	----------------------------

Description

Jar Library (Scala)

Usage

```
lib_jar(jar)
```

Arguments

jar	URI of the JAR to be installed. DBFS and S3 URIs are supported. For example: dbfs:/mnt/databricks/library.jar or s3://my-bucket/library.jar. If S3 is used, make sure the cluster has read access on the library. You may need to launch the cluster with an instance profile to access the S3 URI.
-----	---

See Also[libraries\(\)](#)Other Library Objects: [lib_cran\(\)](#), [lib_egg\(\)](#), [lib_maven\(\)](#), [lib_pypi\(\)](#), [lib_whl\(\)](#), [libraries\(\)](#)

lib_maven*Maven Library (Scala)*

Description

Maven Library (Scala)

Usage

```
lib_maven(coordinates, repo = NULL, exclusions = NULL)
```

Arguments

coordinates	Gradle-style Maven coordinates. For example: org.jsoup:jsoup:1.7.2.
repo	Maven repo to install the Maven package from. If omitted, both Maven Central Repository and Spark Packages are searched.
exclusions	List of dependencies to exclude. For example: list("slf4j:slf4j", "*:hadoop-client"). Maven dependency exclusions.

See Also[libraries\(\)](#)Other Library Objects: [lib_cran\(\)](#), [lib_egg\(\)](#), [lib_jar\(\)](#), [lib_pypi\(\)](#), [lib_whl\(\)](#), [libraries\(\)](#)

lib_pypi*PyPi Library (Python)*

Description

PyPi Library (Python)

Usage

```
lib_pypi(package, repo = NULL)
```

Arguments

package	The name of the PyPI package to install. An optional exact version specification is also supported. Examples: simplejson and simplejson==3.8.0.
repo	The repository where the package can be found. If not specified, the default pip index is used.

See Also

[libraries\(\)](#)

Other Library Objects: [lib_cran\(\)](#), [lib_egg\(\)](#), [lib_jar\(\)](#), [lib_maven\(\)](#), [lib_whl\(\)](#), [libraries\(\)](#)

lib_whl	<i>Wheel Library (Python)</i>
---------	-------------------------------

Description

Wheel Library (Python)

Usage

`lib_whl(whl)`

Arguments

whl	URI of the wheel or zipped wheels to be installed. DBFS and S3 URIs are supported. For example: <code>dbfs:/my/whl</code> or <code>s3://my-bucket/whl</code> . If S3 is used, make sure the cluster has read access on the library. You may need to launch the cluster with an instance profile to access the S3 URI. Also the wheel file name needs to use the correct convention. If zipped wheels are to be installed, the file name suffix should be <code>.wheelhouse.zip</code> .
-----	---

See Also

[libraries\(\)](#)

Other Library Objects: [lib_cran\(\)](#), [lib_egg\(\)](#), [lib_jar\(\)](#), [lib_maven\(\)](#), [lib_pypi\(\)](#), [libraries\(\)](#)

new_cluster	<i>New Cluster</i>
-------------	--------------------

Description

New Cluster

Usage

```

new_cluster(
    num_workers,
    spark_version,
    node_type_id,
    driver_node_type_id = NULL,
    autoscale = NULL,
    cloud_attrs = NULL,
    spark_conf = NULL,
    spark_env_vars = NULL,
    custom_tags = NULL,
    ssh_public_keys = NULL,
    log_conf = NULL,
    init_scripts = NULL,
    enable_elastic_disk = TRUE,
    driver_instance_pool_id = NULL,
    instance_pool_id = NULL,
    kind = c("CLASSIC_PREVIEW"),
    data_security_mode = c("NONE", "SINGLE_USER", "USER_ISOLATION", "LEGACY_TABLE_ACL",
        "LEGACY_PASSTHROUGH", "LEGACY_SINGLE_USER", "LEGACY_SINGLE_USER_STANDARD",
        "DATA_SECURITY_MODE_STANDARD", "DATA_SECURITY_MODE_DEDICATED",
        "DATA_SECURITY_MODE_AUTO")
)

```

Arguments

num_workers	Number of worker nodes that this cluster should have. A cluster has one Spark driver and num_workers executors for a total of num_workers + 1 Spark nodes.
spark_version	The runtime version of the cluster. You can retrieve a list of available runtime versions by using db_cluster_runtime_versions() .
node_type_id	The node type for the worker nodes. db_cluster_list_node_types() can be used to see available node types.
driver_node_type_id	The node type of the Spark driver. This field is optional; if unset, the driver node type will be set as the same value as node_type_id defined above. db_cluster_list_node_types() can be used to see available node types.
autoscale	Instance of cluster_autoscale() .
cloud_attrs	Attributes related to clusters running on specific cloud provider. Defaults to aws_attributes() . Must be one of aws_attributes() , azure_attributes() , gcp_attributes() .
spark_conf	Named list. An object containing a set of optional, user-specified Spark configuration key-value pairs. You can also pass in a string of extra JVM options to the driver and the executors via spark.driver.extraJavaOptions and spark.executor.extraJavaOptions respectively. E.g. list("spark.speculation" = true, "spark.streaming.ui.retainedBatches" = 5).

spark_env_vars	Named list. User-specified environment variable key-value pairs. In order to specify an additional set of SPARK_DAEMON_JAVA_OPTS, we recommend appending them to \$SPARK_DAEMON_JAVA_OPTS as shown in the following example. This ensures that all default Databricks managed environmental variables are included as well. E.g. {"SPARK_DAEMON_JAVA_OPTS": "\$SPARK_DAEMON_JAVA_OPTS -Dspark.shuffle.service.enabled=true"}
custom_tags	Named list. An object containing a set of tags for cluster resources. Databricks tags all cluster resources with these tags in addition to default_tags. Databricks allows at most 45 custom tags.
ssh_public_keys	List. SSH public key contents that will be added to each Spark node in this cluster. The corresponding private keys can be used to login with the user name ubuntu on port 2200. Up to 10 keys can be specified.
log_conf	Instance of <code>cluster_log_conf()</code> .
init_scripts	Instance of <code>init_script_info()</code> .
enable_elastic_disk	When enabled, this cluster will dynamically acquire additional disk space when its Spark workers are running low on disk space.
driver_instance_pool_id	ID of the instance pool to use for the driver node. You must also specify instance_pool_id. Optional.
instance_pool_id	ID of the instance pool to use for cluster nodes. If driver_instance_pool_id is present, instance_pool_id is used for worker nodes only. Otherwise, it is used for both the driver and worker nodes. Optional.
kind	The kind of compute described by this compute specification.
data_security_mode	Data security mode decides what data governance model to use when accessing data from a cluster.

See Also

`job_task()`

Other Task Objects: `condition_task()`, `email_notifications()`, `for_each_task()`, `libraries()`, `notebook_task()`, `pipeline_task()`, `python_wheel_task()`, `run_job_task()`, `spark_jar_task()`, `spark_python_task()`, `spark_submit_task()`, `sql_file_task()`, `sql_query_task()`

notebook_task	<i>Notebook Task</i>
---------------	----------------------

Description

Notebook Task

Usage

notebook_task(notebook_path, base_parameters = NULL)

Arguments

- notebook_path The absolute path of the notebook to be run in the Databricks workspace. This path must begin with a slash.
- base_parameters Named list of base parameters to be used for each run of this job.

Details

If the run is initiated by a call to [db_jobs_run_now\(\)](#) with parameters specified, the two parameters maps are merged. If the same key is specified in base_parameters and in run-now, the value from run-now is used.

Use Task parameter variables to set parameters containing information about job runs.

If the notebook takes a parameter that is not specified in the job’s base_parameters or the run-now override parameters, the default value from the notebook is used.

Retrieve these parameters in a notebook using `dbutils.widgets.get`.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

open_workspace	<i>Connect to Databricks Workspace</i>
----------------	--

Description

Connect to Databricks Workspace

Usage

open_workspace(host = db_host(), token = db_token(), name = NULL)

Arguments

- host Databricks workspace URL, defaults to calling [db_host\(\)](#).
- token Databricks workspace token, defaults to calling [db_token\(\)](#).
- name Desired name to assign the connection

Examples

```
## Not run:
open_workspace(host = db_host(), token = db_token, name = "MyWorkspace")

## End(Not run)
```

pipeline_task	<i>Pipeline Task</i>
---------------	----------------------

Description

Pipeline Task

Usage

```
pipeline_task(pipeline_id)
```

Arguments

pipeline_id The full name of the pipeline task to execute.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

python_wheel_task	<i>Python Wheel Task</i>
-------------------	--------------------------

Description

Python Wheel Task

Usage

```
python_wheel_task(package_name, entry_point = NULL, parameters = list())
```

Arguments

package_name	Name of the package to execute.
entry_point	Named entry point to use, if it does not exist in the metadata of the package it executes the function from the package directly using <code>\$packageName.\$entryPoint()</code> .
parameters	Command-line parameters passed to python wheel task.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

remove_lib_path	<i>Remove Library Path</i>
-----------------	----------------------------

Description

Remove Library Path

Usage

```
remove_lib_path(path, version = FALSE)
```

Arguments

path	Directory to remove from .libPaths() .
version	If TRUE will add the R version string to the end of path before removal.

See Also

[base::.libPaths\(\)](#), [remove_lib_path\(\)](#)

run_job_task	<i>Run Job Task</i>
--------------	---------------------

Description

Run Job Task

Usage

```
run_job_task(job_id, job_parameters, full_refresh = FALSE)
```

Arguments

job_id	ID of the job to trigger.
job_parameters	Named list, job-level parameters used to trigger job.
full_refresh	If the pipeline should perform a full refresh.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

s3_storage_info	<i>S3 Storage Info</i>
-----------------	------------------------

Description

S3 Storage Info

Usage

```
s3_storage_info(
    destination,
    region = NULL,
    endpoint = NULL,
    enable_encryption = FALSE,
    encryption_type = c("sse-s3", "sse-kms"),
    kms_key = NULL,
    canned_acl = NULL
)
```

Arguments

destination	S3 destination. For example: s3://my-bucket/some-prefix. You must configure the cluster with an instance profile and the instance profile must have write access to the destination. You cannot use AWS keys.
region	S3 region. For example: us-west-2. Either region or endpoint must be set. If both are set, endpoint is used.
endpoint	S3 endpoint. For example: https://s3-us-west-2.amazonaws.com. Either region or endpoint must be set. If both are set, endpoint is used.
enable_encryption	Boolean (Default: FALSE). If TRUE Enable server side encryption.
encryption_type	Encryption type, it could be sse-s3 or sse-kms. It is used only when encryption is enabled and the default type is sse-s3.
kms_key	KMS key used if encryption is enabled and encryption type is set to sse-kms.
canned_acl	Set canned access control list. For example: bucket-owner-full-control. If canned_acl is set, the cluster instance profile must have s3:PutObjectAcl permission on the destination bucket and prefix. The full list of possible canned ACLs can be found in docs . By default only the object owner gets full control. If you are using cross account role for writing data, you may want to set bucket-owner-full-control to make bucket owner able to read the logs.

See Also

[cluster_log_conf\(\)](#), [init_script_info\(\)](#)

Other Cluster Log Configuration Objects: [cluster_log_conf\(\)](#), [dbfs_storage_info\(\)](#)

Other Init Script Info Objects: [dbfs_storage_info\(\)](#), [file_storage_info\(\)](#)

show,DatabricksConnection-method
<i>Show method for DatabricksConnection</i>

Description

Show method for DatabricksConnection

Usage

```
## S4 method for signature 'DatabricksConnection'
show(object)
```

Arguments

object	A DatabricksConnection object
--------	-------------------------------

show,DatabricksDriver-method
<i>Show method for DatabricksDriver</i>

Description

Show method for DatabricksDriver

Usage

```
## S4 method for signature 'DatabricksDriver'
show(object)
```

Arguments

object	A DatabricksDriver object
--------	---------------------------

show,DatabricksResult-method
<i>Show method for DatabricksResult</i>

Description

Show method for DatabricksResult

Usage

```
## S4 method for signature 'DatabricksResult'
show(object)
```

Arguments

object A DatabricksResult object

spark_jar_task	<i>Spark Jar Task</i>
----------------	-----------------------

Description

Spark Jar Task

Usage

```
spark_jar_task(main_class_name, parameters = list())
```

Arguments

main_class_name	The full name of the class containing the main method to be executed. This class must be contained in a JAR provided as a library. The code must use SparkContext.getOrCreate to obtain a Spark context; otherwise, runs of the job fail.
parameters	Named list. Parameters passed to the main method. Use Task parameter variables to set parameters containing information about job runs.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

spark_python_task	<i>Spark Python Task</i>
-------------------	--------------------------

Description

Spark Python Task

Usage

```
spark_python_task(python_file, parameters = list())
```

Arguments

python_file	The URI of the Python file to be executed. DBFS and S3 paths are supported.
parameters	List. Command line parameters passed to the Python file. Use Task parameter variables to set parameters containing information about job runs.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

spark_submit_task	<i>Spark Submit Task</i>
-------------------	--------------------------

Description

Spark Submit Task

Usage

```
spark_submit_task(parameters)
```

Arguments

parameters	List. Command-line parameters passed to spark submit. Use Task parameter variables to set parameters containing information about job runs.
------------	---

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [sql_file_task\(\)](#), [sql_query_task\(\)](#)

sql_file_task	<i>SQL File Task</i>
---------------	----------------------

Description

SQL File Task

Usage

sql_file_task(path, warehouse_id, source = NULL, parameters = NULL)

Arguments

path	Path of the SQL file. Must be relative if the source is a remote Git repository and absolute for workspace paths.
warehouse_id	The canonical identifier of the SQL warehouse.
source	Optional location type of the SQL file. When set to WORKSPACE, the SQL file will be retrieved from the local Databricks workspace. When set to GIT, the SQL file will be retrieved from a Git repository defined in git_source() If the value is empty, the task will use GIT if git_source() is defined and WORKSPACE otherwise.
parameters	Named list of paramters to be used for each run of this job.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_query_task\(\)](#)

sql_query_fields.DatabricksConnection
<i>SQL Query Fields for Databricks connections</i>

Description

Generate SQL for field discovery queries optimized for Databricks. This method generates appropriate SQL for discovering table fields.

Usage

```
## S3 method for class 'DatabricksConnection'  
sql_query_fields(con, sql, ...)
```

Arguments

con	DatabricksConnection object
sql	SQL query to discover fields for
...	Additional arguments passed to other methods

Value

SQL object for field discovery

sql_query_save.DatabricksConnection
Create temporary views and tables in Databricks

Description

Create temporary views and tables in Databricks

Usage

```
## S3 method for class 'DatabricksConnection'  
sql_query_save(con, sql, name, temporary = TRUE, ...)
```

Arguments

con	A DatabricksConnection object
sql	SQL query to save as table/view
name	Name for the temporary view or table
temporary	Whether the object should be temporary (default: TRUE)
...	Additional arguments (ignored)

Value

The table/view name (invisibly)

sql_query_task	<i>SQL Query Task</i>
----------------	-----------------------

Description

SQL Query Task

Usage

```
sql_query_task(query_id, warehouse_id, parameters = NULL)
```

Arguments

- query_id The canonical identifier of the SQL query.
- warehouse_id The canonical identifier of the SQL warehouse.
- parameters Named list of paramters to be used for each run of this job.

See Also

Other Task Objects: [condition_task\(\)](#), [email_notifications\(\)](#), [for_each_task\(\)](#), [libraries\(\)](#), [new_cluster\(\)](#), [notebook_task\(\)](#), [pipeline_task\(\)](#), [python_wheel_task\(\)](#), [run_job_task\(\)](#), [spark_jar_task\(\)](#), [spark_python_task\(\)](#), [spark_submit_task\(\)](#), [sql_file_task\(\)](#)

sql_table_analyze.DatabricksConnection
<i>Handle table analysis for Databricks</i>

Description

Handle table analysis for Databricks

Usage

```
## S3 method for class 'DatabricksConnection'  
sql_table_analyze(con, table, ...)
```

Arguments

- con A DatabricksConnection object
- table Table name to analyze
- ... Additional arguments (ignored)

Value

SQL statement for table analysis

wait_for_lib_installs *Wait for Libraries to Install on Databricks Cluster*

Description

Wait for Libraries to Install on Databricks Cluster

Usage

```
wait_for_lib_installs(  
    cluster_id,  
    polling_interval = 5,  
    allow_failures = FALSE,  
    host = db_host(),  
    token = db_token()  
)
```

Arguments

cluster_id	Unique identifier of a Databricks cluster.
polling_interval	Number of seconds to wait between status checks
allow_failures	If FALSE (default) will error if any libraries status is FAILED. When TRUE any FAILED installs will be presented as a warning.
host	Databricks workspace URL, defaults to calling db_host() .
token	Databricks workspace token, defaults to calling db_token() .

Details

Library installs on Databricks clusters are asynchronous, this function allows you to repeatedly check installation status of each library.

Can be used to block any scripts until required dependencies are installed.

See Also

[db_libs_cluster_status\(\)](#)

Index

- * **Access Control Request Objects**
 - access_control_req_group, [8](#)
 - access_control_req_user, [9](#)
- * **Cloud Attributes**
 - aws_attributes, [10](#)
 - azure_attributes, [12](#)
 - gcp_attributes, [190](#)
- * **Cluster Helpers**
 - get_and_start_cluster, [191](#)
 - get_latest_dbr, [193](#)
- * **Cluster Log Configuration Objects**
 - cluster_log_conf, [14](#)
 - dbfs_storage_info, [26](#)
 - s3_storage_info, [228](#)
- * **Cluster Objects**
 - cluster_autoscale, [14](#)
- * **Clusters API**
 - db_cluster_create, [39](#)
 - db_cluster_edit, [43](#)
 - db_cluster_events, [46](#)
 - db_cluster_get, [47](#)
 - db_cluster_list, [48](#)
 - db_cluster_list_node_types, [49](#)
 - db_cluster_list_zones, [50](#)
 - db_cluster_perm_delete, [51](#)
 - db_cluster_pin, [52](#)
 - db_cluster_resize, [53](#)
 - db_cluster_restart, [54](#)
 - db_cluster_runtime_versions, [54](#)
 - db_cluster_start, [55](#)
 - db_cluster_terminate, [56](#)
 - db_cluster_unpin, [57](#)
 - get_and_start_cluster, [191](#)
 - get_latest_dbr, [193](#)
- * **DBFS API**
 - db_dbfs_add_block, [67](#)
 - db_dbfs_close, [68](#)
 - db_dbfs_create, [69](#)
 - db_dbfs_delete, [70](#)
 - db_dbfs_get_status, [71](#)
 - db_dbfs_list, [72](#)
 - db_dbfs_mkdirs, [73](#)
 - db_dbfs_move, [74](#)
 - db_dbfs_put, [75](#)
 - db_dbfs_read, [76](#)
- * **Databricks Authentication Helpers**
 - db_host, [77](#)
 - db_read_netrc, [111](#)
 - db_token, [143](#)
 - db_wsdl, [183](#)
- * **Execution Context API**
 - db_context_command_cancel, [59](#)
 - db_context_command_run, [59](#)
 - db_context_command_run_and_wait, [60](#)
 - db_context_command_status, [61](#)
 - db_context_create, [62](#)
 - db_context_destroy, [63](#)
 - db_context_status, [65](#)
- * **Init Script Info Objects**
 - dbfs_storage_info, [26](#)
 - file_storage_info, [189](#)
 - s3_storage_info, [228](#)
- * **Jobs API**
 - db_jobs_create, [78](#)
 - db_jobs_delete, [79](#)
 - db_jobs_get, [80](#)
 - db_jobs_list, [81](#)
 - db_jobs_repair_run, [82](#)
 - db_jobs_reset, [83](#)
 - db_jobs_run_now, [91](#)
 - db_jobs_runs_cancel, [85](#)
 - db_jobs_runs_delete, [86](#)
 - db_jobs_runs_export, [86](#)
 - db_jobs_runs_get, [87](#)
 - db_jobs_runs_get_output, [88](#)
 - db_jobs_runs_list, [88](#)
 - db_jobs_runs_submit, [90](#)

- db_jobs_update, 92
- * **Libraries API**
 - db_libs_all_cluster_statuses, 93
 - db_libs_cluster_status, 94
 - db_libs_install, 95
 - db_libs_uninstall, 96
- * **Library Objects**
 - lib_cran, 219
 - lib_egg, 220
 - lib_jar, 220
 - lib_maven, 221
 - lib_pypi, 221
 - lib_whl, 222
 - libraries, 219
- * **Model Registry API**
 - db_mlflow_model_approve_transition_req, 97
 - db_mlflow_model_delete_transition_req, 98
 - db_mlflow_model_open_transition_reqs, 99
 - db_mlflow_model_reject_transition_req, 99
 - db_mlflow_model_transition_req, 100
 - db_mlflow_model_transition_stage, 101
 - db_mlflow_model_version_comment, 103
 - db_mlflow_model_version_comment_delete, 104
 - db_mlflow_model_version_comment_edit, 104
 - db_mlflow_registered_model_details, 105
- * **Repos API**
 - db_repo_create, 113
 - db_repo_delete, 113
 - db_repo_get, 114
 - db_repo_get_all, 115
 - db_repo_update, 116
- * **Request Helpers**
 - db_perform_request, 106
 - db_req_error_body, 118
 - db_request, 117
 - db_request_json, 117
- * **SQL Execution APIs**
 - db_sql_exec_cancel, 128
 - db_sql_exec_query, 130
 - db_sql_exec_result, 132
 - db_sql_exec_status, 133
- * **SQL Queries API**
 - db_query_create, 107
 - db_query_delete, 108
 - db_query_get, 109
 - db_query_list, 109
 - db_query_update, 110
- * **SQL Query History API**
 - db_sql_query_history, 136
- * **Secrets API**
 - db_secrets_delete, 118
 - db_secrets_list, 119
 - db_secrets_put, 120
 - db_secrets_scope_acl_delete, 121
 - db_secrets_scope_acl_get, 122
 - db_secrets_scope_acl_list, 123
 - db_secrets_scope_acl_put, 124
 - db_secrets_scope_create, 125
 - db_secrets_scope_delete, 127
 - db_secrets_scope_list_all, 128
- * **Task Objects**
 - condition_task, 15
 - email_notifications, 187
 - for_each_task, 189
 - libraries, 219
 - new_cluster, 222
 - notebook_task, 224
 - pipeline_task, 226
 - python_wheel_task, 226
 - run_job_task, 227
 - spark_jar_task, 230
 - spark_python_task, 231
 - spark_submit_task, 231
 - sql_file_task, 232
 - sql_query_task, 234
- * **Unity Catalog Management**
 - db_uc_catalogs_get, 144
 - db_uc_catalogs_list, 145
 - db_uc_schemas_get, 146
 - db_uc_schemas_list, 147
- * **Unity Catalog Table Management**
 - db_uc_tables_delete, 148
 - db_uc_tables_exists, 149
 - db_uc_tables_get, 150
 - db_uc_tables_list, 151
 - db_uc_tables_summaries, 152

*** Unity Catalog Volume Management**

db_uc_volumes_create, 153
 db_uc_volumes_delete, 154
 db_uc_volumes_get, 155
 db_uc_volumes_list, 156
 db_uc_volumes_update, 157

*** Vector Search API**

db_vs_endpoints_create, 165
 db_vs_endpoints_delete, 166
 db_vs_endpoints_get, 167
 db_vs_endpoints_list, 167
 db_vs_indexes_create, 168
 db_vs_indexes_delete, 169
 db_vs_indexes_delete_data, 170
 db_vs_indexes_get, 171
 db_vs_indexes_list, 171
 db_vs_indexes_query, 172
 db_vs_indexes_query_next_page, 174
 db_vs_indexes_scan, 175
 db_vs_indexes_sync, 176
 db_vs_indexes_upsert_data, 177
 delta_sync_index_spec, 184
 direct_access_index_spec, 185
 embedding_source_column, 188
 embedding_vector_column, 188

*** Volumes FileSystem API**

db_volume_delete, 158
 db_volume_dir_create, 159
 db_volume_dir_delete, 159
 db_volume_dir_exists, 160
 db_volume_file_exists, 161
 db_volume_list, 162
 db_volume_read, 162
 db_volume_upload_dir, 163
 db_volume_write, 164

*** Warehouse API**

db_sql_global_warehouse_get, 134
 db_sql_warehouse_create, 137
 db_sql_warehouse_delete, 138
 db_sql_warehouse_edit, 139
 db_sql_warehouse_get, 141
 db_sql_warehouse_list, 141
 db_sql_warehouse_start, 142
 db_sql_warehouse_stop, 143
 get_and_start_warehouse, 192

*** Warehouse Helpers**

get_and_start_warehouse, 192

*** Workspace API**

db_workspace_delete, 177
 db_workspace_export, 178
 db_workspace_get_status, 180
 db_workspace_import, 180
 db_workspace_list, 182
 db_workspace_mkdirs, 182
 .libPaths(), 227

access_control_req_group, 8, 9
 access_control_req_group(), 8, 79
 access_control_req_user, 9, 9
 access_control_req_user(), 8, 79
 access_control_request, 8
 access_control_request(), 9, 79, 84, 90, 93

add_lib_path, 10

arrow::Table, 135

aws_attributes, 10, 13, 190

aws_attributes(), 40, 44, 223

azure_attributes, 12, 12, 190

azure_attributes(), 40, 44, 223

base::libPaths(), 10, 227

base::as.raw(), 68

close_workspace, 13

cluster_autoscale, 14

cluster_autoscale(), 40, 44, 53, 223

cluster_log_conf, 14, 26, 228

cluster_log_conf(), 26, 41, 45, 224, 228

condition_task, 15, 187, 190, 219, 224–227, 230–232, 234

copy_to.DatabricksConnection, 16

cron_schedule, 17

cron_schedule(), 78, 79, 84, 92

databricks-dbi, 17

databricks-dbplyr, 17

DatabricksConnection-class, 18

DatabricksDriver-class, 18

DatabricksResult-class, 18

DatabricksSQL, 18

db_cluster_action, 39

db_cluster_create, 39, 46–58, 191, 193

db_cluster_create(), 12–14, 56, 187, 190, 195

db_cluster_delete, 42

db_cluster_edit, 42, 43, 47–58, 191, 193

db_cluster_edit(), 12–14, 187, 190, 195

- `db_cluster_events`, [42](#), [46](#), [46](#), [48–58](#), [191](#), [193](#)
- `db_cluster_get`, [42](#), [46](#), [47](#), [47](#), [49–58](#), [191](#), [193](#)
- `db_cluster_get()`, [42](#), [191](#)
- `db_cluster_list`, [42](#), [46–48](#), [48](#), [50–58](#), [191](#), [193](#)
- `db_cluster_list()`, [52](#), [58](#)
- `db_cluster_list_node_types`, [42](#), [46–49](#), [49](#), [50–58](#), [191](#), [193](#)
- `db_cluster_list_node_types()`, [40](#), [44](#), [223](#)
- `db_cluster_list_zones`, [42](#), [46–50](#), [50](#), [51–58](#), [191](#), [193](#)
- `db_cluster_perm_delete`, [42](#), [46–50](#), [51](#), [52–58](#), [191](#), [193](#)
- `db_cluster_pin`, [42](#), [46–51](#), [52](#), [53–58](#), [191](#), [193](#)
- `db_cluster_resize`, [42](#), [46–52](#), [53](#), [54–58](#), [191](#), [193](#)
- `db_cluster_restart`, [42](#), [46–53](#), [54](#), [55–58](#), [191](#), [193](#)
- `db_cluster_runtime_versions`, [42](#), [46–54](#), [54](#), [56–58](#), [191](#), [193](#)
- `db_cluster_runtime_versions()`, [40](#), [44](#), [223](#)
- `db_cluster_start`, [42](#), [46–55](#), [55](#), [57](#), [58](#), [191](#), [193](#)
- `db_cluster_start()`, [191](#)
- `db_cluster_terminate`, [42](#), [46–56](#), [56](#), [58](#), [191](#), [193](#)
- `db_cluster_unpin`, [42](#), [46–57](#), [57](#), [191](#), [193](#)
- `db_collect.DatabricksConnection`, [58](#)
- `db_context_command_cancel`, [59](#), [60–63](#), [65](#)
- `db_context_command_parse`, [59–63](#), [65](#)
- `db_context_command_run`, [59](#), [59](#), [61–63](#), [65](#)
- `db_context_command_run_and_wait`, [59](#), [60](#), [60](#), [62](#), [63](#), [65](#)
- `db_context_command_status`, [59–61](#), [61](#), [63](#), [65](#)
- `db_context_create`, [59–62](#), [62](#), [63](#), [65](#)
- `db_context_destroy`, [59–63](#), [63](#), [65](#)
- `db_context_manager`, [64](#)
- `db_context_status`, [59–63](#), [65](#)
- `db_current_cloud`, [66](#)
- `db_current_user`, [66](#)
- `db_current_workspace_id`, [67](#)
- `db_dbfs_add_block`, [67](#), [69–76](#)
- `db_dbfs_add_block()`, [68–70](#)
- `db_dbfs_close`, [68](#), [68](#), [70–76](#)
- `db_dbfs_close()`, [68–70](#)
- `db_dbfs_create`, [68](#), [69](#), [69](#), [71–76](#)
- `db_dbfs_create()`, [68–70](#)
- `db_dbfs_delete`, [68–70](#), [70](#), [72–76](#)
- `db_dbfs_get_status`, [68–71](#), [71](#), [72–76](#)
- `db_dbfs_list`, [68–72](#), [72](#), [73–76](#)
- `db_dbfs_mkdirs`, [68–72](#), [73](#), [74–76](#)
- `db_dbfs_move`, [68–73](#), [74](#), [75](#), [76](#)
- `db_dbfs_put`, [68–74](#), [75](#), [76](#)
- `db_dbfs_read`, [68–75](#), [76](#)
- `db_host`, [77](#), [112](#), [144](#), [184](#)
- `db_host()`, [13](#), [39](#), [42](#), [43](#), [45](#), [47–57](#), [59–76](#), [79–81](#), [83–91](#), [93–106](#), [108–117](#), [119](#), [120](#), [122–124](#), [126–136](#), [138–150](#), [152–183](#), [191–193](#), [225](#), [235](#)
- `db_jobs_create`, [78](#), [80](#), [81](#), [83–89](#), [91](#), [93](#)
- `db_jobs_create()`, [8](#), [17](#), [83](#), [93](#), [217](#), [218](#)
- `db_jobs_delete`, [79](#), [79](#), [80](#), [81](#), [83–89](#), [91](#), [93](#)
- `db_jobs_get`, [79](#), [80](#), [80](#), [81](#), [83–89](#), [91](#), [93](#)
- `db_jobs_list`, [79](#), [80](#), [81](#), [83–89](#), [91](#), [93](#)
- `db_jobs_repair_run`, [79–81](#), [82](#), [84–89](#), [91](#), [93](#)
- `db_jobs_reset`, [79–81](#), [83](#), [83](#), [85–89](#), [91](#), [93](#)
- `db_jobs_reset()`, [8](#), [17](#), [217](#), [218](#)
- `db_jobs_run_now`, [79–81](#), [83–89](#), [91](#), [91](#), [93](#)
- `db_jobs_run_now()`, [225](#)
- `db_jobs_runs_cancel`, [79–81](#), [83](#), [84](#), [85](#), [86–89](#), [91](#), [93](#)
- `db_jobs_runs_delete`, [79–81](#), [83–85](#), [86](#), [87–89](#), [91](#), [93](#)
- `db_jobs_runs_export`, [79–81](#), [83–86](#), [86](#), [87–89](#), [91](#), [93](#)
- `db_jobs_runs_get`, [79–81](#), [83–87](#), [87](#), [88](#), [89](#), [91](#), [93](#)
- `db_jobs_runs_get_output`, [79–81](#), [83–87](#), [88](#), [89](#), [91](#), [93](#)
- `db_jobs_runs_list`, [79–81](#), [83–88](#), [88](#), [91](#), [93](#)
- `db_jobs_runs_submit`, [79–81](#), [83–89](#), [90](#), [91](#), [93](#)
- `db_jobs_update`, [79–81](#), [83–89](#), [91](#), [92](#)
- `db_jobs_update()`, [8](#), [17](#), [217](#), [218](#)
- `db_libs_all_cluster_statuses`, [93](#), [95](#), [96](#)
- `db_libs_cluster_status`, [94](#), [94](#), [96](#)
- `db_libs_cluster_status()`, [235](#)

- db_libs_install, [94](#), [95](#), [95](#), [96](#)
- db_libs_uninstall, [94–96](#), [96](#)
- db_mlflow_model_approve_transition_req, [97](#), [98–106](#)
- db_mlflow_model_delete_transition_req, [97](#), [98](#), [99–106](#)
- db_mlflow_model_open_transition_reqs, [97](#), [98](#), [99](#), [100–106](#)
- db_mlflow_model_reject_transition_req, [97–99](#), [99](#), [101–106](#)
- db_mlflow_model_transition_req, [97–100](#), [100](#), [102–106](#)
- db_mlflow_model_transition_stage, [97–101](#), [101](#), [103–106](#)
- db_mlflow_model_version_comment, [97–102](#), [103](#), [104–106](#)
- db_mlflow_model_version_comment_delete, [97–103](#), [104](#), [105](#), [106](#)
- db_mlflow_model_version_comment_edit, [97–104](#), [104](#), [106](#)
- db_mlflow_registered_model_details, [97–105](#), [105](#)
- db_perform_request, [106](#), [117](#), [118](#)
- db_query_create, [107](#), [108–111](#)
- db_query_delete, [108](#), [108](#), [109–111](#)
- db_query_get, [108](#), [109](#), [110](#), [111](#)
- db_query_list, [108](#), [109](#), [109](#), [111](#)
- db_query_update, [108–110](#), [110](#)
- db_read_netrc, [77](#), [111](#), [144](#), [184](#)
- db_repl, [112](#)
- db_repo_create, [113](#), [114–116](#)
- db_repo_delete, [113](#), [113](#), [115](#), [116](#)
- db_repo_get, [113](#), [114](#), [114](#), [115](#), [116](#)
- db_repo_get_all, [113–115](#), [115](#), [116](#)
- db_repo_update, [113–115](#), [116](#)
- db_req_error_body, [106](#), [117](#), [118](#), [118](#)
- db_request, [106](#), [117](#), [118](#)
- db_request(), [117](#)
- db_request_json, [106](#), [117](#), [117](#), [118](#)
- db_secrets_delete, [118](#), [120–128](#)
- db_secrets_list, [119](#), [119](#), [121–128](#)
- db_secrets_put, [119](#), [120](#), [120](#), [122–128](#)
- db_secrets_scope_acl_delete, [119–121](#), [121](#), [123–128](#)
- db_secrets_scope_acl_get, [119–122](#), [122](#), [124–128](#)
- db_secrets_scope_acl_list, [119–123](#), [123](#), [125–128](#)
- db_secrets_scope_acl_put, [119–124](#), [124](#), [126–128](#)
- db_secrets_scope_create, [119–125](#), [125](#), [127](#), [128](#)
- db_secrets_scope_delete, [119–126](#), [127](#), [128](#)
- db_secrets_scope_list_all, [119–127](#), [128](#)
- db_sql_exec_cancel, [128](#), [132](#), [133](#)
- db_sql_exec_poll_for_success, [129](#)
- db_sql_exec_query, [129](#), [130](#), [133](#)
- db_sql_exec_result, [129](#), [132](#), [132](#), [133](#)
- db_sql_exec_result(), [132](#)
- db_sql_exec_status, [129](#), [132](#), [133](#), [133](#)
- db_sql_exec_status(), [131](#), [132](#)
- db_sql_global_warehouse_get, [134](#), [138–143](#), [192](#)
- db_sql_query, [134](#)
- db_sql_query_history, [136](#)
- db_sql_warehouse_create, [134](#), [137](#), [139–143](#), [192](#)
- db_sql_warehouse_delete, [134](#), [138](#), [138](#), [140–143](#), [192](#)
- db_sql_warehouse_edit, [134](#), [138](#), [139](#), [139](#), [141–143](#), [192](#)
- db_sql_warehouse_get, [134](#), [138–140](#), [141](#), [142](#), [143](#), [192](#)
- db_sql_warehouse_get(), [192](#)
- db_sql_warehouse_list, [134](#), [138–141](#), [141](#), [142](#), [143](#), [192](#)
- db_sql_warehouse_start, [134](#), [138–142](#), [142](#), [143](#), [192](#)
- db_sql_warehouse_start(), [192](#)
- db_sql_warehouse_stop, [134](#), [138–142](#), [143](#), [192](#)
- db_token, [77](#), [112](#), [143](#), [184](#)
- db_token(), [39](#), [42](#), [43](#), [45](#), [47–57](#), [59–76](#), [79–81](#), [83–91](#), [93–106](#), [108–117](#), [119](#), [120](#), [122–124](#), [126–136](#), [138–150](#), [152–183](#), [191–193](#), [225](#), [235](#)
- db_uc_catalogs_get, [144](#), [145–147](#)
- db_uc_catalogs_list, [145](#), [145](#), [146](#), [147](#)
- db_uc_schemas_get, [145](#), [146](#), [147](#)
- db_uc_schemas_list, [145](#), [146](#), [147](#)
- db_uc_tables_delete, [148](#), [149](#), [151–153](#)
- db_uc_tables_exists, [148](#), [149](#), [151–153](#)
- db_uc_tables_get, [148](#), [149](#), [150](#), [152](#), [153](#)
- db_uc_tables_list, [148](#), [149](#), [151](#), [151](#), [153](#)

db_uc_tables_summaries, [148](#), [149](#), [151](#),
[152](#), [152](#)
 db_uc_volumes_create, [153](#), [155](#)–[158](#)
 db_uc_volumes_delete, [154](#), [154](#), [156](#)–[158](#)
 db_uc_volumes_get, [154](#), [155](#), [155](#), [157](#), [158](#)
 db_uc_volumes_list, [154](#)–[156](#), [156](#), [158](#)
 db_uc_volumes_update, [154](#)–[157](#), [157](#)
 db_volume_delete, [158](#), [159](#)–[165](#)
 db_volume_dir_create, [158](#), [159](#), [160](#)–[165](#)
 db_volume_dir_delete, [158](#), [159](#), [159](#),
[161](#)–[165](#)
 db_volume_dir_exists, [158](#)–[160](#), [160](#),
[161](#)–[165](#)
 db_volume_file_exists, [158](#)–[161](#), [161](#),
[162](#)–[165](#)
 db_volume_list, [158](#)–[161](#), [162](#), [163](#)–[165](#)
 db_volume_read, [158](#)–[162](#), [162](#), [164](#), [165](#)
 db_volume_upload_dir, [158](#)–[163](#), [163](#), [165](#)
 db_volume_write, [158](#)–[164](#), [164](#)
 db_vs_endpoints_create, [165](#), [166](#)–[177](#),
[185](#), [186](#), [188](#), [189](#)
 db_vs_endpoints_delete, [166](#), [166](#),
[167](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_endpoints_get, [166](#), [167](#), [168](#)–[177](#),
[185](#), [186](#), [188](#), [189](#)
 db_vs_endpoints_list, [166](#), [167](#), [167](#),
[169](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_create, [166](#)–[168](#), [168](#),
[170](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_create(), [185](#), [186](#)
 db_vs_indexes_delete, [166](#)–[169](#), [169](#),
[170](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_delete_data, [166](#)–[170](#), [170](#),
[171](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_get, [166](#)–[170](#), [171](#), [172](#)–[177](#),
[185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_list, [166](#)–[171](#), [171](#),
[173](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_query, [166](#)–[172](#), [172](#),
[174](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_query_next_page, [166](#)–[173](#),
[174](#), [175](#)–[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_scan, [166](#)–[174](#), [175](#), [176](#),
[177](#), [185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_sync, [166](#)–[175](#), [176](#), [177](#),
[185](#), [186](#), [188](#), [189](#)
 db_vs_indexes_upsert_data, [166](#)–[176](#), [177](#),
[185](#), [186](#), [188](#), [189](#)

db_workspace_delete, [177](#), [179](#)–[183](#)
 db_workspace_export, [178](#), [178](#), [180](#)–[183](#)
 db_workspace_get_status, [178](#), [179](#), [180](#),
[181](#)–[183](#)
 db_workspace_import, [178](#)–[180](#), [180](#), [182](#),
[183](#)
 db_workspace_list, [178](#)–[181](#), [182](#), [183](#)
 db_workspace_mkdirs, [178](#)–[182](#), [182](#)
 db_wsids, [77](#), [112](#), [144](#), [183](#)
 dbAppendTable, DatabricksConnection, character, data.frame-me
[19](#)
 dbAppendTable, DatabricksConnection, Id, data.frame-method,
[19](#)
 dbBegin, DatabricksConnection-method,
[20](#)
 dbClearResult, DatabricksResult-method,
[20](#)
 dbColumnInfo, DatabricksResult-method,
[21](#)
 dbCommit, DatabricksConnection-method,
[21](#)
 dbConnect, DatabricksDriver-method, [22](#)
 dbDataType, DatabricksConnection-method,
[23](#)
 dbDisconnect, DatabricksConnection-method,
[23](#)
 dbExecute, DatabricksConnection, character-method,
[24](#)
 dbExistsTable, DatabricksConnection, AsIs-method,
[24](#)
 dbExistsTable, DatabricksConnection, character-method,
[25](#)
 dbExistsTable, DatabricksConnection, Id-method,
[25](#)
 dbFetch, DatabricksResult-method, [26](#)
 dbfs_storage_info, [15](#), [26](#), [189](#), [228](#)
 dbfs_storage_info(), [14](#), [194](#)
 dbGetInfo, DatabricksConnection-method,
[27](#)
 dbGetQuery, DatabricksConnection, character-method,
[27](#)
 dbGetRowCount, DatabricksResult-method,
[28](#)
 dbGetRowsAffected, DatabricksResult-method,
[29](#)
 dbGetStatement, DatabricksResult-method,
[29](#)
 dbHasCompleted, DatabricksResult-method,

- 30
- dbIsValid, DatabricksConnection-method, 30
- dbListFields, DatabricksConnection, AsIs-method, 31
- dbListFields, DatabricksConnection, character-method, 31
- dbListTables, DatabricksConnection-method, 32
- dbplyr_edition.DatabricksConnection, 32
- dbQuoteIdentifier, DatabricksConnection, character-method, 33
- dbQuoteIdentifier, DatabricksConnection, Id-method, 33
- dbQuoteIdentifier, DatabricksConnection, SQL-method, 34
- dbRollback, DatabricksConnection-method, 34
- dbSendQuery, DatabricksConnection, character-method, 35
- dbSendStatement, DatabricksConnection, character-method, 35
- dbWriteTable, DatabricksConnection, AsIs, data.frame-method, 36
- dbWriteTable, DatabricksConnection, character, data.frame-method, 37
- dbWriteTable, DatabricksConnection, Id, data.frame-method, 38
- delta_sync_index_spec, 166–177, 184, 186, 188, 189
- delta_sync_index_spec(), 169
- direct_access_index_spec, 166–177, 185, 188, 189
- direct_access_index_spec(), 169
- docker_image, 186
- docker_image(), 41, 45
- email_notifications, 15, 187, 190, 218, 219, 224–227, 230–232, 234
- email_notifications(), 78, 79, 84, 92
- embedding_source_column, 166–177, 185, 186, 188, 189
- embedding_source_column(), 184, 185
- embedding_vector_column, 166–177, 185, 186, 188, 189
- embedding_vector_column(), 184, 185
- file_storage_info, 26, 189, 228
- file_storage_info(), 194
- for_each_task, 15, 187, 189, 219, 224–227, 230–232, 234
- gcp_attributes, 12, 13, 190
- get_attributes(), 40, 44, 223
- get_and_start_cluster, 42, 46–58, 191, 193
- get_and_start_warehouse, 134, 138–143, 192
- get_latest_dbr, 42, 46–58, 191, 193
- git_method, 194
- git_source(), 79, 84, 90, 93, 232
- httr2::req_body_json(), 117
- httr2::req_method(), 117
- httr2::resp_body_json(), 106
- in_databricks_nb, 195
- init_script_info, 194
- init_script_info(), 26, 41, 44, 189, 224, 228
- is.access_control_req_group, 196
- is.access_control_req_user, 196
- is.access_control_request, 195
- is.aws_attributes, 197
- is.azure_attributes, 197
- is.cluster_autoscale, 198
- is.cluster_log_conf, 198
- is.condition_task, 199
- is.cron_schedule, 199
- is.dbfs_storage_info, 200
- is.delta_sync_index, 200
- is.direct_access_index, 201
- is.docker_image, 201
- is.email_notifications, 202
- is.embedding_source_column, 202
- is.embedding_vector_column, 203
- is.file_storage_info, 203
- is.for_each_task, 204
- is.gcp_attributes, 204
- is.git_source, 205
- is.init_script_info, 205
- is.job_task, 206
- is.lib_cran, 207
- is.lib_egg, 208
- is.lib_jar, 208
- is.lib_maven, 209
- is.lib_pypi, 209

[is.lib_whl](#), 210
[is.libraries](#), 206
[is.library](#), 207
[is.new_cluster](#), 210
[is.notebook_task](#), 211
[is.pipeline_task](#), 211
[is.python_wheel_task](#), 212
[is.run_job_task](#), 212
[is.s3_storage_info](#), 213
[is.spark_jar_task](#), 213
[is.spark_python_task](#), 214
[is.spark_submit_task](#), 214
[is.sql_file_task](#), 215
[is.sql_query_task](#), 215
[is.valid_task_type](#), 216
[is.vector_search_index_spec](#), 216

[job_task](#), 217
[job_task\(\)](#), 79, 187, 190, 218, 219, 224
[job_tasks](#), 218
[job_tasks\(\)](#), 78, 79, 84, 90, 92

[lib_cran](#), 219, 219, 220–222
[lib_cran\(\)](#), 96, 219
[lib_egg](#), 219, 220, 220, 221, 222
[lib_egg\(\)](#), 96, 219
[lib_jar](#), 219, 220, 220, 221, 222
[lib_jar\(\)](#), 96, 219
[lib_maven](#), 219–221, 221, 222
[lib_maven\(\)](#), 96, 219
[lib_pypi](#), 219–221, 221, 222
[lib_pypi\(\)](#), 96, 219
[lib_whl](#), 219–222, 222
[lib_whl\(\)](#), 96, 219
[libraries](#), 15, 187, 190, 219, 220–222, 224–227, 230–232, 234
[libraries\(\)](#), 95, 96, 218, 220–222

[new_cluster](#), 15, 187, 190, 219, 222, 225–227, 230–232, 234
[new_cluster\(\)](#), 78, 84, 90, 92, 217
[notebook_task](#), 15, 187, 190, 219, 224, 224, 226, 227, 230–232, 234
[notebook_task\(\)](#), 217

[open_workspace](#), 225

[pipeline_task](#), 15, 187, 190, 219, 224, 225, 226, 227, 230–232, 234
[pipeline_task\(\)](#), 217
[python_wheel_task](#), 15, 187, 190, 219, 224–226, 226, 227, 230–232, 234
[python_wheel_task\(\)](#), 217

[remove_lib_path](#), 227
[remove_lib_path\(\)](#), 10, 227
[run_job_task](#), 15, 187, 190, 219, 224–227, 227, 230–232, 234

[s3_storage_info](#), 15, 26, 189, 228
[s3_storage_info\(\)](#), 14, 194
[show, DatabricksConnection-method](#), 229
[show, DatabricksDriver-method](#), 229
[show, DatabricksResult-method](#), 230
[spark_jar_task](#), 15, 187, 190, 219, 224–227, 230, 231, 232, 234
[spark_jar_task\(\)](#), 217
[spark_python_task](#), 15, 187, 190, 219, 224–227, 230, 231, 231, 232, 234
[spark_python_task\(\)](#), 217
[spark_submit_task](#), 15, 187, 190, 219, 224–227, 230, 231, 231, 232, 234
[spark_submit_task\(\)](#), 217
[sql_file_task](#), 15, 187, 190, 219, 224–227, 230, 231, 232, 234
[sql_query_fields.DatabricksConnection](#), 232
[sql_query_save.DatabricksConnection](#), 233
[sql_query_task](#), 15, 187, 190, 219, 224–227, 230–232, 234
[sql_table_analyze.DatabricksConnection](#), 234

[tibble::tibble](#), 135

[wait_for_lib_installs](#), 235
[wait_for_lib_installs\(\)](#), 95